



Diesel Recovery Emergency Fuel Treatment

DRC55



09543

Part No. 09543

NET WEIGHT 355 lbs. (161.4 kg)



DANGER

Flammable liquid and vapor. May be fatal if swallowed and enters airways. May cause drowsiness or dizziness.

PRECAUTIONARY STATEMENTS

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing mist or vapor. Wear protective gloves/protective clothing/eye protection/face protection. Store in a well-ventilated place. Keep cool. Do not store container above 100 °F/38 °C. Store locked up. Dispose of contents/container in accordance with local/regional/national regulations. In case of fire: Use appropriate media to extinguish.

This diesel fuel additive complies with the federal ultra-low sulfur content requirements for use in all diesel motor vehicles and non-road engines.

HEALTH	1*	REACTIVITY	0
FLAMMABILITY	2	PERSONAL PROTECTION	B

HAZARD: MINIMAL=0 SEVERE=4

Contains Stoddard solvent (8052-41-3), Heavy aromatic solvent naphtha (64742-94-5), 1,2,4-Trimethylbenzene (95-63-6) and Naphthalene (91-20-3).

©2015 Amsoil
Superior, WI 54886
715-392-7101
www.Amsoil.com
15A CRC#673C
Made in U.S.A.
FOR EMERGENCIES
CALL CHEMTREC
1-800-424-9300

Batch No.:
Date Code:

FIRST AID

If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell.

This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. For additional information, consult SDS for this product.

DIRECTIONS: Read entire label before using this product.

1. Remove the existing fuel filter or obtain a new fuel filter.
2. Fill fuel filter with AMSOIL Diesel Recovery Emergency Fuel Treatment.
3. Reinstall fuel filter.
4. Start the engine and allow the fuel system to circulate until full power has been restored to the engine.

TREAT RATE: One gallon of AMSOIL Diesel Recovery Emergency Fuel Treatment to every 128 gallons of fuel (one quart treats 32 gallons of fuel). Additional treatment may be required if equipped with larger fuel tanks.