

FOR INSTITUTIONAL, COMMERCIAL, AND INDUSTRIAL USE

MSDS: Before using this product, read the MSDS which contains more detailed precautionary measures, handling instructions and emergency procedures.

SUPERIOR LUBRICANT THAT PREVENTS FRICTION AND WEAR. THIS LONG-LASTING, ODORLESS, NON-DRIP SPRAY IS SAFE ON MOST PLASTICS. USE ON GARAGE OR OVERHEAD DOORS, HINGES AND PINS, CABLES, SPRINGS, DOOR TRACKS AND CHAINS, BEARINGS AND BUSHINGS, DOCK PARTS, HOLD-DOWNS, ROLLERS, AND TOE GUARDS. IT'S GREAT IN A VARIETY OF APPLICATIONS WHERE A HIGH QUALITY LUBRICANT IS NEEDED.

DIRECTIONS: Read entire label before using this product. Spray evenly on tracks, hinges, and door rollers. Repeat application when necessary.

FIRST AID: ***Inhalation:*** Remove to fresh air. If not breathing, give artificial respiration. Contact a physician immediately. ***Ingestion:*** Call physician immediately. Do **NOT** induce vomiting. Ingestion of aerosols may result in vomiting which could cause aspiration pneumonitis. ***Eyes:*** Immediately flush eyes with plenty of water for at least 15 minutes lifting upper and lower lids. Get prompt medical attention. ***Skin:*** Remove contaminated clothing and wash affected area with soap and water. Call a physician if irritation persists. Wash contaminated clothing prior to re-use.

WARNING: Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120° F (49° C) as container may burst. Chemical contact with flames or extremely hot surfaces can cause ignition, vapor decomposition and toxic gas. Avoid prolonged exposure to sunlight. Use with adequate ventilation. KEEP OUT OF REACH OF CHILDREN.

CONTENTS (CAS No.): White Mineral Oil 8042-47-5, Hydrocarbon Propellant 68476-86-8.

MEDICAL EMERGENCY: 24 HOURS 1-800-424-9300 PRODUCT #09578

HMSI® INDEX:

0=MINIMAL 1=SLIGHT
2=MODERATE 3=SERIOUS 4=SEVERE

PERSONAL PROTECTION INDEX:

GLASSES AND GLOVES
per OSHA 29 CFR 1910.133

Made in USA

Manufactured for

CROWN

Crown Equipment Corporation New Bremen, OH 45869
crown.com

HEALTH	0
FLAMMABILITY	1
REACTIVITY	0
PERSONAL PROTECTION	B

*= CHRONIC

CROWN



INTEGRITY

Parts
SYSTEM®

HEAVY DUTY INDUSTRIAL

dock & door lube

- PREVENTS FRICTION AND WEAR
- NO DRIPPING • LONG-LASTING • ODORLESS
- SAFE ON MOST PLASTICS



PRODUCT #
09578

NET WT. 12 OZ. (340 GRAMS)

WARNING!
CONTENTS UNDER PRESSURE.
READ CAREFULLY OTHER CAUTIONS ON BACK PANEL.