

Multi-Purpose Lubricant

Please read entire label before using this product. Do not apply while equipment is energized.

Stops Squeaks: CARQUEST Multi-Purpose Lubricant silences annoying squeaks and squeals, reduces friction, and leaves a transparent film that guards against corrosion.

DIRECTIONS: Spray directly into mechanism. No need for disassembly.

Protects Metals: CARQUEST Multi-Purpose Lubricant seals out rust and corrosion and keeps working to protect tools, equipment and all metals.

DIRECTIONS: Spray light, even film over entire surface.

Frees Rusted Parts: CARQUEST Multi-Purpose Lubricant penetrates quickly into threads, cracks and crevices to make tough-to-budge lugs, nuts, bolts and fasteners slip right off.

DIRECTIONS: Spray liberally and allow to run off.

Starts Wet Engines: CARQUEST Multi-Purpose Lubricant drives moisture out of wet electrical systems and keeps it out.

DIRECTIONS: Remove distributor cap and spray directly into distributor. Then spray a light coating over the entire electrical system.

WARNING: Contains petroleum distillates 64742-47-8 & 64741-88-4, butyl stearate 123-95-5, carbon dioxide 124-38-9 and petrolatum 8009-03-8. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F. Exposure to high temperature may cause can to burst. Do not place in direct sunlight. Product is flammable and should be kept from all flames and other ignition sources. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. Overexposure to liquid or vapors can cause eye and skin irritation, irritation to upper respiratory tract, and central nervous system effects such as headache, dizziness, drowsiness or confusion. Product may pose an aspiration hazard if swallowed. Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. Vapors are heavier than air and can accumulate in low areas. If you experience any symptoms listed on this label, increase ventilation or leave the area. **FIRST AID:** In case of eye or skin contact, flush with water for 15 minutes. If swallowed, DO NOT induce vomiting. If too much is breathed, remove to fresh air. For severe overexposure, call physician immediately. For additional information, consult SDS for this product. **DISPOSAL:** All used and unused product should be disposed of in conformance with local, state and federal regulations. **ELECTRICAL SHOCK HAZARD:** This can will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. DO NOT use with ignition in "ON" position. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock. **KEEP AWAY FROM CHILDREN**



Multi-Purpose Lubricant

- Stops Squeaks
- Protects Metals
- Frees Rusted Parts
- Starts Wet Engines
- Non-Chlorinated

No. 1020 (CCM) • Net Wt. 9 oz. (255 g)

DANGER: FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. CONTENTS UNDER PRESSURE. Read warnings on back panel.