



# 10 Minute Radiator Flush

- One Step Action
- Non Acid

No. 2015 (CCM) • Net Contents 12 fl. oz. (355 mL)

**WARNING: MAY CAUSE EYE IRRITATION.**  
Read warnings on back panel.

## 10-Minute Radiator Flush

For use in all cooling systems, including aluminum. Harmless to all metal and rubber parts when used as directed. Quickly removes grease, oil and rust.

**DIRECTIONS:** Read entire label before using this product.

1. Drain cooling system completely. Close petcocks. Fill system with fresh water and empty contents of container into radiator.
2. Replace radiator cap, but do not tighten. Turn only to first notch.
3. Run engine for 10 minutes, after reaching normal operating temperature.
4. Stop engine and drain radiator. Refill with water. DO NOT ADD COLD WATER TO HOT SYSTEM.
5. Run engine 5 minutes. Drain radiator. Refill with radiator coolant. Add CARQUEST Radiator Anti-Rust to prevent new rust.

**WARNING:** Contains Water 7732-18-5 and Tallowamine 61791-26-2. **FIRST AID:** Avoid contact with eyes. In case of contact, wash thoroughly for 15 minutes. If swallowed, do not induce vomiting. For severe overexposure, call a physician immediately. For additional information, consult the Material Safety Data Sheet for this product.

**KEEP AWAY FROM CHILDREN**

All used and unused product should be disposed of in accordance with all local, state and federal regulations.

©2007 CARQUEST CORP.

Raleigh, NC 27604

Made in U.S.A.

800-521-3168 Technical Information



07A

#613A