



BRIGGS & STRATTON

4-USE LUBRICANT

Frees Rusted Parts

Lubricates

Displaces Moisture

Stops Corrosion

**DANGER: FLAMMABLE.
HARMFUL OR FATAL IF SWALLOWED.
CONTENTS UNDER PRESSURE.
READ WARNINGS ON BACK PANEL.
KEEP AWAY FROM CHILDREN.**

NET WT. 11 OZ (312 g)



BRIGGS & STRATTON

Lubricates and cleanses annoying surfaces, leaving a protective transparent film. Seals out rust and corrosion to protect tools, equipment and all metals. Penetrates quickly to free rusted parts.

DIRECTIONS: Spray liberally over entire surface. Wipe off excess.

WARNING: Contains Petroleum Distillate 64-74-7-8, White Mineral Oil 69-74-7-5, Butyl Selenate 123-35-5, Ethyl Acryl Ester 1336-48-8 and Carbon Dioxide 124-38-2. Do not puncture, incinerate or store can above 120°F. Exposure to high temperature may cause can to burst. Do not place in direct sunlight or near other heat sources. Product is flammable and should be kept from all flames and other ignition sources. Use only in a well ventilated area. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. Overexposure to vapor may cause irritation to the eyes and respiratory tract, headaches, dizziness, anesthesia, unconsciousness. Deliberate misuse by concentrating and mixing the contents can be harmful or fatal. **All used and unused product should be disposed of in accordance with local, state and federal regulations.**

ELECTRICAL SHOCK HAZARD: This can will conduct electricity. Do not touch can to live electrical sources including battery terminals, sensors, electrical cables, and other electronic components. Failure to observe this warning may result in serious injury from flash fire or electrical shock. Do not apply while equipment is energized.

ADDITIONAL INFORMATION: Consult the Material Safety Data Sheet for this product.

FIRST AID: In case of eye and skin contact flush with water for 15 minutes. If swallowed, may be harmful or fatal. Do not induce vomiting. If too much is treated remove to fresh air. For severe overexposure call a physician immediately.

Lubrica y reduce ruidos molestos, dejando una película transparente protectora. Aleja al óvulo y la corrosión para proteger herramientas, equipos y todos los metales. Penetra rápidamente para aflojar partes oxidadas.

INSTRUCCIONES: Aplicar abundantemente sobre toda la superficie. Remover el exceso.

ADVERTENCIA: Contiene Destilado de Petróleo 64-74-7-8, Aceite Mineral Blanco 69-74-7-5, Estearato de Butilo 123-35-5, Éster de Acilo Graso 1336-48-8 y Dioxido de Carbono 124-38-2. No perforar, incinerar o almacenar el envase de producto a una temperatura superior a 120°F. La exposición a temperaturas elevadas puede hacer explotar el envase. No exponer a los ojos directos del sol o cerca de otras fuentes de calor. Usar únicamente en áreas bien ventiladas. Evitar la continua inhalación del vapor y el contacto del producto. Evitar el contacto con la piel y los ojos. Una exposición excesiva al vapor del producto puede causar irritación en los ojos y en el sistema respiratorio, dolores de cabeza, mareos, anestesia, somnolencia y pérdida del conocimiento. El uso incorrecto mencionado al concentrar o intisar el contenido del producto puede ser nocivo o fatal. Todo producto usado y sobrante sin utilizar debe ser desechado de acuerdo con las regulaciones locales, estatales y federales.

PELIGRO DESCARGA ELÉCTRICA: Este envase puede conducir electricidad. No permitir que el envase del producto, entre en contacto con fuentes eléctricas encendidas incluyendo terminales de baterías, sensores, paneles electrónicos y otros componentes electrónicos. No prestar atención a esta advertencia podría ocasionar graves heridas a causa de un incendio fuego o de una descarga eléctrica. No aplicar mientras que el equipo esté energizado.

INFORMACIÓN ADICIONAL: Consulte la Hoja de Información de Material de Seguridad de este producto.

PREMIEROS AUXILIOS: En caso de contacto con los ojos o con la piel lavar abundantemente con agua durante 15 minutos. En caso de ingestión, puede ser nocivo o fatal. No inducir el vomito. En caso de inhalación excesiva salir al aire libre. En caso de exposición excesiva severa acudir a un médico inmediatamente.

**ADVERTENCIA: INFLAMABLE. SI SE INGIERE
PUEDE HACER DAÑO O SER FATAL. CONTENIDO BAJO PRESIÓN.
NO SE LO DEJE AL ALCANCE DE LOS NIÑOS
PESO NETO 312 g 11 US oz.**

Manufactured for Briggs & Stratton Corp., Milwaukee, WI 53201
Part No. 100043

