

WARNING: Contains Petroleum Distillate 64742-47-8, Petroleum Distillate 8052-41-3, Petroleum Distillate 64742-54-7, Octyl Acid 112-80-1 and Carbon Dioxide 124-38-9. Do not puncture, incinerate or store can above 120°F. Exposure to high temperature may cause can to burst. Do not place in direct sunlight or near any heat source. Product is flammable and should be kept from all flames and other ignition sources. This product contains chemicals known to the State of California to cause cancer, birth defects and other reproductive harm. Use only in a well ventilated area. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. Overexposure to vapor may cause eye irritation, headaches, nausea and other central nervous system effects. Inhalation of mist may cause irritation to the upper respiratory tract and breathing problems. Deliberate misuse by concentrating and inhaling the contents can be harmful or fatal. Vapors are heavier than air and can collect in low areas. **FIRST AID:** In case of eye or skin contact, flush with large amounts of water for at least 15 minutes. If swallowed, may be harmful or fatal. Do not induce vomiting. If too much is breathed, remove to fresh air. For severe overexposure, call a physician immediately.

KEEP AWAY FROM CHILDREN

LOOSEN IT!™

Use LOOSEN-IT! for appliances, toys, sewing machines, lock mechanisms, typewriters, business machines, oil burner motor shafts, guns, fishing reels, farm and garden equipment, shop tools, automobiles and scores of other applications.

- Disperses rust, scale and other oxides
- Penetrates through rust and corrosion to free corroded fasteners
- Frees and lubricates stuck or binding mechanisms
- Eases disassembly of mechanical equipment, pipe fittings and plumbing fixtures
- Helps dissolve stubborn deposits of oil, grease, carbon and soil
- Authorized by USDA for use in federally inspected meat and poultry plants

DIRECTIONS: Read entire label before using this product.

1. Apply liberal coating to corroded surfaces, saturating problem areas.
2. Tap joint lightly to aid penetration.
3. Proceed with disassembly.
4. Repeat application for stubborn joints, fasteners and assemblies.
5. Do not apply while equipment is energized.

ELECTRICAL SHOCK HAZARD: This can will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. DO NOT use with ignition in "ON" position. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

ALL USED AND UNUSED PRODUCT SHOULD BE DISPOSED OF IN CONFORMANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

For additional information, consult the Material Safety Data Sheet for this product.

©2002 CARQUEST CORP.

Lakewood, CO 80228

Made in U.S.A.

800-521-3168 Technical Information

02A

CRCH575C



LOOSEN-IT!™

PENETRATING OIL

- Penetrates and dissolves gum, rust and corrosion
- Frees and lubricates stuck and binding parts



No. 1050 (CCM) • Net Wt. 9 oz. (255 g)

DANGER: FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. CONTENTS UNDER PRESSURE.

Read warnings on back panel.