

Diesel Fuel Conditioner ***with Anti-Gel***



- Cleans Injectors and Increases MPG
- Adds Lubricity to Low Sulfur Fuel
- Lowers Pour Point and Cold Filter Plug Point
- Reliquefies Gelled Fuel

No. 2050 (CCM) • Net Contents 12 fl. oz. (355 mL)

DANGER: COMBUSTIBLE. HARMFUL OR FATAL
IF SWALLOWED. Read warnings on back panel.

Diesel Fuel Conditioner with Anti-Gel

CARQUEST DIESEL FUEL CONDITIONER with ANTI-GEL is non-corrosive and contains no alcohol. It is compatible with all diesel fuels and improves cold weather starting.

- Keeps Injectors Clean
- Increases MPG
- Stabilizes Fuel
- Maintains Cetane Rating
- Dissolves Gum & Varnish
- Fights Rust & Corrosion

This product complies with the federal ultra-low sulfur content requirements for use in all diesel motor vehicles and non-road engines.

DIRECTIONS: Read entire label before using this product. To reliquefy gelled fuel: 1. Remove diesel fuel filter. 2. Fill removed or new filter with CARQUEST Diesel Fuel Conditioner with Anti-Gel. 3. Replace fuel filter. 4. Start engine. 5. Allow fuel system to circulate until full power is restored to engine. For preventative maintenance: This container is sufficient to treat up to 35 gallons of diesel fuel, depending on fuel temperature.

To lower pour point, the following ratios are recommended:

- One bottle treats 18 gallons of fuel to lower pour point by as much as 35°F and CFFP by 31°F.
- One bottle treats 35 gallons of fuel to lower pour point by as much as 15°F and CFFP by 24°F.

WARNING: Contains Petroleum distillates 68476-34-6, 64742-94-5, Mineral spirits 8052-41-3, Naphthalene 91-20-3, and a proprietary additive blend. Product is combustible and should be kept from heat, open flames and other ignition sources. Avoid continuous breathing of vapor. Avoid contact with skin and eyes. Overexposure to liquid or vapors can cause irritation to eyes, skin, and upper respiratory tract, and central nervous system effects such as headache or dizziness. Product may pose an aspiration hazard if swallowed. Use with adequate ventilation. This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. **FIRST AID:** In case of eye or skin contact, flush with water for 15 minutes. If swallowed, DO NOT induce vomiting. If too much is breathed, remove to fresh air. For severe overexposure, call physician immediately. For additional information, consult MSDS for this product. **DISPOSAL:** All used and unused product should be disposed of in conformance with local, state and federal regulations. Do not dump in sewers, floor drains, on the ground, or into any body of water. **KEEP AWAY FROM CHILDREN**

