

Heavy Duty Silicone

CARQUEST Heavy Duty Silicone is a non-corrosive formula that lubricates and eliminates squeaking and binding caused by friction. Its film is clean, odorless, and highly resistant to water. Its lubricating properties are retained as low as -40°F and as high as 400°F.

• Lubricates metal, rubber, nylon and wood. • **NOT FOR USE ON PLASTICS.** • Protects and lubricates tools, jacks, hoists, locks, latches, zippers, springs and pulley. • Meets FDA Regulations CFR-21-178.3570 for lubricants with incidental food contact.

DIRECTIONS: Read entire label before using this product.

1. Do not apply while equipment is energized. 2. Cover and protect plastic and painted surfaces from overspray. Check on small area before using. Not for use on automotive interiors. 3. Apply light, even film. 4. Hold can 8" to 10" away from surface to be sprayed. 5. Use extension tube for pinpoint accuracy. 6. Wipe off excess with cloth. 7. Repeat applications periodically.

WARNING: Contains Acetone 67-64-1, Heptane 142-82-5, Dimethyl Polysiloxane 63148-62-9 and Hydrocarbon Propellant 68476-86-8. This product is extremely flammable and should be kept away from all sources of ignition. Do not puncture, incinerate or store container above 120°F. Exposure to high temperature may cause bursting. Do not place in direct sunlight or near other heat sources. This product contains chemicals known to the State of California to cause cancer, birth defects and other reproduction harm. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Overexposure to vapor may cause irritation to the nose and throat and may cause dizziness, drowsiness and other central nervous system effects. Inhalation of the mist may cause irritation of the respiratory tract. Deliberate misuse by concentrating and inhaling the contents can be harmful or fatal. **FIRST AID:** In case of eye or skin contact, flush with water for 15 minutes. If swallowed, may be harmful or fatal. DO NOT induce vomiting. If too much is breathed, remove to fresh air. For severe overexposure, call a physician immediately. **DISPOSAL:** All used and unused product should be disposed of in conformance with local, state and federal regulations. For additional information consult the Material Safety Data Sheet for this product. **KEEP AWAY FROM CHILDREN**

ELECTRICAL SHOCK HAZARD: This can will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. DO NOT use with ignition in "ON" position. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

SPECIAL USAGE WARNINGS • Contents Extremely Flammable. • Do not smoke while spraying. • Extinguish all flames, pilot lights and heaters. • Vapors will accumulate readily in confined spaces such as garages, engine compartments and low lying areas. • Static electricity may ignite vapors. • Use only with adequate ventilation. • Circulate fresh air during use and until vapors are gone.



Heavy Duty Silicone

- Stops Sticking, Binding, Squeaking on Nylon, Rubber, Metal & Wood Surfaces
- Low & High Temperature applications: -40° to 400°F



No. 1055 (CCM) • Net Wt. 7.5 oz. (213 g)

DANGER: EXTREMELY FLAMMABLE.
HARMFUL OR FATAL IF SWALLOWED. EYE & SKIN
IRRITANT. CONTENTS UNDER PRESSURE.
Read warnings on back panel.