

Diesel Fuel Conditioner



- Cleans Injectors
- Disperses Water
- Increases MPG
- Adds Lubricity to Low Sulfur Fuel

No. 2035 (CCM) • Net Contents 12 fl. oz. (355 mL)

**DANGER: COMBUSTIBLE. HARMFUL OR FATAL
IF SWALLOWED.** Read warnings on back panel.

Diesel Fuel Conditioner

CARQUEST DIESEL FUEL CONDITIONER is non-corrosive and contains no alcohol. It is compatible with all diesel fuels.

- Keeps Injectors Clean
- Increases MPG
- Stabilizes Fuel
- Maintains Cetane Rating
- Dissolves Gum & Varnish
- Fights Rust & Corrosion

DIRECTIONS: *Read entire label before using this product.*

To reliquefy gelled fuel: 1. Remove diesel fuel filter. 2. Fill removed or new filter with CARQUEST Diesel Fuel Conditioner. 3. Replace fuel filter. 4. Start engine. 5. Allow fuel system to circulate until full power is restored to engine.

For preventive maintenance: Add one bottle of this product to your fuel tank for every 35 gallons of diesel fuel and operate normally.

For pre-existing conditions: Add two bottles of this product to your fuel tank for every 35 gallons of diesel fuel and operate normally.

For cold conditions, use CARQUEST Diesel Fuel Conditioner with Anti-Gel (2050).

This product complies with the federal ultra-low sulfur content requirements for use in all diesel motor vehicles and non-road engines.

WARNING: Contains Petroleum Distillate 68476-34-6, Mineral spirits 8052-41-3, Petroleum naphtha 64742-94-5, Naphthalene 91-20-3 and an additive blend. Avoid continuous breathing of vapors. Avoid contact with skin and eyes. Overexposure to vapor may cause eye and skin irritation, irritation to respiratory tract, headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous system effects. Product is combustible and should be kept from all flames and other ignition sources. This product contains chemicals known to the State of California to cause cancer, birth defects and other reproductive harm. Use only in a well ventilated area. **FIRST AID:** In case of eye contact, flush with water for 15 minutes. If swallowed, DO NOT induce vomiting. If too much is breathed remove to fresh air. For severe overexposure, call a physician immediately. **KEEP AWAY FROM CHILDREN.**

©2010 CARQUEST CORP. 10A #924
Raleigh, NC 27604 Made in U.S.A.
800-521-3168 Technical Information

ALL USED AND UNUSED PRODUCT SHOULD
BE DISPOSED OF IN CONFORMANCE WITH
LOCAL, STATE AND FEDERAL REGULATIONS.

