

Diesel Fuel Conditioner



- Cleans Injectors
- Disperses Water
- Increases MPG
- Adds Lubricity to Low Sulfur Fuel

No. 2045

Net Contents: 1 gal. (3.78L)

DANGER: COMBUSTIBLE. HARMFUL OR FATAL
IF SWALLOWED. Read warnings on back panel.

Diesel Fuel Conditioner

CARQUEST DIESEL FUEL CONDITIONER is non-corrosive and contains no alcohol. It is compatible with all diesel fuels.

- Keeps Injectors Clean
- Improves Fuel Economy
- Dissolves Gum and Varnish
- Stabilizes Fuel
- Maintains Cetane Rating
- Fights Rust and Corrosion

This product complies with the federal ultra-low sulfur content requirements for use in all diesel motor vehicles and non-road engines.

DIRECTIONS: *Read entire label before using this product.*

To reliquefy gelled fuel: 1. Remove diesel fuel filter. 2. Fill removed or new filter with CARQUEST Diesel Fuel Conditioner. 3. Replace fuel filter. 4. Start engine. 5. Allow fuel system to circulate until full power is restored to engine.

For preventive maintenance: Add one bottle of this product to your fuel tank for every 500 gallons of diesel fuel and operate normally.

For pre-existing conditions: Add one bottle of this product to your fuel tank for every 200 gallons of diesel fuel and operate normally.

For cold conditions, use CARQUEST Diesel Fuel Conditioner with Anti-Gel (2060).

WARNING: Contains Petroleum distillates 68476-34-6, 64742-94-5, Mineral spirits 8052-41-3, Naphthalene 91-20-3, and a proprietary additive blend. Product is combustible and should be kept from heat, open flames and other ignition sources. Avoid continuous breathing of vapor. Avoid contact with skin and eyes. Overexposure to liquid or vapors can cause irritation to eyes, skin, and upper respiratory tract, and central nervous system effects such as headache or dizziness. Product may pose an aspiration hazard if swallowed. Use with adequate ventilation. This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

FIRST AID: In case of eye or skin contact, flush with water for 15 minutes. If swallowed, DO NOT induce vomiting. If too much is breathed, remove to fresh air. For severe overexposure, call physician immediately. For additional information, consult MSDS for this product. **DISPOSAL:** All used and unused product should be disposed of in conformance with local, state and federal regulations. Do not dump in sewers, floor drains, on the ground, or into any body of water. **KEEP AWAY FROM CHILDREN**

©2010 CARQUEST CORP.
Raleigh, NC 27604

10A
#605P

Made in U.S.A.
800-521-3168 Technical Information

