

NON-CHLORINATED

Brake Parts Cleaner



- Removes Brake Fluid, Grease and Oil
- Degreases Instantly
- Leaves No Residue
- Contains No Chlorinated Solvents



Part No. 1011 (CCM) • Net Contents: 1 gal. (3.78 L)

DANGER: EXTREMELY FLAMMABLE. VAPOR HARMFUL. HARMFUL OR FATAL IF SWALLOWED. MAY BE FATAL OR CAUSE BLINDNESS IF SWALLOWED. EYE AND SKIN IRRITANT. Read warnings on back panel.

Non-Chlorinated Brake Parts Cleaner

CARQUEST Non-Chlorinated Brake Parts Cleaner removes brake fluid, grease, oil and other contaminants from brake linings and drums. It also stops disc brake squeal and can be applied without disassembling the brake unit. Does not contain chlorinated solvents or silicones.

APPLICATIONS: brake linings, drums, disc brake pads, cylinders, springs, other related brake parts.

Directions: Read entire label before using this product. Follow all directions in numerical order.

Not for use on sensitive electronic equipment such as tape decks, VCRs, computers, etc. Use CARQUEST Quick Dry Electronic Cleaner for those applications.

WARNING: DANGER ☠ POISON

Contains Methanol 67-56-1, Toluene 108-88-3, Xylene 1330-20-7, Acetone 67-64-1 and Heptane 142-82-5. Cannot be made non-poisonous. This product is extremely flammable. Keep from flames and other ignition sources. Overexposure to vapors may cause eye and skin irritation, headaches, nausea, dizziness, irritation to upper respiratory tract and irregular heartbeats. High concentrations have caused liver and kidney damage in laboratory animals. Deliberate misuse by concentrating and inhaling the contents can be harmful or fatal. Use only in a well ventilated area. Avoid continuous breathing of vapor and spray mist. **Excessive inhalation of dust and/or vapors may be harmful.** Avoid contact with skin and eyes. Vapors are heavier than air and will collect in low areas. If ventilation is not adequate, respiratory protection should be used.

FIRST AID: In case of eye or skin contact, flush with water for 15 minutes. If swallowed, do not induce vomiting. If too much is breathed, remove to fresh air. For severe overexposure, call a physician immediately.

HANDLING AND SPILL PRECAUTIONS: Keep container closed. Wash thoroughly after handling. Do not enter where vapors are suspected in high concentrations unless air-supplied positive pressure breathing apparatus is used and a trained observer is present and equipped with rescue gear. Vapors of this solvent may develop a flammable atmosphere

1. DO NOT use on polycarbonate plastics such as LEXAN®. If in doubt, call the manufacturer of the equipment. **MAY ALSO BE HARMFUL TO OTHER PLASTICS.**
2. Protect all rubber brake parts, plastic and painted surfaces from product and overspray. DO NOT spray directly on painted surfaces. DO NOT apply while equipment is energized.
3. Wet down surfaces to be cleaned. Avoid breathing any dust or vapors that may become airborne. (See *inhalation warning*.)
4. After all surfaces have been wetted, continue using Brake Parts Cleaner to remove contaminants.
5. Air dry or wipe with a clean cloth.
6. For heavy deposits, repeat application as necessary.
7. Runoff should be collected and disposed of properly. (See *disposal statement*.)

in contact with flames, high energy sparks or high intensity sources of heat. Do not cut or weld containers due to explosion hazard. FOR SPILLS, use proper protective equipment. Take precautions as necessary to prevent contamination of ground or surface waters. FOR SMALL SPILLS, use absorbent and sweep into closed containers for disposal. For large spills evacuate the area, dike and transfer into containers for disposal.

DISPOSAL: Unused contents and containers must be disposed of in accordance with all federal, state, and local regulations. DO NOT dump in sewers, on the ground or into any body of water. For additional information, consult the Material Safety Data Sheet for this product.

KEEP AWAY FROM CHILDREN

NOT FOR USE IN CALIFORNIA.

©2009 CARQUEST CORP.
Raleigh, NC 27604
Made in U.S.A.
800-521-3168 Technical Information
09A #594P



1

0