

DIRECTIONS: *Read entire label before using this product.*

1. Do not apply while equipment is energized.
2. Spray Cable Clean® onto a lint-free cloth.
3. Wipe prepared cable with a stroking motion to clean. Cable Clean® evaporates almost immediately after application.
4. Avoid overuse.
5. Do not use on polycarbonate plastics such as LEXAN®, ABS and Noryl. If in doubt, contact the manufacturer of the equipment. **MAY BE HARMFUL TO OTHER PLASTICS.**
6. For personal safety, do not use on energized equipment.

WARNING: Contains Tetrachloroethylene, Trichloroethylene, 1,2-Butylene Oxide and Carbon Dioxide. Do not puncture, incinerate, or store can above 120°F. Exposure to high temperatures may cause can to burst. Do not place in direct sunlight or near any other heat sources. Vapors may decompose to harmful and corrosive gases such as hydrogen chloride and possibly phosgene when exposed to flame or other heat source. This product has no flash or fire point at normal handling temperatures. In high concentrations, this product can be made to burn. Do not apply while equipment is energized or near flame or arc. Make sure equipment is thoroughly dry and vented before restarting. Harmful if inhaled. Progressively higher exposure can cause eye and skin irritation, dizziness, drunkenness, irritation to upper respiratory tract, central nervous system effects, irregular heartbeats and death. Deliberate misuse by concentrating and inhaling the contents can be harmful or fatal. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid continuous breathing of vapors and spray mist. Avoid contact with skin and eyes. Vapors are heavier than air and can collect in low areas, pits, small rooms or other unventilated areas. If ventilation is not adequate, respiratory protection should be used.

FIRST AID: In case of eye or skin contact flush with water for 15 minutes. If swallowed, DO NOT induce vomiting. If too much is breathed, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. For severe overexposure, call a physician immediately.

DISPOSAL: All used and unused product should be disposed of in conformance with local, state and federal regulations. For additional information, consult the Material Safety Data Sheet for this product.

KEEP AWAY FROM CHILDREN

ELECTRICAL SHOCK HAZARD: This can will conduct electricity. Do not touch can to live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from electrical shock.

Manufactured by:

CRC INDUSTRIES, INC.

885 Louis Drive, Warminster, PA 18974

www.crcindustries.com

Made in USA

09749

08A CRC#761

DOT 20



ELECTRICAL GRADE

Cable Clean®

**High Voltage
Splice Cleaner**



Splice and Termination Cleaner

No Flash or Fire Point

**Non-Staining, Non-Conductive
& Non-Corrosive**



No. 09749

400 mL (603 g)

WARNING: VAPOR HARMFUL. CONTENTS UNDER PRESSURE. Read warnings on back panel