



Motor Flush

5-Minute Engine Cleaner

- Use Before Oil Change to Clean Engine & Oil Pan of Sludge, Gum & Varnish Build-up
- Harmless to Metal Parts
- Suitable for Gasoline and Diesel Engines

No. 2085 (CCM)

Net Contents 1 pt. 14 oz./30 fl. oz. (888 mL)

**DANGER: FLAMMABLE. HARMFUL OR FATAL
IF SWALLOWED. READ WARNINGS ON BACK PANEL.**



Motor Flush

Due to today's longer oil change intervals, there is an increased build-up of sludge, gums and varnishes inside the engine. It is extremely important that the engine be cleaned out thoroughly before installing fresh motor oil.

CARQUEST MOTOR FLUSH:

- Frees sticky valves and rings
- Allows oil to flow freely to all parts of the engine
- Should be used at least twice a year or every 5,000-6,000 miles, at time of oil change
- Is recommended for use prior to engine overhaul

DIRECTIONS: *Please read entire label before using this product.*

1. Use Motor Flush just before changing oil.
2. Turn off engine and check oil level to make certain that oil is near "full mark." Leave old oil filter in place during cleaning.
3. Add one can Motor Flush to oil in crankcase. (For crankcase capacities over 5 quarts, use approximately 20% Motor Flush for each additional quart of oil.) Close oil filter top, start engine and run at normal idle for approximately five minutes. Do not drive vehicle or race engine until crankcase has been drained and fresh motor oil installed. Note: Be sure to idle engine in open air or in area where exhaust fumes are vented to the atmosphere.
4. Shut off engine and drain crankcase immediately. Replace drain plug and install new oil filter.
5. Refill crankcase with fresh motor oil. Start engine and allow to idle for a few minutes to assure proper circulation of new oil to all vital parts.

WARNING: Contains Petroleum distillate 68476-34-6, Xylene 1330-20-7, 2-Butoxyethanol 111-76-2, Acetone 67-64-1, and Ethylbenzene 100-41-4. Product is flammable and should be kept from heat, open flames and other ignition sources. Avoid continuous breathing of vapor. Avoid contact with skin and eyes. Overexposure to liquid or vapors can cause irritation to eyes, skin, and upper respiratory tract, and central nervous system effects such as headache or dizziness. Product may pose an aspiration hazard if swallowed. This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

FIRST AID: In case of eye or skin contact, flush with water for 15 minutes. If swallowed, DO NOT induce vomiting. If too much is breathed, remove to fresh air. For severe overexposure, call physician immediately. For additional information, consult MSDS for this product.

DISPOSAL: All used and unused product should be disposed of in conformance with local, state and federal regulations. Do not dump in sewers, floor drains, on the ground, or into any body of water.

KEEP AWAY FROM CHILDREN

©2009 CARQUEST CORP.
Raleigh, NC 27604
Made in U.S.A.

09A
#611A