



Lead Substitute

- Add to Unleaded Fuel
- Protects & Lubricates Valves and Seats
- For Off-Road Use Only

No. 2080 (CCM) • Net Contents 12 fl. oz. (355 mL)

DANGER: HARMFUL OR FATAL IF SWALLOWED.
Read warnings on back panel.

Lead Substitute

Replaces lubrication formerly found in leaded fuels. Use in every tankful. Protects against valve seat recession. For Off-Road use only.

DIRECTIONS: Read entire label before using this product.

Add contents of container to fuel tank and fill with gasoline. One 12 oz. bottle will treat up to 20 gallons of gasoline To provide continuous lubrication and freedom from valve seat recession, use in every tank of fuel. Also reduces carburetor deposits as well as reduction of intake valve and port deposits.

WARNING: Contains Petroleum Distillate 68476-34-6 and Organic Additives. Overexposure to vapor may cause eye and skin irritation, irritation to respiratory tract, headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous system effects. High concentrations have caused liver and kidney effects in laboratory animals. This product contains chemicals known to the State of California to cause cancer, birth defects and other reproductive harm. Use only in a well ventilated area. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. **FIRST AID:** In case of eye contact, flush with water for 15 minutes. For skin contact, wash with soap and water. If swallowed, do not induce vomiting. If too much is breathed, remove to fresh air. For severe overexposure, call a physician immediately. For additional information, consult the Material Safety Data Sheet for this product.

KEEP AWAY FROM CHILDREN

All used and unused product should be disposed of in accordance with all local, state and federal regulations.

©2007 CARQUEST CORP.
Raleigh, NC 27604
Made in U.S.A.
800-521-3168 Technical Information



07A
#6348