



Engine Stop-Leak

- Stops Leaks
- Saves Costly Repairs

No. 2070 (CCM) • Net Contents 12 fl. oz. (355 mL)

Read warnings on back panel.

Engine Stop-Leak

Stops leaks in main bearing seals, timing gear covers, pan gaskets and other engine oil seals. Eliminates need for costly disassembly and seal replacements. Harmless to all internal engine parts and compatible with all motor oils. Recommended for use in cars, trucks, buses, tractors and diesels.

DIRECTIONS: Read entire label before using this product.

For best results, use immediately following oil and filter change.

1. Start engine and warm to operating temperature.
2. Add entire contents of container to motor oil (treats 3-6 quarts).
3. Drive vehicle as usual. Oil leaks will be sealed within 1000 miles of driving, unless leaks are a result of worn metal or cracked or broken seals. These conditions require mechanical repair.

WARNING: Contains Petroleum Distillates 64742-52-5, 64742-53-6 and Heterocyclic Ether NJRTK 74289023-5180. Keep away from heat and flame. Avoid continuous breathing of vapors. Avoid contact with skin and eyes. **FIRST AID:** In case of eye or skin contact, flush with large amounts of water for at least 15 minutes. If swallowed, do not induce vomiting. If too much is breathed, remove to fresh air. For severe overexposure, call a physician immediately. For additional information, consult the Material Safety Data Sheet for this product.

KEEP AWAY FROM CHILDREN

All used and unused product should be disposed of in accordance with all local, state and federal regulations.

©2006 CARQUEST CORP.
Lakewood, CO 80228
Made in U.S.A.

06A
#641D

