

ARDEX® Details™

DIRECTIONS: Shake can before using. Spray lightly on surface. Use on interior surfaces and padded dash. Use to coat surfaces such as door seals and bumpers. Do not spray on or near any hot surface. When spraying, be sure to prevent spray from getting onto flooring. Surface may become slippery. Do not spray on foot pedals.

DANGER: EXTREMELY FLAMMABLE. Do not spray near sparks, heat or open flames. Vapors will accumulate readily and may ignite explosively. Keep area ventilated during use and until all vapors are gone. DO NOT SMOKE WHILE USING. Turn off stoves, electric stools and appliances, and any other sources of ignition.

DANGER: CONTENTS UNDER PRESSURE. Avoid prolonged exposure to sunlight, heat from radiators, stoves, hot water, and other heat sources. Exposure to temperatures above 120F may cause can to burst with violence and cause injury. Do not puncture, incinerate, or place can in trash compactor.

VAPOR HARMFUL: Use with adequate ventilation. Avoid continuous breathing of vapor and spray mist. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during applications and drying. If you experience eye watering, headaches, or dizziness, increase fresh air or wear properly fitted respiratory protection (NIOSH/MSHA approved) or leave area. Avoid contact with skin or eyes. Refer to MSDS for complete safety and health information.

FIRST AID: In case of eye contact, flush thoroughly with plenty of water for 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. In case of respiratory difficulty, provide fresh air and call physician. If swallowed, get medical assistance immediately. DO NOT induce vomiting.

DISPOSAL: All used and unused product should be disposed of in accordance with local, state and federal regulations. DO NOT dump in sewers, floor drains, on the ground, or into any body of water.

NOTICE: Reports have associated repeated and prolonged occupational overexposures to solvent with permanent brain and nervous system damage. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

CONTAINS: Methylpentane CAS# 107-83-5, Propane CAS# 74-98-6, Isobutane CAS# 75-28-5 and Polydimethylsiloxane CAS# 9016-00-06.

KEEP OUT OF THE REACH OF CHILDREN.

HEALTH	2	4 EXTREME
FLAMMABILITY	3	3 SERIOUS
REACTIVITY	0	2 MODERATE
PERSONAL PROTECTION EQUIPMENT	B Safety Glasses & Gloves	1 SLIGHT 0 MINIMAL GLASSES

Details...takes care of details-Fast!

ardex®

ARDEX LABORATORIES INC. Philadelphia, PA 19116
1-800-44-ARDEX www.ardexlabs.com
For Chemical Emergency Call CHEMTREC: 1-800-424-9300
Made in USA



6201-01
Details




#09880/0758-A 08A

ardex®

Details™

A professionally formulated coating for hard to reach places such as air conditioning vents and door seals.

Product #6201-01



DANGER: EXTREMELY FLAMMABLE.
Harmful or Fatal if Swallowed.
Contents Under Pressure.
Peligro: Extremadamente InFlamable.
Carefully read other cautions on back panel.

Net Wt.: 13 Oz. (369g)