

**FOR PROFESSIONAL USE ONLY.
NOT INTENDED FOR RETAIL SALE.**

PRECAUTIONS

DANGER EXTREMELY FLAMMABLE

- Contents under pressure. Explosion may be caused if this container is exposed to excessive heat.
- Keep away from heat, sparks, motors open flames and direct sunlight.
- Do not puncture, incinerate or store above 120°F.
- Extinguish pilot lights. Do not smoke.
- Do not apply while equipment is energized.
- Use in well-ventilated area such as one with open windows or doors or other sources of fresh air.
- This can will conduct electricity. Keep away from all live electrical sources.

HEALTH HAZARD WARNINGS

- Avoid prolonged breathing and skin contact.
- Eye and skin contact can cause irritation and drying of the skin.
- Breathing of vapors may cause respiratory irritation, headaches, nausea and unconsciousness.
- NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage.
- Deliberately concentrating and inhaling the vapor of the contents may be harmful or fatal.

FIRST AID PROCEDURES

- **Eye Contact:** Flush with water for at least 15 minutes, contact physician.
- **Skin Contact:** Wash with soap and water. Contact physician if irritation persists.
- **Breathing:** Remove to fresh air, administer oxygen or artificial respiration if necessary. Contact physician.
- **Swallowing:** Do not induce vomiting. Contact physician.

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

HAZARDOUS INGREDIENTS

Acetone (CAS 67-64-1), Heptane isomers (CAS 142-82-5), Toluene (CAS 108-88-3), Diacetone Alcohol (CAS 123-42-2), and Carbon dioxide (CAS 124-38-9). For additional information, consult the MSDS for this product.

KEEP OUT OF THE REACH OF CHILDREN.

- Cleans gum, varnish, and carbon build-up.
- Professional formula

DIRECTIONS:

Do not spray on plastic or painted surfaces. Wash off overspray immediately.

Engine OFF - Do not spray on throttle plate sensor (TPS) or Mass Air Flow (MAF) sensor. Remove air cleaner, spray into air intake. Use a small brush to clean back of throttle plate, bore and IAC passages. Also clean EGR and PVC passages. Spray initially, stop and allow solvent to penetrate, then spray again for maximum effect.

Dispose of in accordance with local, state and federal regulations.

Chemtrec 1-800-424-9300

Manufactured For:
CDI
PO Box 269
Bath, OH 44210

Made in USA

FOR PROFESSIONAL USE ONLY.

OXYGEN SENSOR SAFE / CATALYTIC CONVERTER SAFE

NON-CHLORINATED

Throttle Plate & Air Intake Cleaner

JDA# 07001829

PART NO. 48-11-765-1

Firestone



DANGER! EXTREMELY FLAMMABLE. VAPORS MAY CAUSE FLASH FIRES. HARMFUL OR FATAL IF SWALLOWED. EYES AND SKIN IRRITANT. CONTENTS UNDER PRESSURE. Read warning and safety information on back panel.

NET WT 12 oz (340g)