

**FOR PROFESSIONAL USE ONLY.
NOT INTENDED FOR RETAIL SALE.**

**PRECAUTIONS
DANGER FLAMMABLE.**

- Contents under pressure.
- Explosion may be caused if this container is exposed to excessive heat, keep out of direct sunlight.
- Keep away from heat, sparks, motors and open flames.
- Do not puncture, incinerate or store above 120°F.
- Extinguish pilot lights. Do not smoke.
- Do not apply while equipment is energized.
- Use in well-ventilated area such as one with open windows or doors or other sources of fresh air.
- This can will conduct electricity. Keep away from all live electrical sources.

HEALTH HAZARD WARNINGS

- Avoid prolonged breathing and skin contact.
- Eye and skin contact can cause irritation and drying of the skin.
- Breathing of vapors may cause respiratory irritation, headaches, nausea and unconsciousness.
- Deliberately concentrating and inhaling the vapor of the contents may be harmful or fatal.

FIRST AID PROCEDURES

- Eye Contact: Flush with water for at least 15 minutes, contact physician.
- Skin Contact: Wash with soap and water. Contact physician if irritation persists.
- Breathing: Remove to fresh air, administer oxygen or artificial respiration if necessary. Contact physician.
- Swallowing: Do not induce vomiting. Contact physician immediately.

HAZARDOUS INGREDIENTS

Petroleum Distillate (8052-41-3), Petroleum Distillate (64742-47-8), Heavy Paraffinic Distillates (64741-88-4), Oleic Acid (112-80-1) and Carbon Dioxide (124-38-9). For additional information, consult MSDS for this product.

KEEP OUT OF REACH OF CHILDREN

- Displaces moisture and waterproofs ignition systems.
- Lubricates and stops corrosion in locks and latches.
- Will not harm rubber, plastics, or painted surfaces.

DIRECTIONS

- ① Saturate area and let soak for several minutes. Do not need to wipe off.
- ② To dry wet ignitions, spray on spark plug wires and distributor cap. Starts engines quickly.
- ③ When using as a lubricant, spray on area, parts, or mechanisms to be treated.

All used and unused product should be disposed of in accordance with local, state and federal regulations. Do not dump in sewers, floor drains, on the ground or in any body of water.

CHEMTREC: 1-800-424-9300

Manufactured for:
CDI
PO Box 269
Bath, OH 44210

Made in USA

FOR PROFESSIONAL USE

BF60

MULTI-PURPOSE LUBRICANT

- Loosens & Frees Rusted Parts
- Displaces Moisture for Ignition Systems
- Cleans & Protects

JDA# 07001826

PART NO.

48-11-750-3

Firestone



**DANGER: FLAMMABLE. HARMFUL OR FATAL
IF SWALLOWED. CONTENTS UNDER PRESSURE.
Carefully read cautions on rear panel.**

NET WT. 13.0 OZ (369g)