

Superior Chemistry. Superior Performance.

MAG1

CONCENTRATED
FORMULA

Treats
35 Gal.
(132 L)

DIESEL FUEL TREATMENT WITH ANTIGEL

Tratamiento para Combustible
Diesel con Antigelificante

Increases Mileage • Reliquesfies Gelled Fuel • Reduces Emissions
• Extra Fuel System Cleaning Power • Adds Lubricity

**DANGER: HARMFUL OR FATAL IF SWALLOWED.
COMBUSTIBLE. (READ CAUTIONS ON BACK PANEL)**

12 FL OZ (355 mL)

MAG 1 DIESEL FUEL TREATMENT with AntiGel offers maximum protection against harmful effects of low-sulfur fuels. Contains high levels of detergents, dispersants and lubricity additives to deliver extra fuel system cleaning power and lubricity. Meets Cummins L-10 Superior Spec.

• Clean Injectors • Increases Mileage • Reduces Emissions • Adds Lubricity • Increases Power • Prevents Corrosion
SUPERIOR COLD WEATHER PERFORMANCE AND PROTECTION INCLUDES AN ANTIGEL.

• Lowers fuel Pour Point and Cold Filter Plugging Point (CFPP) • Prevents fuel gelling • Reliquesfies gelled fuel

DIRECTIONS: Read entire label before using. Compatible with all diesel fuels. Detailed instructions & MSDS at www.wd-wpp.com.
PREVENTIVE MAINTENANCE: Add one bottle when refueling. TO RELIQUEFY GELLED FUEL: Remove diesel fuel filter and fill with MAG 1 Diesel Fuel Treatment with AntiGel. Replace fuel filter and run engine until full power is restored. TO LOWER POUR POINT, the following ratios are recommended:

- One bottle treats 18 Gal. (68 L) of fuel to lower pour point by as much as 35° F (19° C) and CFPP by 31° F (17° C).
- One bottle treats 35 Gal. (132 L) of fuel to lower pour point by as much as 15° F (8° C) and CFPP by 24° F (13° C).

WARNING: Contains petroleum distillates 68476-34-6 & 64742-94-5, stoddard solvent 8052-41-3, naphthalene 91-20-3 and additive blend. Use only in well ventilated area. Keep away from heat and open flame. This product contains chemicals known to the State of California to cause cancer, birth defects and other reproductive harm. Avoid prolonged contact with skin. FIRST AID: If swallowed do not induce vomiting. Call physician immediately. EYES: Flush with water. KEEP OUT OF REACH OF CHILDREN. All used and unused product should be disposed of in accordance with local, state and federal regulations. DO NOT dump in sewers, floor drains, on the ground, or into any body of water. This product complies with the federal ultra-low sulfur content requirements for use in all diesel motor vehicles and non-road engines.

INSTRUCCIONES: Agregue el contenido de esta botella al rellenar el tanque. Compatible con todos los combustibles diesel.

PRECAUCIONES: Contiene destilados de petróleo. Usar sólo en áreas bien ventiladas. Combustible, mantener alejado de llamas y fuentes de encendido. Si se ingiere, consiga atención médica inmediatamente.

Distributed by Warren Performance Products
P.O. Box 3007 • Omaha, NE 68103

Made In U.S.A. 09A

Part Number 170

