

**DIRECTIONS: Read entire label before using this product. 1. Do not apply while equipment is energized. 2. Shake can well before use. 3. Spray a light, even coat on surfaces to be protected. 4. Use extension tube for hard to reach areas and for spot lubrication. 5. Thin, non-drying film may be removed with petroleum solvents.**

**INSTRUCCIONES: Lea toda la etiqueta antes de usar este producto. 1. No aplique el producto mientras el equipo está conectado. 2. Agite bien antes de usar. 3. Rocíe con una capa liviana y pareja sobre las superficies a proteger. 4. Utilice el tubo de extensión para alcanzar las áreas difíciles y para lubricar partes. 5. La película delgada que no se seca puede ser eliminada con solventes para petróleo.**

**Danger:** Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Causes skin irritation. Causes eye irritation. May cause drowsiness or dizziness.



**Precautionary Statements:** Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not apply while equipment is energized. Extinguish all flames, pilot lights and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing mist or vapor. Wash thoroughly after handling. Wear protective gloves. Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst. Dispose of contents/container in accordance with local/regional/national regulations. **First Aid:** If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Contains petroleum distillates 64742-47-8, 64742-48-9, 64742-88-7, paraffin oils 64742-70-7, 64742-71-8, butyl stearate 123-95-5, calcium dodecylbenzenesulphonate 26264-06-2, carbon dioxide 124-38-9, fatty acids 61788-89-4, petrolatum 8009-03-8, sorbitan monolaurate 61791-48-8, n-nonane 111-84-2, and n-octane 111-65-9. Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. For additional information, consult SDS for this product.

**Electrical Shock Hazard:** This metal can will conduct electricity. Keep away from all live electrical sources. Failure to observe this warning may result in serious injury and/or flash fire.

**Peligro:** Aerosol extremadamente inflamable. Contiene gas a presión; puede explotar si se calienta. Puede ser mortal en caso de ingestión y de penetración en las vías respiratorias. Provoca irritación cutánea. Provoca irritación ocular. Puede provocar somnolencia o vértigo.

**Consejos de prudencia:** Mantener alejado del calor/de chispas/de llamas al descubierto/de superficies calientes. - No fumar. No vaporizar sobre una llama al descubierto o cualquier otra fuente de ignición. Recipiente a presión: No perforar ni quemar, incluso después del uso. No aplique el producto sobre un equipo conectado. Apague todas las llamas, pilotos y calefactores. El vapor se acumulará rápidamente y puede inflamarse. Utilice solo con ventilación adecuada; mantenga la ventilación durante la utilización del producto hasta que el vapor haya desaparecido. Abra las puertas y ventanas y utilice otros medios para asegurar la provisión de aire fresco al utilizar el producto y mientras se está secando. Si presenta algunos de los síntomas enumerados en esta etiqueta, aumente la ventilación o deje el área. Evitar respirar nieblas o vapores. Lávese cuidadosamente después de la manipulación. Usar guantes de protección. Almacenar en un lugar bien ventilado. Guardar bajo llave. Proteger de la luz solar. No exponer a una temperatura superior a 50 °C/122 °F. La exposición a altas temperaturas puede provocar que la lata estalle. Eliminación de contenidos / contenedor en consonancia con los reglamentos locales / regionales / nacionales pertinentes.

**Primeros Auxilios:** En caso de ingestión: Llamar inmediatamente a un centro de toxicología o a un médico. No provocar el vómito. En caso de contacto con la piel: Lavar con abundante agua. En caso de irritación cutánea: Consultar a un médico. Quitar la ropa contaminada y lavarla antes de volverla a usar. En caso de inhalación: Transportar la persona al aire libre y mantenerla en una posición que le facilite la respiración. Llamar a un CENTRO DE TOXICOLOGÍA o a un médico si la persona se encuentra mal. En caso de contacto con los ojos: Enjuagar con agua cuidadosamente durante varios minutos. Quitar las lentes de contacto cuando estén presentes y pueda hacerse con facilidad. Proseguir con el lavado. Si la irritación ocular persiste, consultar a un médico.

Su mal uso deliberado, concentrando e inhalando su contenido es ilegal y puede ser perjudicial o fatal. La inhalación abusiva puede causar la muerte. Para mayor información, consulte la Hoja de Datos de Seguridad para este producto.

**Peligro de Descarga Eléctrica:** Esta lata de metal puede conducir la electricidad. Manténgala alejada de todas las fuentes eléctricas vivas. El incumplimiento de esta advertencia puede resultar lesiones graves y/o incendio repentino.

©2019 CRC Industries, Inc., 885 Louis Dr., Warrminster, PA 18974  
800-521-3168 (Technical Information) • 800-272-4620 (Customer Care)

Made in U.S.A. 19A  
www.crcindustries.com

**WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.**  
**ADVERTENCIA: Cáncer y Daño Reproductivo - www.P65Warnings.ca.gov.**



# Stor & Lube® Corrosion Inhibitor Inhibidor de Corrosión

Long Term Rust  
Preventative Lubricant

Lubricante Preventivo  
Del Óxido a Largo Plazo



Nonfood Compounds  
Program Listed: H2  
Reg. # 017222



**DANGER: FLAMMABLE.  
HARMFUL OR FATAL IF SWALLOWED.  
EYE AND SKIN IRRITANT.  
CONTENTS UNDER PRESSURE.  
KEEP AWAY FROM CHILDREN.  
Read warnings on back panel.**

**PELIGRO: INFLAMABLE.  
NOCIVO O FATAL SI SE INGIERE.  
IRRITANTE DE OJOS Y PIEL.  
CONTENIDO BAJO PRESIÓN.  
MANTENER ALEJADO DEL  
ALCANCE DE LOS NIÑOS.  
Lea las advertencias en el dorso.**



No. 02061  
Item# 1003189

Net Wt./Peso Neto  
11 oz (311 g)



PLEASE RECYCLE  
WHEN EMPTY

To review S.D.S.: Tear (DO NOT CUT) label along these perforations and fold back label. After viewing, reattach label. Do not completely remove label until can is empty. Para revisar la Hoja de Datos de Seguridad (HDS): Rasgue (NO CORTE) la etiqueta siguiendo estas perforaciones y dóblela hacia atrás. Al terminar, vuelva a pegar la etiqueta. No la retire completamente hasta que la lata esté vacía.

## 1. Identification

**Product identifier:** Stor & Lube® Corrosion Inhibitor

**Product code** No. 02061 (Item# 1003189)

**Recommended use** Lubricant and corrosion inhibitor

**Restrictions** None known.

**Manufactured or sold by:**

CRC Industries, Inc., 885 Louis Drive, Warminster, PA 18974

Phone: 215-674-4300

**Emergency phone number** CHEMTREC - 24 HOURS: 800-424-9300

## 2. Hazard(s) identification

**Physical hazards** Flammable aerosols (Category 1)

Gases under pressure (Compressed gas)

**Health hazards** Skin corrosion/irritation (Category 2)

Serious eye damage/eye irritation (Category 2B)

Specific target organ toxicity, single exposure (Category 3 narcotic effects)

Aspiration hazard (Category 1)

**Label elements (see front side of label)**

## 3. Composition/information on ingredients

**Hazardous components**

Chemical name	CAS number	%
hydroreated light distillates	64742-47-8	40 – 50
hydroreated heavy naphtha	64742-48-9	10 – 20
catalytic dewaxed heavy paraffin oils	64742-70-7	10 – 20
catalytic dewaxed light paraffin oils	64742-71-8	5 – 10
butyl stearate	123-95-5	3 – 5
calcium dodecylbenzenesulphonate	28264-06-2	3 – 5
carbon dioxide	124-38-9	1 – 3
fatty acids	61788-89-4	1 – 3
petrolatum	8009-03-8	1 – 3
medium aliphatic solvent naphtha	64742-88-7	1 – 3
sorbitan monolattate	61791-48-8	1 – 3
n-nonane	111-84-2	< 3
n-octane	111-65-9	< 0.2

(Specific chemical identity and/or percentage of composition has been withheld as a trade secret.)

## 4. First-aid measures

**Inhalation** Remove victim to fresh air. Call a POISON CENTER or doctor/physician if you feel unwell.

**Skin contact** Remove contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical attention.

**Eye contact** Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

**Ingestion** Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting.

**Most important symptoms/effects** Aspiration may cause pulmonary edema and pneumonitis.

Skin and eye irritation. Vapors have a narcotic effect and may cause headache, fatigue, dizziness, drowsiness, and nausea.

**Special treatment needed** Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

## 5. Fire-fighting measures

**Suitable extinguishing media** Water fog. Alcohol resistant foam. Dry chemicals. Carbon dioxide (CO2).

**Unsuitable extinguishing media** Do not use water jet as an extinguisher, as this will spread the fire.

**Specific hazards** Extremely flammable aerosol. Contents under pressure. Pressurized container may rupture when exposed to heat or flame.

**Special protective equipment and precautions for firefighters** Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

## 6. Accidental release measures

**Personal precautions** Keep people away from and upwind of spill/leak. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them.

**Containment and cleaning up** Eliminate all ignition sources. Keep combustibles away from spilled material. Wipe up with absorbent material. Clean surface thoroughly to remove residual contamination. Avoid discharge into drains, water courses, or onto the ground.

## 7. Handling and storage

**Handling** Pressurized container. Do not pierce or burn, even after use. Avoid breathing mist or vapor.

Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling.

**Storage** Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated and away from incompatible materials.

## 8. Exposure controls/personal protection

**Occupational exposure limits**

Components	Type	Value
hydroreated heavy naphtha	PEL	400 mg/m3
hydroreated light distillates	PEL	400 mg/m3
carbon dioxide	PEL	9000 mg/m3
catalytic dewaxed heavy/light paraffin oils	TWA	5 mg/m3
n-nonane	TWA	200 ppm
n-octane	TWA	300 ppm
petrolatum	TWA	5 mg/m3
butyl stearate	TWA	10 mg/m3
medium aliphatic solvent naphtha	TWA	200mg/m3

**Appropriate engineering controls** Mechanical ventilation or local exhaust ventilation is recommended.

**Individual protection measures:**

**Eye/face protection** Wear safety glasses with side shields (or goggles).

**Skin protection** Wear protective gloves such as nitrile or neoprene. Wear appropriate clothing to prevent skin contact.

**Respiratory protection** If needed, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Wear positive pressure self-contained breathing apparatus (SCBA) in case of emergency.

## 9. Physical and chemical properties

**Appearance** Tan creamy liquid.

**Odor threshold** Not available.

**Melting point/freezing point** -56 °F (-49 °C)

**Flash point** 144 °F (62 °C) Tag Closed Cup

**Explosive limit - lower (%)** 0.5

**Vapor pressure** 1180 hPa

**Relative density** 0.87

**Partition coefficient (n-octanol/water)** Not available.

**Decomposition temperature** Not available.

**VOC (Weight %):** 24.5% (1.8 lb/gal, 213 g/L)

**Odor** Petroleum.

**pH** Not available.

**Initial boiling point** 315 °F (157 °C)

**Evaporation rate** Slow.

**Explosive limit - upper (%)** 6

**Vapor density** > 1 (Air = 1)

**Solubility(ies)** Not available.

**Auto-ignition temperature** 410 °F (210 °C)

**Viscosity** Not available.

## 10. Stability and reactivity

**Reactivity** Non-reactive

**Chemical stability** Stable

**Possibility of hazardous reactions** No

**Conditions to avoid** Heat, flames and sparks. Temperatures exceeding the flash point. Incompatible materials.

**Incompatible materials** Strong oxidizing agents.

**Hazardous decomposition products** Carbon oxides. Sulfur compounds.

## 11. Toxicological information

**Information on likely routes of exposure:**

**Ingestion** Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

**Inhalation** Vapors have a narcotic effect and may cause headache, fatigue, dizziness, nausea and vomiting.

**Skin contact** Causes skin irritation.

**Eye contact** Causes eye irritation.

**Information on toxicological effects:**

**Acute toxicity** May be fatal if swallowed and enters airways.

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** Not expected to cause skin sensitization.

**Carcinogenicity** Not considered to be a carcinogen by IARC, ACGIH, NTP or OSHA.

**Reproductive toxicity** Not expected to cause reproductive or developmental effects.

**Aspiration hazard** May be fatal if swallowed and enters airways.

**Chronic effects** Prolonged inhalation may be harmful.

## 12. Ecological information

See full SDS for additional information

## 13. Disposal considerations

**Disposal instructions** The dispensed liquid product is not a RCRA hazardous waste. Empty container may be recycled.

**Hazardous waste code** Not regulated.

## 14. Transport information

**DOT shipping description:** UN1950, Aerosols, flammable, 2.1, Limited Quantity

## 15. Regulatory information

SARA 313 None.

See full SDS for additional information

## 16. Other information

Issue date 17-OCT-17

CRC #527J-K/1002538-1002540

Version # 04