

DIRECTIONS: Read entire label before using this product. 1. Do not apply while equipment is energized. 2. Wear eye protection and rubber gloves or other non-porous hand protection. Protect painted surfaces from overspray, as product will dissolve paint. 3. Gasket removal: spray liberal coating on gasket and adhesive and allow to set for 5-10 minutes. Remove with putty knife and dry rag. 4. Paint and graffiti removal: spray liberal coating on painted surface. Allow to dry and brush with a stiff bristle brush.

INSTRUCCIONES: Lea la etiqueta completa antes de usar este producto. 1. No aplique el producto mientras el equipo esté conectado. 2. Utilice protección para los ojos y guantes de goma u otro tipo de protección no porosa para manos. Proteja las superficies pintadas del exceso de rocío, dado que el producto disuelve la pintura. 3. Eliminator de juntas: rocíe una capa abundante sobre la junta y el adhesivo y deje actuar por 5-10 minutos. Retire con una espátula y un trapo seco. 4. Eliminador de pintura y grafitos: rocíe una capa abundante sobre la superficie pintada. Deje secar y limpie con un cepillo de cerdas dura.

Danger: Extremely flammable aerosol. Contains gas under pressure, may explode if heated. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. Suspected of causing cancer. May damage fertility or the unborn child. May cause damage to organs (central nervous system, kidney, liver) through prolonged or repeated exposure.



Precautionary Statements: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container. Do not pierce or burn, even after use. Do not breathe mist or vapor. Do not apply while equipment is energized. Extinguish all flames, pilot lights, and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst. Dispose of contents/container in accordance with local/regional/national regulations.

First Aid: If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If exposed or concerned: Get medical advice/attention.

Contains acetone 67-64-1, liquefied petroleum gas 68476-86-8, N-methyl-2-pyrrolidone 872-50-4, xylene 1330-20-7, ethylbenzene 100-41-4, and toluene 108-88-3. Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. For additional information, consult SDS for this product.

Electrical Shock Hazard: This metal can will conduct electricity. Keep away from all live electrical sources. Failure to observe this warning may result in serious injury and/or flash fire.

Peligro: Aerosol extremadamente inflamable. Contiene gas a presión; puede explotar si se calienta. Provoca irritación cutánea. Provoca irritación ocular grave. Puede irritar las vías respiratorias. Puede provocar somnolencia o vértigo. Susceptible de provocar cáncer. Puede perjudicar la fertilidad o dañar al feto. Puede provocar daños en los órganos (sistema nervioso central, riñón, hígado) tras exposiciones prolongadas o repetidas.

Consejos de prudencia: Procurarse las instrucciones antes del uso. No manipular antes de haber leído y comprendido todas las precauciones de seguridad. Mantener alejado del calor/de chispas/de llamas al descubierto/de superficies calientes. - No fumar. No vaporizar sobre una llama al descubierto o cualquier otra fuente de ignición. Recipiente a presión: No perforar ni quemar, incluso después del uso. No respirar nieblas o vapores. No aplique el producto sobre un equipo conectado. Apague todas las llamas, pilotos y calefactores. El vapor se acumulará rápidamente y puede inflamarse. Utilice solo con ventilación adecuada; mantenga la ventilación durante la utilización del producto hasta que el vapor haya desaparecido. Abra las puertas y ventanas y utilice otros medios para asegurar la provisión de aire fresco al utilizar el producto y mientras se esté secando. Si presenta algunos de los síntomas enumerados en esta etiqueta, aumente la ventilación o deje el área. Lávese cuidadosamente después de la manipulación. Usar guantes/ropa de protección/equipo de protección para los ojos/la cara. Almacenar en un lugar bien ventilado. Guardar bajo llave. Proteger de la luz solar. No exponer a una temperatura superior a 50 °C/122 °F. La exposición a altas temperaturas puede provocar que la lata estalle. Eliminación de contenidos / contenedor en consonancia con los reglamentos locales / regionales / nacionales pertinentes.

Primeros Auxilios: En caso de contacto con la piel: Lavar con abundante agua. En caso de irritación cutánea: Consultar a un médico. Quitar la ropa contaminada y lavarla antes de volverla a usar. En caso de inhalación: Transportar la persona al aire libre y mantenerla en una posición que le facilite la respiración. Llamar a un CENTRO DE TOXICOLOGÍA o a un médico si la persona se encuentra mal. En caso de contacto con los ojos: Enjuagar con agua cuidadosamente durante varios minutos. Quitar las lentes de contacto cuando estén presentes y pueda hacerse con facilidad. Proseguir con el lavado. Si la irritación ocular persiste, consultar a un médico. En caso de exposición demostrada o supuesta: consultar a un médico.

Su mal uso deliberado, concentrando e inhalando su contenido es ilegal y puede ser perjudicial o fatal. La inhalación abusiva puede causar la muerte. Para mayor información, consulte la Hoja de Datos de Seguridad para este producto.

Peligro de Descarga Eléctrica: Esta lata de metal puede conducir la electricidad. Manténgala alejada de todas las fuentes eléctricas vivas. El incumplimiento de esta advertencia puede resultar lesiones graves y/o incendio repentino.

VOC Category: Gasket Adhesive Remover **VOC Limit:** 50%



Gasket Remover

Removes Gaskets, Paint and Graffiti

Remueve Juntas, Pintura y Grafitos



Nonfood Compounds
Program Listed: C3
Reg.# 017394



No. 03017
Item# 1003266

Net Wt./Peso Neto
12 oz (340 g)



PLEASE RECYCLE
WHEN EMPTY

To review S.D.S.: Tear (DO NOT CUT) label along these perforations and fold back label. After viewing, reattach label. Do not completely remove label until can is empty. Para revisar la Hoja de Datos de Seguridad (HDS): Resegue (NO CORTE) la etiqueta siguiendo estas perforaciones y dóblala hacia atrás. Al terminar, vuelva a pegar la etiqueta. No la retire completamente hasta que la lata esté vacía.

1. Identification

Product identifier: Gasket Remover

Product code: No. 03017 (Item# 1003266)

Recommended use: Gasket remover

Restrictions: None known.

Manufactured or sold by:

CRC Industries, Inc., 885 Louis Drive, Warminster, PA 18974

Phone: 215-674-4300

Emergency phone number: CHEMTREC - 24 HOURS: 800-424-9300

2. Hazard(s) identification

| | |
|-------------------------|--|
| Physical hazards | Flammable aerosols (Category 1) Gases under pressure (Liquefied gas) |
| Health hazards | Skin corrosion/irritation (Category 2) Serious eye damage/eye irritation (Category 2A) Carcinogenicity (Category 2) Reproductive toxicity (Category 1B) Specific target organ toxicity, single exposure (Category 3 respiratory tract irritation) Specific target organ toxicity, single exposure (Category 3 narcotic effects) Specific target organ toxicity, repeated exposure (Category 2 central nervous system, kidney, liver) |

Label elements (see front side of label)

3. Composition/information on ingredients

Hazardous components

| Chemical name | CAS number | % |
|-------------------------|------------|---------|
| acetone | 67-64-1 | 50 – 60 |
| liquefied petroleum gas | 68476-86-8 | 20 – 30 |
| N-methyl-2-pyrrolidone | 872-50-4 | 10 – 20 |
| xylene | 1330-20-7 | 1 – 3 |
| ethylbenzene | 100-41-4 | < 1 |
| toluene | 108-88-3 | < 0.2 |

(Specific chemical identity and/or percentage of composition has been withheld as a trade secret.)

4. First-aid measures

Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact: Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention.

Eye contact: Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion: In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth.

Most important symptoms/effects: May cause drowsiness, dizziness, headache, nausea, vomiting, narcotic effects, and behavioral changes. Severe eye, skin, and respiratory irritation.

Special treatment needed: Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

5. Fire-fighting measures

Suitable extinguishing media: Water fog, Alcohol resistant foam, Carbon dioxide (CO2), Dry chemical powder, Sand, Earth.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards: Extremely flammable aerosol. Contents under pressure. Pressurized container may rupture when exposed to heat or flame. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur.

Special protective equipment and precautions for firefighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions: Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective equipment. Ventilate closed spaces before entering them.

Containment and cleaning up: Eliminate all ignition sources. Keep combustibles away from spilled material. Wipe up with absorbent material and place into suitable containers. Prevent entry into waterways, sewer, basements, or confined areas.

7. Handling and storage

Handling: Pressurized container: Do not pierce or burn, even after use. Do not smoke while using or until sprayed surface is thoroughly dry. Do not breathe mist or vapor. Avoid contact with eyes, skin, and clothing. Pregnant or breastfeeding women must not handle this product. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling.

Storage: Store in a cool, dry place (below 122°F/50°C) and out of direct sunlight. Keep away from heat, sparks, and open flame. This material can accumulate static charge which may cause spark and become an ignition source. Avoid spark promoters. Store in a well-ventilated place and away from incompatible materials.

8. Exposure controls/personal protection

Occupational exposure limits

| Components | Type | Value |
|------------------------|------|---------|
| acetone | TWA | 250 ppm |
| ethylbenzene | TWA | 20 ppm |
| xylene | TWA | 100 ppm |
| N-methyl-2-pyrrolidone | TWA | 10 ppm |
| toluene | TWA | 20 ppm |

Appropriate engineering controls: Mechanical ventilation or local exhaust ventilation is recommended.

Individual protection measures:

Eye/face protection: Wear safety glasses with side shields (or goggles).

Skin protection: Wear protective gloves such as butyl rubber. Wear appropriate chemical resistant clothing.

Respiratory protection: If needed, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus (SCBA) in confined spaces and for emergencies.

9. Physical and chemical properties

| | |
|--|--|
| Appearance: Light grey liquid. | Odor: Solvent. |
| Odor threshold: Not available. | pH: Not available. |
| Melting point/freezing point: -139 °F (-95 °C) | Initial boiling point: 133 °F (56 °C) |
| Flash point: 56 °F (13 °C) Tag Closed Cup | Evaporation rate: Fast |
| Explosive limit - lower (%) : 1 | Explosive limit - upper (%) : 12.8 |
| Vapor pressure: 1341 hPa | Vapor density > 1 (air = 1) : |
| Relative density: 0.78 | Solubility(ies): Soluble. |
| Partition coefficient (n-octanol/water): Not available. | Decomposition temperature: Not available. |
| Auto-ignition temperature: 473 °F (245 °C) | VOC (Weight %): 47.5% (3.1 lb/gal, 371 g/L) |
| Viscosity: Not available. | |

10. Stability and reactivity

Reactivity: Non-reactive **Chemical stability:** Stable

Possibility of hazardous reactions: No

Conditions to avoid: Heat, flames and sparks. Incompatible materials.

Incompatible materials: Strong acids. Acids. Strong oxidizing agents. Halogens. Peroxides. Phenols.

Hazardous decomposition products: Carbon oxides.

11. Toxicological information

Information on likely routes of exposure:

Ingestion: Health injuries are not known or expected under normal use.

Inhalation: May cause damage to organs through prolonged or repeated exposure by inhalation.

May cause drowsiness and dizziness. Headache, Nausea, vomiting. May cause irritation to the respiratory system.

Skin contact: Causes skin irritation.

Eye contact: Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics: May cause drowsiness, dizziness, headache, nausea, vomiting, narcotic effects, and behavioral changes.

Severe eye, skin, and respiratory irritation.

Information on toxicological effects:

Acute toxicity: Not known.

Respiratory sensitization: Not a respiratory sensitizer.

Skin sensitization: Not expected to cause skin sensitization.

Carcinogenicity: Suspected of causing cancer.

Reproductive toxicity: May damage fertility of the unborn child.

Aspiration hazard: Not an aspiration hazard.

Chronic effects: May cause damage to organs (central nervous system, kidney, liver) through prolonged or repeated exposure.

12. Ecological information

See full SDS for additional information

13. Disposal considerations

Disposal instructions: This material must be disposed of as hazardous waste.

Hazardous waste code D001: Waste Flammable liquid with a flash point <140 F

14. Transport information

DOT shipping description: UN1950, Aerosols, flammable, 2.1, limited quantity

15. Regulatory information

SARA 313: ethylbenzene, N-methyl-2-pyrrolidone, xylene

See full SDS for additional information

16. Other information

Issue date 12-SEP-17

CRC # 553B/1002570

Version # 02