

DIRECTIONS: Read entire label before using this product. 1. Do not use on energized equipment. 2. Safe on most plastics. Test small area. 3. Shake well before using. 4. Always direct spray tip toward the surface to be bonded. 5. Hold can 6-12 inches from surface to be sprayed. 6. Apply a light uniform coat of adhesive to surface. 7. For POROUS substrates, apply two coats in opposite directions. 8. For PERMANENT bonds, apply a heavy coat to both surfaces, let dry for 3 to 5 minutes and press substrates together. 9. For NON-PERMANENT bonds, apply a light coating to one surface only, let dry for 5 minutes and bond. 10. After use, invert can and depress spray tip until spray is free of adhesive. 11. If clogged, clean with petroleum distillate.

INSTRUCCIONES: Lea la etiqueta completa antes de usar este producto. 1. No use este producto en equipos con corriente eléctrica. 2. Seguro en la mayoría de los plásticos. Comprobar en un área pequeña. 3. Agitar bien antes de usar. 4. Siempre dirija la punta de pulverización hacia la superficie a ser adherida. 5. Sujete la lata de 6 a 12 pulgadas de la superficie a pulverizarse. 6. Aplicar una capa ligera uniforme de adhesivo a la superficie. 7. Para sustratos POROSOS, aplicar dos capas en direcciones opuestas. 8. Para adherencias PERMANENTES, aplicar una capa gruesa a ambas superficies, secar secar durante 3 a 5 minutos y apretar los sustratos el uno contra el otro. 9. Para adherencias NO PERMANENTES, aplicar una capa ligera a solo una superficie, dejar secar durante 5 minutos y unir. 10. Después del uso, invierta la lata y libere la punta de pulverización hasta que el spray esté libre de adhesivo. 11. Si se tapa, limpiar con destilado de petróleo.

Danger: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.



Precautionary Statements: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe mist or vapor. Do not apply while equipment is energized. Extinguish all flames, pilot lights, and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst. Dispose of contents/container in accordance with local/regional/national regulations. **First Aid:** If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If exposed or concerned: Get medical advice/attention.

Contains acetone 67-64-1, methyl acetate 79-20-9, petroleum distillates 8030-30-6, and toluene 108-88-3. Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. For additional information, consult SDS for this product.

Electrical Shock Hazard: This metal can will conduct electricity. Keep away from all live electrical sources. Failure to observe this warning may result in serious injury and/or flash fire.

Peligro: Aerosol extremadamente inflamable. Contiene gas a presión; puede explotar si se calienta. Provoca irritación ocular grave. Puede irritar las vías respiratorias. Puede provocar somnolencia o vértigo. Susceptible de perjudicar la fertilidad o dañar al feto. Puede provocar daños en los órganos tras exposiciones prolongadas o repetidas.

Consejos de Prudencia: Procurarse las instrucciones antes del uso. No manipular antes de haber leído y comprendido todas las precauciones de seguridad. Mantener alejado del calor/de chispas/de llamas al descubierto/de superficies calientes. - No fumar. No vaporizar sobre una llama al descubierto o cualquier otra fuente de ignición. Recipiente a presión: No perforar ni quemar, incluso después del uso. No respirar nieblas o vapores. No aplique el producto sobre un equipo conectado. Apague todas las llamas, pilotos y calefactores. El vapor se acumulará rápidamente y puede inflamarse. Utilice solo con ventilación adecuada; mantenga la ventilación durante la utilización del producto hasta que el vapor haya desaparecido. Abra las puertas y ventanas y utilice otros medios para asegurar la provisión de aire fresco al utilizar el producto y mientras se esté secando. Si presenta algunos de los síntomas enumerados en esta etiqueta, aumente la ventilación o deje el área. Lávese cuidadosamente después de la manipulación. Usar guantes/ropa de protección/equipo de protección para los ojos/la cara. Almacenar en un lugar bien ventilado. Guardar bajo llave. Proteger de la luz solar. No exponer a una temperatura superior a 50°C/122°F. La exposición a altas temperaturas puede provocar que la lata estalle. Eliminar el contenido/recipiente conforme a las reglamentaciones local/regional/nacional.

Primeros Auxilios: En caso de inhalación: Transportar la persona al aire libre y mantenerla en una posición que le facilite la respiración. Llamar a un CENTRO DE TOXICOLOGIA o a un médico si la persona se encuentra mal. En caso de contacto con los ojos: Enjuagar con agua cuidadosamente durante varios minutos. Quitar las lentes de contacto cuando estén presentes y pueda hacerse con facilidad. Proseguir con el lavado. Si la irritación ocular persiste, consultar a un médico. En caso de exposición demostrada o supuesta: consultar a un médico.

Su mal uso deliberado, concentrando e inhalando su contenido es ilegal y puede ser perjudicial o fatal. La inhalación abusiva puede causar la muerte. Para mayor información, consulte la Hoja de Datos de Seguridad para este producto.

Peligro de Descarga Eléctrica: Esta lata de metal puede conducir la electricidad. Manténgala alejada de todas las fuentes eléctricas vivas. El incumplimiento de esta advertencia puede resultar lesiones graves y/o incendio repentino.

©2018 CRC Industries, Inc., 885 Louis Dr., Warminster, PA 18974 **VOC Category: Web Spray Adhesive VOC Limit: 40%** 18A
800-521-3168 (Technical Information) • 800-272-4620 (Customer Care) Made in U.S.A. www.crcindustries.com

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.
ADVERTENCIA: Cáncer y Daño Reproductivo - www.P65Warnings.ca.gov.



Spray Adhesive

Spray Adhesivo

Web Spray Pattern
Minimal Soak-In
High Tack Formula
Good Water Resistance

Patrón de rociado de web
Absorción mínima
Fórmula de alto poder de fijación
Buena resistencia al agua

Recommended for foam, foils, plastics, papers, cardboard, and cloths
Recomendado para poliestireno, papel metálico, plástico, papel, cartón y tela

DANGER: EXTREMELY FLAMMABLE. EYE IRRITANT. MAY CAUSE RESPIRATORY IRRITATION. CONTENTS UNDER PRESSURE. KEEP AWAY FROM CHILDREN.
Read warnings on back panel.

PELIGRO: EXTREMAMENTE INFLAMABLE. IRRITANTE DE LOS OJOS. PUEDE IRRITAR LAS VÍAS RESPIRATORIAS. CONTENIDO BAJO PRESIÓN. MANTENGA FUERA DEL ALCANCE DE LOS NIÑOS.
Lea las advertencias en el dorso.



No. 03018
Item# 1003268

1.01 lb / 16.25 oz (460 g)

1. Identification

Product identifier: Spray Adhesive

Product code No. 03018 (Item# 1003268)

Recommended use General purpose aerosol adhesive

Restrictions None known.

Manufactured or sold by:

CRC Industries, Inc., 885 Louis Drive, Warminster, PA 18974

Phone: 215-674-4300

Emergency phone number CHEMTREC - 24 HOURS: 800-424-9300

2. Hazard(s) identification

Physical hazards Flammable aerosols (Category 1)

Gases under pressure (Liquefied gas)

Health hazards Serious eye damage/eye irritation (Category 2A)

Reproductive toxicity (Category 2)

Specific target organ toxicity, single exposure

(Category 3 narcotic effects, respiratory tract irritation)

Specific target organ toxicity, repeated exposure (Category 2)

Label elements (see front side of label)

3. Composition/information on ingredients

Hazardous components

Chemical name	CAS number	%
acetone	67-64-1	30 – 40
methyl acetate	79-20-9	10 – 20
petroleum distillates	8030-30-6	1 – 10
toluene	108-88-3	1 – 10

(Specific chemical identity and/or percentage of composition has been withheld as a trade secret.)

4. First-aid measures

Inhalation Move to fresh air. If breathing is difficult, give oxygen. Provide oxygen or artificial respiration if needed. If person is not breathing, call 911 or an ambulance.

Skin contact Wash off immediately with soap and plenty of water. Get medical attention if symptoms occur.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Ingestion Do not induce vomiting. Call a physician or poison control center immediately. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects Narcotic effects. Severe eye irritation. Respiratory irritation.

Special treatment needed Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

5. Fire-fighting measures

Suitable extinguishing media Water fog. Dry chemicals. Foam. Carbon dioxide (CO₂).

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards Extremely flammable aerosol. Contents under pressure. Pressurized container may rupture when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. Accidental release measures

Personal precautions Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective equipment. Ventilate closed spaces before entering them.

Containment and cleaning up Eliminate all ignition sources. Keep combustibles away from spilled material. Wipe up with absorbent material and place into containers. Clean surface thoroughly to remove residual contamination. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Handling Pressurized container. Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Avoid contact with eyes. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Use only in well-ventilated areas. Wear appropriate personal protective equipment.

Storage Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place, away from incompatible materials.

8. Exposure controls/personal protection

Occupational exposure limits

Components	Type	Value
acetone	TWA	250 ppm
methyl acetate	TWA	200 ppm
petroleum distillates	PEL	100 ppm
toluene	TWA	20 ppm

Appropriate engineering controls Mechanical ventilation or local exhaust ventilation is recommended.

Individual protection measures:

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection Wear protective gloves such as laminate film. Wear appropriate clothing to prevent skin contact.

Respiratory protection If needed, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Wear positive pressure self-contained breathing apparatus (SCBA) in case of emergency.

9. Physical and chemical properties

Appearance Beige liquid.

Odor Solvent.

Odor threshold Not available.

pH Not available.

Melting point/freezing point -144 °F (-98 °C)

Initial boiling point 95 °F (35 °C)

Flash point -4 °F (-20 °C)

Evaporation rate Not available.

Explosive limit - lower (%) 1.3

Explosive limit - upper (%) 16

Vapor pressure 1690 hPa

Vapor density Not available

Relative density 0.76

Solubility(ies) Insoluble.

Auto-ignition temperature 550 °F (288 °C)

Viscosity Not available.

VOC (Weight %) 35.8% (2.3 lb/gal, 272 g/L)

10. Stability and reactivity

Reactivity Non-reactive

Chemical stability Stable

Possibility of hazardous reactions No

Conditions to avoid Heat, flames and sparks. Incompatible materials.

Incompatible materials Strong oxidizing agents. Strong acids and alkalis.

Hazardous decomposition products Carbon oxides. Hydrocarbons. Fumes.

11. Toxicological information

Information on likely routes of exposure:

Inhalation May cause drowsiness, dizziness, headache, nausea and vomiting. May cause irritation to the respiratory system.

Skin contact Prolonged skin contact may cause temporary irritation.

Eye contact Causes serious eye irritation.

Ingestion May be harmful if swallowed and enters airways.

Information on toxicological effects:

Acute toxicity Not known.

Sensitization Not a sensitizer.

Germ cell mutagenicity Not expected to be mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

Reproductive toxicity Suspected of damaging fertility or the unborn child.

Specific target organ toxicity May cause respiratory irritation. May cause drowsiness and dizziness. May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard Based on available data, the classification criteria are not met.

Chronic effects May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful.

12. Ecological information

See full SDS for additional information

13. Disposal considerations

Disposal instructions This material must be disposed of as hazardous waste.

Hazardous waste code D001, F003

14. Transport information

DOT shipping description: UN1950, Aerosols, flammable, 2.1, limited quantity

15. Regulatory information

SARA 313 toluene

See full SDS for additional information

16. Other information

Issue date 29-AUG-18

Version # 04