

DIRECTIONS: Read entire label before using this product. 1. Do not apply while equipment is energized. 2. Spray in light, even coats to areas requiring lubrication or moisture protection. 3. Repeat step 2 until adequate lubrication or protection is achieved. Use only the necessary amount to achieve results. 4. Re-apply as needed to maintain performance.

INSTRUCCIONES: Lea toda la etiqueta antes de usar este producto. 1. No aplique el producto mientras el equipo está conectado. 2. Pinte en capas ligeras y parejas, en las zonas que requieren lubricación o protección contra la humedad. 3. Repita el paso 1 hasta alcanzar la lubricación o protección adecuada. Utilice solamente la cantidad necesaria para alcanzar los resultados deseados. 4. Aplique nuevamente, según sea necesario, para mantener el rendimiento.

Danger: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Causes skin and eye irritation. May cause drowsiness or dizziness. Suspected of damaging fertility.



Precautionary Statements: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container. Do not pierce or burn, even after use. Do not apply while equipment is energized. Extinguish all flames, pilot lights and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing mist or vapor. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst. When exposed to extreme heat or hot surfaces, vapors may decompose to harmful or fatal corrosive gases such as hydrogen fluoride. Dispose of contents/container in accordance with local/regional/national regulations.

First Aid: If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. If exposed or concerned: Get medical attention.

Contains 1,1-difluoroethane 75-37-6, hydro-treated light naphtha 64742-49-0, 2-methylpentane 107-83-5, and n-hexane 110-54-3. Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. For additional information, consult SDS for this product.

Electrical Shock Hazard: This can will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

Peligro: Aerosol extremadamente inflamable. Contiene gas a presión; puede explotar si se calienta. Puede ser mortal en caso de ingestión y de penetración en las vías respiratorias. Provoca irritación cutánea y ocular. Puede provocar somnolencia o vértigo. Susceptible de perjudicar la fertilidad.



Consejos de prudencia: Procurarse las instrucciones antes del uso. No manipular antes de haber leído y comprendido todas las precauciones de seguridad. Mantener alejado del calor/de chispas/de llamas al descubierto/de superficies calientes. - No fumar. No perforar sobre una llama al descubierto o cualquier otra fuente de ignición. Recipiente a presión: No perforar ni quemar, incluso después del uso. No aplique el producto sobre un equipo conectado. Apague todas las llamas, pilotos y calefactores. El vapor se acumulará rápidamente y puede inflamarse. Utilice solo con ventilación adecuada; mantenga la ventilación durante la utilización del producto hasta que el vapor haya desaparecido. Abra las puertas y ventanas y utilice otros medios para asegurar la provisión de aire fresco al utilizar el producto y mientras se este secando. Si presenta algunos de los síntomas enumerados en esta etiqueta, aumente la ventilación o deje el área. Evitar respirar nieblas o vapores. Usar guantes/ropa de protección/equipo de protección para los ojos/la cara. Lávese cuidadosamente después de la manipulación. Almacenar en un lugar bien ventilado. Guardar bajo llave. Proteger de la luz solar. No exponer a una temperatura superior a 50 °C/122 °F. La exposición a altas temperaturas puede provocar que la lata estalle. Al exponerlo al calor extremo, los vapores pueden descomponerse en gases corrosivos y tóxicos como el fluoruro de hidrógeno. Eliminación de contenidos / contenedor en consonancia con los reglamentos locales / regionales / nacionales pertinentes.

Primeros Auxilios: En caso de ingestión: Llamar inmediatamente a un centro de toxicología o a un médico. NO provocar el vómito. En caso de contacto con la piel: Lavar con abundante agua. Si ocurre irritación de la piel: Busque atención médica. Quitar la ropa contaminada y lavarla antes de volverla a usar. En caso de inhalación: Transportar la persona al aire libre y mantenerla en una posición que le facilite la respiración. Llamar a un CENTRO DE TOXICOLOGIA o a un médico si la persona se encuentra mal. En caso de contacto con los ojos: Enjuagar con agua cuidadosamente durante varios minutos. Quitar las lentes de contacto cuando estén presentes y pueda hacerse con facilidad. Proseguir con el lavado. Si persiste la irritación de los ojos. Busque atención médica. En caso de exposición demostrada o supuesta: Busque atención médica.

Su mal uso deliberado, concentrando e inhalando su contenido es ilegal y puede ser perjudicial o fatal. La inhalación abusiva puede causar la muerte. Para mayor información, consulte la Hoja de Datos de Seguridad para este producto.

Peligro de Descarga Eléctrica: Esta lata conduce la electricidad. Mantenga fuera del alcance de todas las fuentes eléctricas vivas, incluso bornes de baterías, solenoides, tableros eléctricos y otros componentes electrónicos. Pasar por alto esta advertencia puede derivar en lesiones graves provocadas por fuego explosivo y/o descarga eléctrica.

©2016 CRC Industries, Inc., 885 Louis Dr., Warminster, PA 18974 Made in U.S.A. 16A CRC# 519E/F
800-521-3168 (Technical Information) • 800-272-4620 (Customer Care) • 215-442-6260 (SDS) www.crcindustries.com



Food Grade Silicone

Silicona Apta para Uso Alimentario

Multi-Purpose Lubricant
Lubricante Multipropósito



Nonfood Compounds Program Listed
Category Code: H1 Reg.# 017393



**DANGER: EXTREMELY
FLAMMABLE. HARMFUL
OR FATAL IF SWALLOWED.
CONTENTS UNDER PRESSURE.
KEEP AWAY FROM CHILDREN.
Read warnings on back panel.**

**PELIGRO: EXTREMAMENTE
INFLAMABLE. SU INGESTIÓN
ES PERJUDICIAL O MORTAL.
CONTENIDO BAJO PRESIÓN.
MANTENGA FUERA DEL
ALCANCE DE LOS NIÑOS.
Lea las advertencias en el dorso.**

No. 03040

**Net Wt./Peso Neto
10 oz (283 g)**

To review S.D.S.: Tear (DO NOT CUT) label along these perforations and fold back label.
After viewing, reattach label. Do not completely remove label until can is empty.
Para revisar la Hoja de Datos de Seguridad (HDS): Ráscala (NO CORTE) la etiqueta siguiendo estos
perforaciones y dóblela hacia atrás. Al terminar, vuelva a pegar la etiqueta.
No la retire completamente hasta que la lata está vacía.

1. Identification

Product identifier: Food Grade Silicone

Product code 03040

Recommended use Silicone-based multi-purpose lubricant

Restrictions None known.

Manufactured or sold by:

CRC Industries, Inc., 885 Louis Drive, Warminster, PA 18974

Phone: 215-674-4300

Emergency phone number CHEMTREC - 24 HOURS: 800-424-9300

2. Hazard(s) identification

Physical hazards Flammable aerosols (Category 1)
Gases under pressure (Liquefied gas)

Health hazards Skin corrosion/irritation (Category 2)
Serious eye damage/eye irritation (Category 2B)
Reproductive toxicity (Category 2 fertility)
Specific target organ toxicity, single exposure (Category 3 narcotic effects)
Aspiration hazard (Category 1)

Label elements (see front side of label)

3. Composition/information on ingredients

Hazardous components

Chemical name	CAS number	%
1,1-difluoroethane	75-37-6	30 – 40
hydrotreated light naphtha	64742-49-0	30 – 40
2-methylpentane	107-83-5	10 – 20
n-Hexane	110-54-3	3 – 5

(Specific chemical identity and/or percentage of composition has been withheld as a trade secret.)

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact Wash off with soap and plenty of water. Remove contaminated clothing. If skin irritation occurs: Get medical attention.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Call a physician or poison control center immediately. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects Vapors have a narcotic effect and may cause headache, fatigue, drowsiness, dizziness and nausea. Skin and eye irritation.

Special treatment needed Provide general supportive measures and treat symptomatically.

5. Fire-fighting measures

Suitable extinguishing media Water fog. Foam. Dry chemical powder. Carbon dioxide. Sand. Earth.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards Contents under pressure. Pressurized container may rupture when exposed to heat or flame. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur.

Special protective equipment and precautions for firefighters Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions Do not touch damaged containers or spilled material unless wearing appropriate protective equipment. Do not breathe gas, mist or vapor. Ventilate closed spaces before entering them.

Containment and cleaning up Eliminate all ignition sources. Keep combustibles away from spilled material. Wipe up with absorbent material. Clean surface thoroughly to remove residual contamination. Prevent entry into waterways, sewer, basements or confined areas. Use appropriate containment to avoid environmental contamination.

7. Handling and storage

Handling Pressurized container. Do not pierce or burn, even after use. When using, do not eat, drink or smoke. Do not breathe gas, mist or vapor. Avoid contact with skin and eyes. Avoid contact during pregnancy/while nursing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Do not empty into drains.

Storage Store in a cool, dry place (below 122°F/50°C) and out of direct sunlight. Store in a well-ventilated place. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source.

8. Exposure controls/personal protection

Occupational exposure limits

Components	Type	Value
hydrotreated light naphtha	PEL	100 ppm
n-hexane	TWA	50 ppm
2-methylpentane	TWA	500 ppm

Appropriate engineering controls Mechanical ventilation or local exhaust ventilation is recommended.

Individual protection measures:

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection Wear protective gloves such as nitrile, PVC or Viton®. Wear appropriate clothing to prevent skin contact.

Respiratory protection If needed, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Wear positive pressure self-contained breathing apparatus (SCBA) in case of emergency.

9. Physical and chemical properties

Appearance Clear, water-white liquid.

Odor threshold Not available.

Melting point/freezing point Not available.

Flash point < 0 °F (< -17.8 °C) Tag Closed Cup

Explosive limit - lower (%) 1

Vapor pressure 3083 hPa

Relative density 0.81

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature 437 °F (225 °C)

Decomposition temperature Not available.

Viscosity Not available.

VOC (Weight %): 60% (3.3 lb/gal, 398.9 g/l)

Odor Mild solvent.

pH Not available.

Initial boiling point 118 °F (48 °C)

Evaporation rate Fast.

Explosive limit - upper (%) 8

Vapor density > 1 (Air = 1)

Solubility(ies) Negligible in water.

10. Stability and reactivity

Reactivity Non-reactive

Chemical stability Stable

Possibility of hazardous reactions No

Conditions to avoid Heat, flames and sparks. Incompatible materials. When exposed to extreme heat or hot surfaces, vapors may decompose to harmful or fatal corrosive gases such as hydrogen fluoride.

Incompatible materials Strong oxidizing agents. Chlorine.

Hazardous decomposition products Carbon oxides. Hydrogen fluoride.

11. Toxicological information

Information on likely routes of exposure:

Ingestion May be fatal if swallowed and enters airways.

Inhalation Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. May cause damage to organs by inhalation.

Skin contact Causes skin irritation.

Eye contact Causes eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Skin and eye irritation.

Information on toxicological effects:

Acute toxicity May be fatal if swallowed and enters airways. Narcotic effects.

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization Not expected to cause skin sensitization.

Carcinogenicity Not considered to be a carcinogen by IARC, ACGIH, NTP or OSHA.

Reproductive toxicity Suspected of damaging fertility.

Aspiration hazard May be fatal if swallowed and enters airways.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

See full SDS for additional information

13. Disposal considerations

Disposal instructions This material must be disposed of as hazardous waste.

Hazardous waste code D001: Waste Flammable liquid

14. Transport information

DOT shipping description: UN1950, Aerosols, flammable, 2.1, limited quantity

15. Regulatory information

SARA 313 n-hexane

See full SDS for additional information

16. Other information

Issue date 11/15/2016

CRC #519E/F

Version # 04