

DIRECTIONS: Read entire label before using this product.

1. Do not apply while equipment is energized. 2. Spray in light, even coats to areas requiring lubrication or moisture protection. 3. Repeat step 2 until adequate lubrication or protection is achieved. Use only the necessary amount to achieve results. 4. Re-apply as needed to maintain performance.

INSTRUCCIONES: Lea toda la etiqueta antes de usar este producto.

1. No aplique el producto mientras el equipo esté conectado. 2. Rocíe en capas ligeras y parejas, en las zonas que requieren lubricación o protección contra la humedad. 3. Repita el paso 1 hasta alcanzar la lubricación o protección adecuada. Utilice solamente la cantidad necesaria para alcanzar los resultados deseados. 4. Aplique nuevamente, según sea necesario, para mantener el rendimiento.

Danger: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness.



Precautionary Statements: Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not apply while equipment is energized. Extinguish all flames, pilot lights, and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing mist/vapor. Wash thoroughly after handling. Wear protective gloves. Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst. Dispose of contents/container in accordance with local/regional/national regulations.

First Aid: If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell.

Contains 1,1-difluoroethane 75-37-6, heptanes 64742-49-0, 142-82-5, 589-34-4, 591-76-4, 565-59-3, 617-78-7, 562-49-2, and methylcyclohexane 108-87-2. Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. For additional information, consult SDS for this product.

Electrical Shock Hazard: This metal can will conduct electricity. Keep away from all live electrical sources. Failure to observe this warning may result in serious injury and/or flash fire.

Peligro: Aerosol extremadamente inflamable. Contiene gas a presión; puede explotar si se calienta. Puede ser mortal en caso de ingestión y de penetración en las vías respiratorias. Provoca irritación cutánea. Puede provocar somnolencia o vértigo.

Consejos de prudencia: Mantener alejado del calor/de chispas/de llamas al descubierto/de superficies calientes. - No fumar. No vaporizar sobre una llama al descubierto o cualquier otra fuente de ignición. Recipiente a presión: No perforar ni quemar, incluso después del uso. No aplique el producto sobre un equipo conectado. Apague todas las llamas, pilotos y calefactores. El vapor se acumulará rápidamente y puede inflamarse. Utilice solo con ventilación adecuada; mantenga la ventilación durante la utilización del producto hasta que el vapor haya desaparecido. Abra las puertas y ventanas y utilice otros medios para asegurar la provisión de aire fresco al utilizar el producto y mientras se esté secando. Si presenta algunos de los síntomas enumerados en esta etiqueta, aumente la ventilación o deje el área. Evitar respirar nieblas/vapores. Lávese cuidadosamente después de la manipulación. Usar guantes de protección. Almacenar en un lugar bien ventilado. Guardar bajo llave. Proteger de la luz solar. No exponer a una temperatura superior a 50 °C/122 °F. La exposición a altas temperaturas puede provocar que la lata estalle. Eliminar el contenido/recipiente conforme a las reglamentaciones local/regional/nacional.

Primeros Auxilios: En caso de ingestión: Llamar inmediatamente a un centro de toxicología o a un médico. NO provocar el vómito. En caso de contacto con la piel: Lavar con abundante agua. En caso de irritación cutánea: Consultar a un médico. Quitar la ropa contaminada y lavarla antes de volverla a usar. En caso de inhalación: Transportar la persona al aire libre y mantenerla en una posición que le facilite la respiración. Llamar a un CENTRO DE TOXICOLOGÍA o a un médico si la persona se encuentra mal.

Su mal uso deliberado, concentrando e inhalando su contenido es ilegal y puede ser perjudicial o fatal. La inhalación abusiva puede causar la muerte. Para mayor información, consulte la Hoja de Datos de Seguridad para este producto.

Peligro de Descarga Eléctrica: Esta lata de metal puede conducir la electricidad. Manténgala alejada de todas las fuentes eléctricas vivas. El incumplimiento de esta advertencia puede resultar lesiones graves y/o incendio repentino.



Food Grade Silicone

Silicona para grado alimenticio

Multi-Purpose Lubricant
Lubricante Multipropósito

Perma-Lock®
2-WAY INTEGRATED ACTUATOR

S.D.I.L.®
Safety Data Label™



NSF H1

Nonfood Compounds Program
Listed: H1 Reg.# 017393



No. 03040
Item# 1003296

Net Wt.
10 oz (283 g)

DANGER: EXTREMELY FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. SKIN IRRITANT. CONTENTS UNDER PRESSURE. KEEP AWAY FROM CHILDREN.
Read warnings on back panel.

PELIGRO: EXTREMAMENTE INFLAMABLE. NOCIVO O FATAL SI SE INGERE. IRRITANTE DE LA PIEL. CONTENIDO BAJO PRESIÓN. MANTÉNGALA FUERA DEL ALCANCE DE LOS NIÑOS.
Lea las advertencias en el dorso.

To review S.D.S.: Tear (DO NOT CUT) label along these perforations and fold back label.

Alter viewing, reattach label. Do not completely remove label until can is empty.

Para revisar la Hoja de Datos de Seguridad (HDS): Rasgue (NO CORTE) la etiqueta siguiendo estas perforaciones y dóblala hacia atrás. Al terminar, vuelva a pegarla a la etiqueta.

No la retire completamente hasta que la lata esté vacía.



PLEASE RECYCLE WHEN EMPTY

1. Identification

Product identifier: Food Grade Silicone

Product code No. 03040 (Item# 1003296)

Recommended use Silicone-based multi-purpose lubricant

Restrictions None known.

Manufactured or sold by:

CRC Industries, Inc., 885 Louis Drive, Warminster, PA 18974

Phone: 215-674-4300

Emergency phone number CHEMTREC - 24 HOURS: 800-424-9300

2. Hazard(s) identification

Physical hazards Flammable aerosols (Category 1)

Gases under pressure (Liquefied gas)

Health hazards Skin corrosion/irritation (Category 2)

Specific target organ toxicity, single exposure

(Category 3 narcotic effects)

Aspiration hazard (Category 1)

Label elements (see front side of label)

3. Composition/information on ingredients

Hazardous components

Chemical name	CAS number	%
1,1-difluoroethane	75-37-6	30 – 40
hydrotreated light naphtha	64742-49-0	20 – 30
n-heptane	142-82-5	10 – 20
3-methylhexane	589-34-4	5 – 10
methylcyclohexane	108-87-2	5 – 10
2-methylhexane	591-76-4	3 – 5
2,3-dimethylpentane	565-59-3	1 – 3
3-ethylpentane	617-78-7	1 – 3
3,3-dimethylpentane	562-49-2	< 0.3

(Specific chemical identity and/or percentage of composition has been withheld as a trade secret.)

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact Wash off with soap and plenty of water. Remove contaminated clothing. If skin irritation occurs: Get medical attention.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Call a physician or poison control center immediately. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects Aspiration hazard. Narcotic effects. Skin irritation.

Special treatment needed Provide general supportive measures and treat symptomatically.

5. Fire-fighting measures

Suitable extinguishing media Water fog. Foam. Dry chemical powder. Carbon dioxide.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards Extremely flammable aerosol. Contents under pressure. Pressurized container may rupture when exposed to heat or flame.

Special protective equipment and precautions for firefighters Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapor. Ventilate closed spaces before entering them.

Containment and cleaning up Eliminate all ignition sources. Keep combustibles away from spilled material. Wipe up with absorbent material. Clean surface thoroughly to remove residual contamination. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Handling Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment.

Storage Store in a cool, dry place (below 122°F/50°C) and out of direct sunlight. Store in a well-ventilated place. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source.

8. Exposure controls/personal protection

Occupational exposure limits

Components	Type	Value
methylcyclohexane	TWA	400 ppm
hydrotreated light naphtha	PEL	100 ppm
n-heptane	TWA	400 ppm
2,3-dimethylpentane	TWA	400 ppm
2-methylhexane	TWA	400 ppm
3,3-dimethylpentane	TWA	400 ppm
3-ethylpentane	TWA	400 ppm
3-methylhexane	TWA	400 ppm

Appropriate engineering controls Mechanical ventilation or local exhaust ventilation is recommended.

Individual protection measures:

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection Wear protective gloves such as nitrile or viton/butyl. Wear appropriate clothing to prevent skin contact.

Respiratory protection If needed, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Wear positive pressure self-contained breathing apparatus (SCBA) in case of emergency.

9. Physical and chemical properties

Appearance Water-white liquid.

Odor threshold Not available.

Melting point/freezing point -196 °F (-127 °C)

Flash point < 23 °F (< -5 °C) Tag Closed Cup

Flammability (solid, gas) Not available.

Flammability limit - upper (%) 7

Vapor density > 1 (Air = 1)

Solubility(ies) Negligible in water.

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature 509 °F (265 °C)

Viscosity Not available.

Odor Mild petroleum.

pH Not available.

Initial boiling point 149 °F (65 °C)

Evaporation rate Fast.

Flammability limit - lower (%) 1.1

Vapor pressure 2931 hPa

Relative density 0.78

Decomposition temperature Not available.

VOC (Weight %): 60% (3.9 lb/gal, 468 g/L)

10. Stability and reactivity

Reactivity Non-reactive

Chemical stability Stable

Possibility of hazardous reactions No

Conditions to avoid Heat, flames and sparks. Incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition products Carbon oxides.

11. Toxicological information

Information on likely routes of exposure:

Inhalation May cause drowsiness, dizziness, headache, nausea and vomiting.

Skin contact Causes skin irritation.

Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics Aspiration hazard. Narcotic effects. Skin irritation.

Information on toxicological effects:

Acute toxicity May be fatal if swallowed and enters airways.

Respiratory or skin sensitization Not a sensitizer.

Germ cell mutagenicity Not expected to be mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

Reproductive toxicity Not expected to cause reproductive or developmental effects.

Specific target organ toxicity May cause drowsiness and dizziness.

Aspiration hazard May be fatal if swallowed and enters airways.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

See full SDS for additional information

13. Disposal considerations

Disposal instructions This material must be disposed of as hazardous waste.

Hazardous waste code D001: Waste Flammable liquid

14. Transport information

DOT shipping description: UN1950, Aerosols, flammable, 2.1, limited quantity

15. Regulatory information

SARA 313 None

See full SDS for additional information

16. Other information

Issue date 18-OCT-18

CRC # 1750887

Version # 05