

**DIRECTIONS: Read entire label before using this product.** Shake well before using. 1. Spray an even coat of Power Lube® and allow product to coat all moving parts. 2. For superior performance, reapply product after first coat has penetrated all parts. 3. Repeat process as necessary to maintain proper lubrication.

**INSTRUCCIONES: Lea toda la etiqueta antes de usar este producto.** Agite bien antes de usar. 1. Rocíe una capa pareja de Power Lube® y permita que el producto cubra todas las piezas móviles. 2. Para obtener un excelente resultado, aplique el producto nuevamente luego de que la primera capa haya penetrado en todas las piezas. 3. Repita el proceso tanto como sea necesario para mantener la lubricación correcta.

**Danger:** Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Causes serious eye irritation. Suspected of damaging fertility.

**Precautionary Statements:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container. Do not pierce or burn, even after use. Do not apply while equipment is energized. Extinguish all flames, pilot lights, and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst. When exposed to extreme heat or hot surfaces, vapors may decompose to harmful or fatal corrosive gases such as hydrogen fluoride. Dispose of contents/container in accordance with local/regional/national regulations.

**First Aid:** If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If exposed or concerned: Get medical advice/attention.

Contains petroleum distillates 8, naphtha 64742-47-8, 64742-70-7, 64742-71-8, 64742-49-0, liquefied petroleum gas 68476-86-8, methyl salicylate 119-36-8, 2-methylpentane 107-83-5, diglycolene glycol monomethyl ether 34590-94-8, fatty acid dimers 61788-89-4, petrolatum 8009-03-8, sodium petroleum sulfonate 68608-26-4, n-hexane 110-54-3, and benzotriazole-methanamine 94270-86-7. Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. For additional information, consult SDS for this product.

**Electrical Shock Hazard:** This metal can will conduct electricity. Keep away from all live electrical sources. Failure to observe this warning may result in serious injury and/or flash fire.

**Peligro:** Aerosol extremadamente inflamable. Contiene gas a presión; puede explotar si se calienta. Puede ser mortal en caso de ingestión y de penetración en las vías respiratorias. Provoca irritación ocular grave. Susceptible de perjudicar la fertilidad.

**Consejos de prudencia:** Procurarse las instrucciones antes del uso. No manipular antes de haber leído y comprendido todas las precauciones de seguridad. Mantener alejado del calor/de chispas/de llamas al descubierto/de superficies calientes. - No fumar. No vaporizar sobre una llama al descubierto o cualquier otro fuente de ignición. Recipiente a presión: No perforar ni quemar, incluso después del uso. No aplique el producto sobre un equipo conectado. Apague todas las llamas, pilotos y calentadores. El vapor se acumula rápidamente y puede inflamarse. Utilice solo con ventilación adecuada; mantenga la ventilación durante la utilización del producto hasta que el vapor haya desaparecido. Abra las puertas y ventanas y utilice otros medios para asegurar la provisión de aire fresco al utilizar el producto y mientras se esté secando. Si presenta algunos de los síntomas enumerados en esta etiqueta, aumente la ventilación o deje el área. Lávese cuidadosamente después de la manipulación. Usar guantes/ropa de protección/equipo de protección para los ojos/la cara. Almacenar en un lugar bien ventilado. Guardar bajo llave. Proteger de la luz solar. No exponer a una temperatura superior a 50 °C/122 °F. La exposición a altas temperaturas puede provocar que la lata estalle. Al exponerlo al calor extremo, los vapores pueden descomponerse en gases corrosivos y tóxicos como el fluoruro de hidrógeno. Eliminación de contenidos / contenedor en consonancia con los reglamentos locales / regionales / nacionales pertinentes.

**Primeros Auxilios:** En caso de ingestión: Llamar inmediatamente a un centro de toxicología o a un médico. NO provocar el vómito. En caso de contacto con los ojos: Enjuagar con agua cuidadosamente durante varios minutos. Quitar las lentes de contacto cuando estén presentes y pueda hacerse con facilidad. Proseguir con el lavado. Si la irritación ocular persiste, consultar a un médico. En caso de exposición demostrada o sospecha: consultar a un médico.

Su mal uso deliberado, concentrando e inhalando su contenido es ilegal y puede ser perjudicial o fatal. La inhalación abusiva puede causar la muerte. Para mayor información, consulte la Hoja de Datos de Seguridad para este producto.

**Peligro de Descarga Eléctrica:** Esta lata de metal puede conducir la electricidad. Manténgala alejada de todas las fuentes eléctricas vivas. El incumplimiento de esta advertencia puede resultar lesiones graves y/o incendio repentino.

©2017 CRC Industries, Inc., 885 Louis Dr., Warmminster, PA 18974  
800-521-3168 (Technical Information) • 800-272-4620 (Customer Care)

Made in U.S.A. 17A  
www.crcindustries.com



Nonfood Compounds  
Program List# H2  
Reg.# 017403



# Power Lube® High Performance Lubricant w/PTFE Alto Rendimiento Lubricante c/PTFE

Lubricates Moving Parts  
Protects Against Corrosion

Lubrica Piezas Móviles  
Protege Contra la Corrosión

**DANGER: EXTREMELY  
FLAMMABLE. HARMFUL OR FATAL  
IF SWALLOWED. EYE IRRITANT.  
CONTENTS UNDER PRESSURE.  
KEEP AWAY FROM CHILDREN.  
Read warnings on back panel.**

**PELIGRO: EXTREMAMENTE  
INFLAMABLE. SU INGESTIÓN ES  
PERJUDICIAL O MORTAL.  
IRRITANTE DE LOS OJOS.  
CONTENIDO BAJO PRESIÓN.  
MANTENGA FUERA DEL  
ALCANCE DE LOS NIÑOS.  
Lea las advertencias en el dorso.**



No. 03045  
Item# 1003304

Net Wt./Peso Neto  
11 oz (311 g)



PLEASE RECYCLE  
WHEN EMPTY

To review S.D.S.: Tear (DO NOT CUT) label along these perforations and fold back label. After viewing, reattach label. Do not completely remove label until can is empty. Para revisar la Hoja de Datos de Seguridad (HDS): Rasgue (NO CORTE) la etiqueta siguiendo estas perforaciones y doblela hacia atrás. Al terminar, vuelva a pegar la etiqueta. No la retire completamente hasta que la lata esté vacía.

**WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.**  
**ADVERTENCIA: Cáncer y Daño Reproductivo - www.P65Warnings.ca.gov.**

## 1. Identification

**Product identifier:** Power Lube® High Performance Lubricant w/PFE  
**Product code No.** 03045 (Item# 1003304)  
**Recommended use:** Multi-purpose lubricant  
**Restrictions:** None known.  
**Manufactured or sold by:** CRC Industries, Inc., 885 Louis Drive, Warminster, PA 18974  
**Phone:** 215-674-4300  
**Emergency phone number:** CHEMTREC - 24 HOURS: 800-424-9300

## 2. Hazard(s) identification

**Physical hazards** Flammable aerosols (Category 1)  
Gases under pressure (Liquefied gas)  
**Health hazards** Serious eye damage/eye irritation (Category 2A)  
Reproductive toxicity (fertility) (Category 2)  
Aspiration hazard (Category 1)  
**Label elements (see front side of label)**

## 3. Composition/information on ingredients

### Hazardous components

Chemical name	CAS number	%
hydrotreated light distillates	64742-47-8	30 - 40
liquefied petroleum gas	68476-86-8	10 - 20
catalytic dewaxed heavy paraffin oils	64742-70-7	10 - 20
methyl salicylate	119-36-8	3 - 5
catalytic dewaxed light paraffin oils	64742-71-8	3 - 5
2-methylpentane	107-83-5	1 - 3
dipropylene glycol monomethyl ether	34590-94-8	1 - 3
fatty acids	61788-89-4	1 - 3
hydrotreated light naphtha	64742-49-0	1 - 3
petrolatum	8009-03-9	1 - 3
sodium petroleum sulfonate	68608-26-4	1 - 3
n-hexane	110-54-3	< 0.3
benzotriazole-methanamide	94270-86-7	< 0.2

(Specific chemical identity and/or percentage of composition has been withheld as a trade secret.)

## 4. First-aid measures

**Inhalation** Move to fresh air. Call a physician if symptoms develop or persist.  
**Skin contact** Wash off with soap and water. Get medical attention if irritation develops and persists.  
**Eye contact** Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.  
**Ingestion** Call a physician or poison control center immediately. Rinse mouth.  
Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.  
**Most important symptoms/effects:** Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Narcotic effects.  
**Special treatment needed:** Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

## 5. Fire-fighting measures

**Suitable extinguishing media:** Water fog. Alcohol resistant foam. Dry chemicals. Carbon dioxide (CO<sub>2</sub>). Sand.  
**Unsuitable extinguishing media:** Do not use water jet as an extinguisher, as this will spread the fire.  
**Specific hazards:** Contents under pressure. Pressurized container may rupture when exposed to heat or flame. This product is a poor conductor of electricity and can become electrostatically charged and ignite.  
**Special protective equipment and precautions for firefighters:** Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

## 6. Accidental release measures

**Personal precautions:** Keep people away from and upwind of spill/leak. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them.  
**Containment and cleaning up:** Eliminate all ignition sources. Keep combustibles away from spilled material. Wipe up with absorbent material. Clean surface thoroughly to remove residual contamination. Avoid discharge into drains, water courses, or onto the ground.

## 7. Handling and storage

**Handling:** Pressurized container. Do not pierce or burn, even after use. Avoid contact with skin and eyes. Pregnant or breastfeeding women must not handle this product. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling.  
**Storage:** Store in a cool, dry place and out of direct sunlight. Store in a well-ventilated place. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Avoid spark promoters. Store away from incompatible materials.

## 8. Exposure controls/personal protection

### Occupational exposure limits

Components	Type	Value
catalytic dewaxed heavy paraffin oils	TWA	5 mg/m <sup>3</sup>
catalytic dewaxed light paraffin oils	TWA	5 mg/m <sup>3</sup>
petrolatum	TWA	5 mg/m <sup>3</sup>
2-methylpentane	TWA	500 ppm
dipropylene glycol monomethyl ether	TWA	100 ppm
n-hexane	TWA	50 ppm
hydrotreated light distillates	PEL	100 ppm
hydrotreated light naphtha	PEL	100 ppm

**Appropriate engineering controls:** Mechanical ventilation or local exhaust ventilation is recommended.

### Individual protection measures:

**Eye/face protection:** Wear safety glasses with side shields (or goggles).

**Skin protection:** Use protective gloves such as nitrile or polyvinyl chloride (PVC). Wear suitable protective clothing to prevent skin contact.

**Respiratory protection:** If needed, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Wear positive pressure self-contained breathing apparatus (SCBA) in case of emergency.

## 9. Physical and chemical properties

**Appearance:** Amber liquid with white precipitates.

**Odor threshold:** Not available.

**Melting point/freezing point:** -112 °F (-80 °C)

**Flash point < 20 °F (< -6.7 °C):** Tag Closed Cup

**Explosive limit - lower (%):** 0.6

**Vapor pressure:** 1078 hPa

**Relative density:** 0.86

**Partition coefficient (n-octanol/water):** Not available.

**Decomposition temperature:** Not available.

**VOC (Weight %):** 23.9% (1.7 lb/gal, 205.6 g/L)

**Odor:** Wintergreen.

**pH:** Not available.

**Initial boiling point:** 118 °F (48 °C)

**Evaporation rate:** Fast.

**Explosive limit - upper (%):** 14

**Vapor density > 1 (Air = 1):** Not available.

**Solubility(ies):** Not available.

**Auto-ignition temperature:** 406 °F (207 °C)

**Viscosity:** Not available.

## 10. Stability and reactivity

**Reactivity:** Non-reactive.

**Chemical stability:** Stable

**Possibility of hazardous reactions:** No

**Conditions to avoid:** Heat, flames and sparks. When exposed to extreme heat or hot surfaces, vapors may decompose to harmful or fatal corrosive gases such as hydrogen fluoride. Incompatible materials.

**Incompatible materials:** Strong oxidizing agents.

**Hazardous decomposition products:** Carbon oxides. Aldehydes. Ketones. Organic acids. Hydrogen fluoride. Carbonyl fluoride. Perfluoroisobutylene.

## 11. Toxicological information

**Information on likely routes of exposure:**

**Inhalation:** Prolonged inhalation may be harmful.

**Skin contact:** Prolonged skin contact may cause temporary irritation.

**Eye contact:** Causes serious eye irritation.

**Ingestion:** Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

**Information on toxicological effects:**

**Acute toxicity:** May be fatal if swallowed and enters airways. Narcotic effects.

**Respiratory sensitization:** Not a respiratory sensitizer.

**Skin sensitization:** Not expected to cause skin sensitization.

**Carcinogenicity:** Not considered to be a carcinogen by IARC, ACGIH, NTP or OSHA.

**Reproductive toxicity:** Suspected of damaging fertility.

**Aspiration hazard:** If aspirated into lungs during swallowing or vomiting, may cause chemical pneumonia, pulmonary injury or death.

**Chronic effects:** Prolonged inhalation may be harmful.

## 12. Ecological information

See full SDS for additional information

## 13. Disposal considerations

**Disposal instructions:** This material must be disposed of as hazardous waste.

**Hazardous waste code:** D001: Waste Flammable liquid

## 14. Transport information

**DOT shipping description:** UN1950, Aerosols, flammable, 2.1, Limited Quantity

## 15. Regulatory information

SARA 313 n-hexane

See full SDS for additional information

## 16. Other information

Issue date 17-NOV-17

CRC # 494K-L/1002489-1002491

Version # 02