



Heavy Duty Clear Penetrating Grease

Grasa Penetrante Transparente para Usos Pesados

Contains PTFE
High Adhesive Strength
Effective from -30°F to 500°F
Resists Water Wash Out

Contiene Politetrafluoretileno (PTFE)
Alto Poder Adhesivo
Efectiva entre -30°F y 500°F
Resiste la Limpieza con Agua

DANGER: EXTREMELY FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. SKIN IRRITANT. CONTENTS UNDER PRESSURE. KEEP AWAY FROM CHILDREN.
Read warnings on back panel.

PELIGRO: EXTREMAMENTE INFLAMABLE. NOCIVO O FATAL SI SE INGIERE. IRRITANTE DE LA PIEL. CONTENIDO BAJO PRESIÓN. MANTENGA FUERA DEL ALCANCE DE LOS NIÑOS.
Lea las advertencias en el dorso.



No. 03056
Item# 1003316

Net Wt. / Peso Neto
13 oz (368 g)



Nonfood Compounds
Program Listed: H2
Reg.# 145908



DIRECTIONS: Read entire label before using this product.

1. For personal safety, do not apply while equipment is energized. 2. Shake well before using. 3. Spray in light even coats. 4. Use extension tube for hard to reach areas.

INSTRUCCIONES: Lea toda la etiqueta antes de usar este producto.

1. Por razones de seguridad personal, no aplique el producto mientras el equipo esté conectado. 2. Agite bien antes de usar. 3. Rocíe en capas ligeras y parejas. 4. Utilice el tubo de extensión para alcanzar las áreas difíciles.

Danger: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness.



Precautionary Statements: Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not apply while equipment is energized. Extinguish all flames, pilot lights, and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing mist/vapor. Wash thoroughly after handling. Wear protective gloves. Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst. Dispose of contents/container in accordance with local/regional/national regulations. **First Aid:** If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell.

Contains heptane 426260-76-6, n-butane 106-97-8, propane 74-98-6, hydrotreated light distillates 64742-47-8, and aluminum hydroxide benzoate stearate 54326-11-3. Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. For additional information, consult SDS for this product.

Electrical Shock Hazard: This metal can will conduct electricity. Keep away from all live electrical sources. Failure to observe this warning may result in serious injury and/or flash fire.

Peligro: Aerosol extremadamente inflamable. Contiene gas a presión; puede explotar si se calienta. Puede ser mortal en caso de ingestión y de penetración en las vías respiratorias. Provoca irritación cutánea. Puede provocar somnolencia o vértigo.

Consejos de prudencia: Mantener alejado del calor/de chispas/de llamas al descubierto/de superficies calientes. - No fumar. No vaporizar sobre una llama al descubierto o cualquier otra fuente de ignición. Recipiente a presión: No perforar ni quemar, incluso después del uso. No aplique el producto sobre un equipo conectado. Apague todas las llamas, pilotos y calefactores. El vapor se acumulará rápidamente y puede inflamarse. Utilice solo con ventilación adecuada; mantenga la ventilación durante la utilización del producto hasta que el vapor haya desaparecido. Abra las puertas y ventanas y utilice otros medios para asegurar la provisión de aire fresco al utilizar el producto y mientras se esté secando. Si presenta algunos de los síntomas enumerados en esta etiqueta, aumente la ventilación o deje el área. Evitar respirar nieblas/vapores. Lávese cuidadosamente después de la manipulación. Usar guantes de protección. Almacenar en un lugar bien ventilado. Guardar bajo llave. Proteger de la luz solar. No exponer a una temperatura superior a 50 °C/122 °F. La exposición a altas temperaturas puede provocar que la lata estalle. Eliminar el contenido/recipiente conforme a las reglamentaciones local/regional/nacional.

Primeros Auxilios: En caso de ingestión: Llamar inmediatamente a un centro de toxicología o a un médico. NO provocar el vómito. En caso de contacto con la piel: Lavar con abundante agua. En caso de irritación cutánea: Consultar a un médico. Quitar la ropa contaminada y lavarla antes de volverla a usar. En caso de inhalación: Transportar la persona al aire libre y mantenerla en una posición que le facilite la respiración. Llamar a un CENTRO DE TOXICOLOGÍA o a un médico si la persona se encuentra mal.

Su mal uso deliberado, concentrando e inhalando su contenido es ilegal y puede ser perjudicial o fatal. La inhalación abusiva puede causar la muerte. Para mayor información, consulte la Hoja de Datos de Seguridad para este producto.

Peligro de Descarga Eléctrica: Esta lata de metal puede conducir la electricidad. Manténgala alejada de todas las fuentes eléctricas vivas. El incumplimiento de esta advertencia puede resultar lesiones graves y/o incendio repentino.

Not for use in California.

©2019 CRC Industries, Inc., 885 Louis Dr., Warminster, PA 18974
www.crcindustries.com 19A
800-521-3168 (Technical Info.) • 800-272-4620 (Cust. Care) Made in USA with Foreign and Domestic Components

To review S.D.S.: Tear (DO NOT CUT) label along these perforations and fold back label. After viewing, reattach label. Do not completely remove label until can is empty. Para revisar la Hoja de Datos de Seguridad (HDS): Rasgue (NO CORTE) la etiqueta siguiendo estas perforaciones y dóblela hacia atrás. Al terminar, vuelva a pegar la etiqueta. No la retire completamente hasta que la lata esté vacía.

1. Identification

Product identifier: Heavy Duty Clear Penetrating Grease

Product code No. 03056 (Item# 1003316)

Recommended use Penetrating grease

Restrictions None known.

Manufactured or sold by:

CRC Industries, Inc., 885 Louis Drive, Warminster, PA 18974

Phone: 215-674-4300

Emergency phone number CHEMTREC - 24 HOURS: 800-424-9300

2. Hazard(s) identification

Physical hazards Flammable aerosols (Category 1)

Gases under pressure (Liquefied gas)

Health hazards

Skin corrosion/irritation (Category 2)

Specific target organ toxicity, single exposure (Category 3 narcotic effects)

Aspiration hazard (Category 1)

Label elements (see front side of label)

3. Composition/information on ingredients

Hazardous components

Chemical name	CAS number	%
branched, cyclic and linear heptane	426260-76-6	20 – 30
n-butane	106-97-8	10 – 20
propane	74-98-6	10 – 20
hydrotreated light distillates	64742-47-8	5 – 10
aluminum hydroxide benzoate stearate	54326-11-3	3 – 5

(Specific chemical identity and/or percentage of composition has been withheld as a trade secret.)

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.

Skin contact Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Call a physician or poison control center immediately. Rinse mouth.

Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects Aspiration hazard. Narcotic effects. Skin irritation.

Special treatment needed Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

5. Fire-fighting measures

Suitable extinguishing media Water fog. Foam. Carbon dioxide (CO₂). Dry chemicals.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards Extremely flammable aerosol. Contents under pressure. Pressurized container may explode rupture when exposed to heat or flame. This product is a poor conductor of electricity and can become electrostatically charged. Material will float and may ignite on surface of water.

Special protective equipment and precautions for firefighters Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions Remove all possible sources of ignition in the surrounding area. Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective equipment. Ventilate closed spaces before entering them.

Containment and cleaning up Eliminate all ignition sources. Keep combustibles away from spilled material. Wipe up with absorbent material and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Use appropriate containment to avoid environmental contamination.

7. Handling and storage

Handling Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Avoid breathing mist/vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling.

Storage Protect from sunlight and do not expose to temperatures exceeding 50 °C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source.

8. Exposure controls/personal protection

Occupational exposure limits

Components	Type	Value
propane	PEL	1000 ppm
aluminum hydroxide benzoate stearate	TWA	1 mg/m ³
n-butane	STEL	1000 ppm

Appropriate engineering controls Mechanical ventilation or local exhaust ventilation is recommended.

Individual protection measures:

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection Wear protective gloves such as nitrile. Wear appropriate clothing to prevent skin contact.

Respiratory protection If needed, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Wear positive pressure self-contained breathing apparatus (SCBA) in case of emergency.

9. Physical and chemical properties

Appearance Colorless liquid.

Odor threshold Not available.

Melting point/freezing point Not available.

Flash point 20 °F (-6.7 °C)

Explosive limit - lower (%) 0.5

Vapor pressure 2961 hPa

Relative density 0.72

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature 410 °F (210 °C)

Decomposition temperature Not available.

Viscosity Not available.

VOC (Weight %): 45% (3.0 lb/gal, 360 g/L)

Odor Characteristic.

pH Not applicable.

Initial boiling point 175 °F (79 °C)

Evaporation rate Fast

Explosive limit - upper (%) 6.7

Vapor density > 1 (Air = 1)

Solubility(ies) Negligible in water.

10. Stability and reactivity

Reactivity Non-reactive

Chemical stability Stable

Possibility of hazardous reactions No

Conditions to avoid Heat, flames and sparks. Incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition products None known.

11. Toxicological information

Information on likely routes of exposure:

Inhalation May cause drowsiness, dizziness, headache, nausea, or vomiting.

Skin contact Causes skin irritation.

Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Information on toxicological effects:

Acute toxicity May be fatal if swallowed and enters airways.

Respiratory or skin sensitization Not a sensitizer.

Germ cell mutagenicity Not expected to be mutagenic or genotoxic.

Reproductive toxicity Not expected to cause reproductive or developmental effects.

Specific target organ toxicity May cause drowsiness and dizziness.

Aspiration hazard May be fatal if swallowed and enters airways.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

See full SDS for additional information

13. Disposal considerations

Disposal instructions This material must be disposed of as hazardous waste.

Hazardous waste code D001: Waste Flammable liquid

14. Transport information

DOT shipping description: UN1950, Aerosols, flammable, 2.1, limited quantity

15. Regulatory information

SARA 313 None

See full SDS for additional information

16. Other information

Issue date 12-APR-19

Version # 01