

DIRECTIONS: *Read entire label before using this product.* 1. Do not apply while equipment is energized or on hot surface. 2. Shake well before use. 3. Spray in light, even coats. 4. Use extension tube for hard-to-reach areas.
INSTRUCCIONES: *Lea toda la etiqueta antes de usar este producto.* 1. No lo aplique sobre equipos encendidos o sobre superficies calientes. 2. Rocíe una capa ligera y pareja para proteger las superficies y para que actúe como sellador. 3. Aplique generosamente para aflojar las piezas oxidadas. 4. Rocíe las superficies húmedas hasta que queden libres de excedentes y sin humedad.

Danger: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Causes skin irritation. Causes eye irritation. May cause drowsiness or dizziness. Suspected of damaging fertility.



Precautionary Statements: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container. Do not pierce or burn, even after use. Do not apply while equipment is energized. Extinguish all flames, pilot lights, and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing mist or vapor. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst. Dispose of contents/container in accordance with local/regional/national regulations.

First Aid: If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If exposed or concerned: Get medical advice/attention.

Contains liquefied petroleum gas 68476-86-8, isohexane 64742-49-0, 107-83-5, 110-54-3, 75-83-2, 79-29-9, 96-14-0, petroleum distillates 64742-52-5, and calcium salt 57855-77-3. Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. For additional information, consult SDS for this product.

Electrical Shock Hazard: This metal can will conduct electricity. Keep away from all live electrical sources. Failure to observe this warning may result in serious injury and/or flash fire.

Peligro: Aerosol extremadamente inflamable. Contiene gas a presión; puede explotar si se calienta. Puede ser mortal en caso de ingestión y de penetración en las vías respiratorias. Provoca irritación cutánea. Provoca irritación ocular. Puede provocar somnolencia o vértigo. Susceptible de perjudicar la fertilidad.

Consejos de Prudencia: Procurarse las instrucciones antes del uso. No manipular antes de haber leído y comprendido todas las precauciones de seguridad. Mantener alejado del calor/de chispas/de llamas al descubierto/de superficies calientes. - No fumar. No vaporizar sobre una llama al descubierto o cualquier otra fuente de ignición. Recipiente a presión: No perforar ni quemar, incluso después del uso. No aplique el producto sobre un equipo conectado. Apague todas las llamas, pilotos y calefactores. El vapor se acumulará rápidamente y puede inflamarse. Utilice solo con ventilación adecuada; mantenga la ventilación durante la utilización del producto hasta que el vapor haya desaparecido. Abra las puertas y ventanas y utilice otros medios para asegurar la provisión de aire fresco al utilizar el producto y mientras se esté secando. Si presenta algunos de los síntomas enumerados en esta etiqueta, aumente la ventilación o deje el área. Evitar respirar nieblas o vapores. Lávese cuidadosamente después de la manipulación. Usar guantes/ropa de protección/equipo de protección para los ojos/la cara. Almacenar en un lugar bien ventilado. Guardar bajo llave. Proteger de la luz solar. No exponer a una temperatura superior a 50 °C/122 °F. La exposición a altas temperaturas puede provocar que la lata estalle. Eliminación de contenidos / contenedor en consonancia con los reglamentos locales / regionales / nacionales pertinentes.

Primeros Auxilios: En caso de ingestión: Llamar inmediatamente a un centro de toxicología o a un médico. NO provocar el vómito. En caso de contacto con la piel: Lavar con abundante agua. En caso de irritación cutánea: Consultar a un médico. Quitar la ropa contaminada y lavarla antes de volverla a usar. En caso de inhalación: Transportar la persona al aire libre y mantenerla en una posición que le facilite la respiración. Llamar a un CENTRO DE TOXICOLOGÍA o a un médico si la persona se encuentra mal. En caso de contacto con los ojos: Enjuagar con agua cuidadosamente durante varios minutos. Quitar las lentes de contacto cuando estén presentes y pueda hacerse con facilidad. Proseguir con el lavado. Si la irritación ocular persiste, consultar a un médico. En caso de exposición demostrada o supuesta: consultar a un médico.

Su mal uso deliberado, concentrando e inhalando su contenido es ilegal y puede ser perjudicial o fatal. La inhalación abusiva puede causar la muerte. Para mayor información, consulte la Hoja de Datos de Seguridad para este producto.

Peligro de Descarga Eléctrica: Esta lata de metal puede conducir la electricidad. Manténgala alejada de todas las fuentes eléctricas vivas. El incumplimiento de esta advertencia puede resultar lesiones graves y/o incendio repentino.

©2017 CRC Industries, Inc., 885 Louis Dr., Warminster, PA 18974
 800-521-3168 (Technical Information) • 800-272-4620 (Customer Care)

Made in U.S.A. 17A
 www.crcindustries.com

⚠ WARNING: Cancer - www.P65Warnings.ca.gov.
⚠ ADVERTENCIA: Cáncer - www.P65Warnings.ca.gov.



White Lithium Grease

Grasa blanca de litio

Tough, High Viscosity Film

Excellent Heat and Water Resistance

Película de Alta Viscosidad y Resistencia
Excelente Resistencia al Calor y al Agua



Nonfood Compounds
 Program Listed: H2
 Reg.# 017410



DANGER: EXTREMELY FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. CAUSES SKIN AND EYE IRRITATION. CONTENTS UNDER PRESSURE. KEEP AWAY FROM CHILDREN. Read warnings on back panel.

PELIGRO: EXTREMADAMENTE INFLAMABLE. NOCIVO O FATAL SI SE INGIERE. IRRITA LOS OJOS Y LA PIEL. CONTENIDO BAJO PRESIÓN. MANTENER ALEJADO DEL ALCANCE DE LOS NIÑOS. Lea las advertencias en el dorso.



No. 03080
 Item# 1003341

Net Wt./Peso Neto
10 oz (283 g)



PLEASE RECYCLE WHEN EMPTY

To review S.D.S.: Tear (DO NOT CUT) label along these perforations and fold back label. After viewing, reattach label. Do not completely remove label until can is empty. Para revisar la Hoja de Datos de Seguridad (HDS): Rasgue (NO CORTE) la etiqueta siguiendo estas perforaciones y doblela hacia atrás. Al terminar, vuelva a pegar la etiqueta. No la retire completamente hasta que la lata esté vacía.



1. Identification

Product identifier: White Lithium Grease

Product code No. 03080 (Item# 1003341)

Recommended use Lubricating grease

Restrictions None known.

Manufactured or sold by:

CRC Industries, Inc., 885 Louis Drive, Warminster, PA 18974

Phone: 215-674-4300

Emergency phone number CHEMTREC - 24 HOURS: 800-424-9300

2. Hazard(s) identification

Physical hazards	Flammable aerosols (Category 1) Gases under pressure (Liquefied gas)
Health hazards	Skin corrosion/irritation (Category 2) Serious eye damage/eye irritation (Category 2B) Reproductive toxicity (Category 2 fertility) Specific target organ toxicity, single exposure (Category 3 narcotic effects) Aspiration hazard (Category 1)

Label elements (see front side of label)

3. Composition/information on ingredients

Hazardous components	CAS number	%
Chemical name		
liquefied petroleum gas	68476-86-8	30 – 40
2-methylpentane	107-83-5	20 – 30
hydro-treated heavy naphthenic distillates	64742-52-5	10 – 20
hydro-treated light naphtha	64742-49-0	10 – 20
n-hexane	110-54-3	3 – 5
zinc oxide	1314-13-2	< 1
2,2-dimethylbutane	75-83-2	< 0.3
2,3-dimethylbutane	79-29-8	< 0.3
3-methylpentane	96-14-0	< 0.3
calcium salt	57855-77-3	< 0.3

(Specific chemical identity and/or percentage of composition has been withheld as a trade secret.)

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact Remove contaminated clothing. Wash off with soap and plenty of water. If skin irritation occurs: Get medical advice.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Continue rinsing, if eye irritation persists: Get medical advice.

Ingestion Call a physician or poison control center immediately. Rinse mouth.

Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects May cause drowsiness, dizziness, headache, nausea and vomiting. Skin and eye irritation. Aspiration may cause pulmonary edema and pneumonitis.

Special treatment needed Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

5. Fire-fighting measures

Suitable extinguishing media Water fog, Foam, Carbon dioxide (CO₂), Dry chemical powder.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards Extremely flammable aerosol. Pressurized container may rupture when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective equipment. Ventilate closed spaces before entering them.

Containment and cleaning up Eliminate all ignition sources. Keep combustibles away from spilled material. Absorb in vermiculite, dry sand, earth or other absorbent material and place into containers. Prevent entry into waterways, sewer, basements or confined areas.

7. Handling and storage

Handling Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling.

Storage Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source.

8. Exposure controls/personal protection

Occupational exposure limits

Components	Type	Value
hydro-treated heavy naphthenic distillates	TWA	5 mg/m ³
hydro-treated light naphtha	PEL	400 mg/m ³
n-hexane	TWA	50 ppm
2,2-dimethylbutane	TWA	500 ppm
2,3-dimethylbutane	TWA	500 ppm
2-methylpentane	TWA	500 ppm
3-methylpentane	TWA	500 ppm
titanium dioxide	TWA	10 mg/m ³
zinc oxide	TWA	2 mg/m ³

Appropriate engineering controls Mechanical ventilation or local exhaust ventilation is recommended.

Individual protection measures:

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection Wear protective gloves such as nitrile, PVC or viton/butyl. Wear appropriate clothing to prevent skin contact.

Respiratory protection If needed, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Wear positive pressure self-contained breathing apparatus (SCBA) in case of emergency.

9. Physical and chemical properties

Appearance Off-white semi-solid grease.

Odor threshold Not available.

Melting point/freezing point -245 °F (-154 °C)

Flash point < 0 °F (< -18 °C) Tag Closed Cup

Explosive limit - lower (%) 1

Vapor pressure 2378 hPa

Relative density 0.64

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature 437 °F (225 °C)

Viscosity Not available.

Odor Solvent.

pH Not available.

Initial boiling point 118°F (48 °C)

Evaporation rate Fast.

Explosive limit - upper (%) 8

Vapor density > 1 (Air = 1)

Solubility(ies) Insoluble.

Decomposition temperature Not available.

VOC (Weight %): 84.7% (5.0 lb/gal, 602.7 g/L)

10. Stability and reactivity

Reactivity Non-reactive

Chemical stability Stable

Possibility of hazardous reactions No

Conditions to avoid Heat, flames and sparks. Incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition products None known.

11. Toxicological information

Information on likely routes of exposure:

Ingestion Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Inhalation May cause drowsiness, dizziness, headache, nausea and vomiting.

Skin contact Causes skin irritation.

Eye contact Causes eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics Aspiration hazard. Narcotic effects. Skin and eye irritation.

Information on toxicological effects:

Acute toxicity May be fatal if swallowed and enters airways.

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization Not expected to cause skin sensitization.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

Reproductive toxicity Suspected of damaging fertility.

Aspiration hazard May be fatal if swallowed and enters airways. If aspirated into lungs during swallowing or vomiting, may cause chemical pneumonia, pulmonary injury or death.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

See full SDS for additional information

13. Disposal considerations

Disposal instructions This material must be disposed of as hazardous waste.

Hazardous waste code D001: Waste Flammable liquid

14. Transport information

DOT shipping description: UN1950, Aerosols, flammable, 2.1, limited quantity

15. Regulatory information

SARA 313 n-hexane, zinc oxide

See full SDS for additional information

16. Other information

Issue date 03-OCT-17

CRC # 568F-G/1002591-1002592

Version # 03

