



Welder's Anti Spatter

Producto contra salpicaduras para soldadores

Water Based Formula
Fórmula a Base de Agua

Keeps Tips and Nozzles Clean
Prevents Spatter Build-Up

Mantiene las Puntas y Boquillas limpias
Evita la Acumulación de Salpicaduras



No. 03083
Item# 1003349

Net Wt./Peso Neto
14 oz (396 g)



To review S.D.S.: Tear (DO NOT CUT) label along these perforations and fold back label. After viewing, reattach label. Do not completely remove label until can is empty. Para revisar la Hoja de Datos de Seguridad (HDS): Rasgue (NO CORTE) la etiqueta siguiendo estas perforaciones y doblela hacia atrás. Al terminar, vuelva a pegar la etiqueta. No la retire completamente hasta que la lata esté vacía.

DIRECTIONS: Read entire label before using this product. 1. For personal safety, do not apply while equipment is energized. 2. Shake well and hold can 8" to 12" from surface. 3. Spray a light, even film on area to be welded. Performs best when used on a clean surface. 4. Spray on tips, nozzles and other surfaces to help prevent weld spatter build-up. 5. After welding, wipe or clean area before applying another treatment.

INSTRUCCIONES: Lea toda la etiqueta antes de usar este producto. 1. Por razones de seguridad personal, no aplique el producto mientras el equipo esté conectado. 2. Agite bien y mantenga la lata alejada a una distancia de 8" a 12" de la superficie. 3. Rocíe las áreas a soldar en capas ligeras y parejas. Se obtiene el mejor rendimiento aplicándolo sobre una superficie limpia. 4. Rocíe en las puntas, boquillas y otras superficies para ayudar a evitar la acumulación de salpicaduras de la soldadura. 5. Después de soldar, enjuague o limpie el área antes de aplicar otro tratamiento.

Danger: Extremely flammable aerosol. Contains gas under pressure; may explode if heated.

Precautionary Statements: Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not apply while equipment is energized. Extinguish all flames, pilot lights, and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation: maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst. Dispose of contents/container in accordance with local/regional/national regulations.

First Aid: Wash hands after handling.

Contains water 7732-18-5, dimethyl ether 115-10-6, lactic acid 50-21-5, and white mineral oil 8042-47-5. Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. For additional information, consult SDS for this product.

Electrical Shock Hazard: This metal can will conduct electricity. Do not touch can to live electrical sources, as this may result in serious injury.

Peligro: Aerosol extremadamente inflamable. Contiene gas a presión; puede explotar si se calienta.

Consejos de Prudencia: Mantener alejado del calor/de chimpas/de llamas al descubierto/o de superficies calientes. - No fumar. No vaporizar sobre una llama al descubierto o cualquier otra fuente de ignición. Recipiente a presión: No perforar ni quemar, incluso después del uso. No aplique el producto sobre un equipo conectado. Apague todas las llamas, pilotos y calefactores. El vapor me acumulará rápidamente y puede inflamarme. Utilice molo con ventilación adecuada; mantenga la ventilación durante la utilización del producto hasta que el vapor haya desaparecido. Abra las puertas y ventanas y utilice otros medios para asegurar la provisión de aire fresco al utilizar el producto y mientras me esté secando. Almacenar en un lugar bien ventilado. Proteger de la luz molar. No exponer a una temperatura superior a 50 °C/122 °F. La exposición a altas temperaturas puede provocar que la lata estalle. Eliminación de contenidos / contenedor en consonancia con los reglamentos locales / regionales / nacionales pertinentes.

Primeros Auxilios: Lávese las manos después del uso.

Su mal uso deliberado, concentrando e inhalando su contenido es ilegal y puede ser perjudicial o fatal. La inhalación abusiva puede causar la muerte. Para mayor información, consulte la Hoja de Datos de Seguridad para este producto.

Peligro de Descarga Eléctrica: Esta lata de metal puede conducir la electricidad. No toque la lata con fuentes eléctricas vivas, ya que esto puede resultar en lesiones graves.

VOC Category: Clear Coating MIR Limit: 0.85 (CA) / 1.50 (EPA)

©2017 CRC Industries, Inc., 885 Louis Dr., Warminster, PA 18974
800-521-3168 (Technical Information) • 800-272-4620 (Customer Care)

Made in U.S.A. 17A
www.crcindustries.com

WARNING: Cancer - www.P65Warnings.ca.gov.
ADVERTENCIA: Cáncer - www.P65Warnings.ca.gov.

1. Identification

Product identifier: Welder's Anti Spatter

Product code No. 03083 (Item# 1003349)

Recommended use Prevents spatter from adhering to surrounding metal surfaces during welding

Restrictions None known.

Manufactured or sold by:

CRC Industries, Inc., 885 Louis Drive, Warminster, PA 18974

Phone: 215-674-4300

Emergency phone number CHEMTREC - 24 HOURS: 800-424-9300

2. Hazard(s) identification

Physical hazards Flammable aerosols (Category 1)
Gases under pressure (Liquefied gas)

Hazard health Not classified

Label elements (see front side of label)

3. Composition/information on ingredients

Hazardous components

Chemical name	CAS number	%
water	7732-18-5	60 – 70
dimethyl ether	115-10-6	20 – 30
lactic acid	50-21-5	5 – 10
white mineral oil	8042-47-5	1 – 3

(Specific chemical identity and/or percentage of composition has been withheld as a trade secret.)

4. First-aid measures

Inhalation If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Do not induce vomiting. Never give anything by mouth to a victim who is unconscious or is having convulsions. Get medical attention.

Most important symptoms/effects Direct contact with eyes may cause temporary irritation.

Special treatment needed Treat symptomatically.

5. Fire-fighting measures

Suitable extinguishing media Water fog, Foam, Dry chemical powder, Carbon dioxide (CO₂).

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards Extremely flammable aerosol. Contents under pressure. Pressurized container may rupture when exposed to heat or flame.

Special protective equipment and precautions for firefighters Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions Many vapors are heavier than air and will spread along ground and collect in low or confined areas. Do not touch damaged containers or spilled material unless wearing appropriate protective equipment.

Containment and cleaning up Eliminate all ignition sources. Keep combustibles away from spilled material. Wipe up with absorbent material. Clean surface thoroughly to remove residual contamination. Prevent entry into waterways, sewer, basements or confined areas. Avoid release to the environment.

7. Handling and storage

Handling Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Avoid breathing mist or vapor. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling.

Storage Store in a cool, dry place (below 122°F/50°C) and out of direct sunlight. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Store away from incompatible materials.

8. Exposure controls/personal protection

Occupational exposure limits

Components	Type	Value
white mineral oil	TWA	5 mg/m ³

Appropriate engineering controls Mechanical ventilation or local exhaust ventilation is recommended.

Individual protection measures:

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection Wear protective gloves such as nitrile or PVC. Wear appropriate clothing to prevent skin contact.

Respiratory protection If needed, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies.

9. Physical and chemical properties

Appearance Milky white liquid.

Odor threshold Not available.

Melting point/freezing point 32 °F (0 °C)

Flash point > 265 °F (> 129 °C) Tag Closed Cup

Explosive limit - lower (%) 3

Vapor pressure 1146 hPa

Relative density 0.92

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature 500 °F (260 °C)

Decomposition temperature Not available.

Viscosity Not available.

VOC (Weight %): 25.3% (2.1 lb/gal, 254 g/L)

Odor Slight ethereal.

pH 7 – 8

Initial boiling point 212 °F (100 °C)

Evaporation rate Slow.

Explosive limit - upper (%) 23.5

Vapor density > 1 (Air = 1)

Solubility(ies) Soluble in water

10. Stability and reactivity

Reactivity Non-reactive

Chemical stability Stable

Possibility of hazardous reactions No

Conditions to avoid Heat, flames and sparks. Incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition products Carbon oxides. Acid smoke.

11. Toxicological information

Information on likely routes of exposure:

Inhalation Prolonged inhalation may be harmful.

Skin contact Prolonged skin contact may cause temporary irritation.

Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Ingestion of large amounts may produce gastrointestinal disturbances including irritation, nausea, and diarrhea.

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation.

Information on toxicological effects:

Acute toxicity Not classified.

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization Not expected to cause skin sensitization.

Carcinogenicity Not considered to be a carcinogen by IARC, ACGIH, NTP or OSHA.

Reproductive toxicity Not expected to cause reproductive or developmental effects.

Aspiration hazard Based on available data, the classification criteria are not met.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

See full SDS for additional information

13. Disposal considerations

Disposal instructions The dispensed liquid product is not a RCRA hazardous waste.

Empty container can be recycled.

Hazardous waste code Not regulated.

14. Transport information

DOT shipping description: UN1950, Aerosols, flammable, 2.1, limited quantity

15. Regulatory information

SARA 313 None

See full SDS for additional information

16. Other information

Issue date 29-JAN-18

Version # 03