



**DIRECTIONS:** Read entire label before using this product. 1. Do not apply while equipment is energized. 2. For best performance, use on a clean surface. 3. Shake well before use. 4. Hold can 8" to 12" away from surface to be sprayed. 5. Spray with a light, even film and allow to cure for 10 to 15 minutes. 6. Wipe off excess with a clean cloth. 7. Repeat application if necessary.

**INSTRUCCIONES:** Lea toda la etiqueta antes de usar este producto. 1. No aplique el productomientras el equipo esté conectado. 2. Para obtener elmejor rendimiento, aplíquelo sobre una superficie limpia. 3. Agite bien antes de usar. 4. Mantenga la lata a una distancia de entre 8" y 12" de la superficie a rociar. 5. Rociar con una ligera, pareja, y deje secar de 10 a 15 minutos. 6. Quite el excedente con un trapo limpio. 7. Repita la aplicación si fuera necesario.

**Danger:** Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. Suspected of damaging the unborn child. May cause damage to organs through prolonged or repeated exposure.



**Precautionary Statements:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container; Do not pierce or burn, even after use. Do not breathe mist or vapor. Do not apply while equipment is energized. Extinguish all flames, pilot lights and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst. Dispose of contents/container in accordance with local/regional/national regulations.

**First Aid:** If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If exposed or concerned: Get medical advice/attention.

Contains acetone 67-64-1, isopropyl alcohol 67-63-0, n-butane 106-97-8, propane 74-98-6, heptanes 426260-76-6, 142-82-5, molybdenum disulfide 1317-33-5, medium aliph. solvent naphtha 64742-88-7, and toluene 108-88-3. Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. For additional information, consult SDS for this product.

**Electrical Shock Hazard:** This metal can will conduct electricity. Keep away from all live electrical sources. Failure to observe this warning may result in serious injury and/or flash fire.

**Peligro:** Aerosol extremadamente inflamable. Contiene gas a presión; puede explotar si se calienta. Puede ser mortal en caso de ingestión y de penetración en las vías respiratorias. Provoca irritación ocular grave. Puede irritar las vías respiratorias. Puede provocar somnolencia o vértigo. Susceptible de dañar al feto. Puede provocar daños en los órganos tras exposiciones prolongadas o repetidas.

**Consejos de Prudencia:** Procurarse las instrucciones antes del uso. No manipular antes de haber leído y comprendido todas las precauciones de seguridad. Mantener alejado del calor/de chispas/de llamas al descubierta/de superficies calientes. - No fumar. No vaporizar sobre una llama al descubierta o cualquier otra fuente de ignición. Recipiente a presión: No perforar ni quemar, incluso después del uso. No respirar nieblas o vapores. No aplique el producto sobre un equipo conectado. Apague todas las llamas, pilotos y calefactores. El vapor se acumulará rápidamente y puede inflamarse. Utilice solo con ventilación adecuada; mantenga la ventilación durante la utilización del producto hasta que el vapor haya desaparecido. Abra las puertas y ventanas y utilice otros medios para asegurar la provisión de aire fresco al utilizar el producto y mientras se esté secando. Si presenta algunos de los síntomas enumerados en esta etiqueta, aumente la ventilación o deje el área. Lávese cuidadosamente después de la manipulación. Usar quantes/ropa de protección/equipo de protección para los ojos/la cara. Almacenar en un lugar bien ventilado. Guardar bajo llave. Proteger de la luz solar. No exponer a una temperatura superior a 50°C/122°F. La exposición a altas temperaturas puede provocar que la lata estalle. Eliminación de contenidos / contenedor en consonancia con los reglamentos locales / regionales / nacionales pertinentes.

**Primeros Auxilios:** En caso de ingestión: Llamar inmediatamente a un centro de toxicología o a un médico. NO provocar el vómito. En caso de inhalación: Transportar a la persona al aire libre y mantenerla en una posición que le facilite la respiración. Llamar a un CENTRO DE TOXICOLOGIA o a un médico si la persona se encuentra mal. En caso de contacto con los ojos: Enjuagar con agua cuidadosamente durante varios minutos. Quitar las lentes de contacto cuando estén presentes y pueda hacerse con facilidad. Proseguir con el lavado. Si la irritación ocular persiste, consultar a un médico. En caso de exposición demostrada o sospecha: consultar a un médico.

Su mal uso deliberado, concentrando e inhalando su contenido es ilegal y puede ser perjudicial o fatal. La inhalación abusiva puede causar la muerte. Para mayor información, consulte la Hoja de Datos de Seguridad para este producto.

**Peligro de Descarga Eléctrica:** Esta lata de metal puede conducir la electricidad. Manténgala alejada de todas las fuentes eléctricas vivas. El incumplimiento de esta advertencia puede resultar lesiones graves y/o incendio repentino.

©2017 CRC Industries, Inc., 885 Louis Dr., Warminster, PA 18974  
800-521-3168 (Technical Information) • 800-272-4620 (Customer Care)

Made in U.S.A. 17A  
www.crcindustries.com



# Dry Moly Lube

## Lubricante Seco de Molibdeno

Non-Conductive, Dry Film  
Ideal with High Temperature and Pressure

No es Conductor, Capa Seca  
Ideal para las Altas Temperaturas y la Presión

**DANGER:** EXTREMELY FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. VAPOR HARMFUL. EYE IRRITANT. MAY CAUSE RESPIRATORY IRRITATION. CONTENTS UNDER PRESSURE. KEEP AWAY FROM CHILDREN. Read warnings on back panel.

**PELIGRO:** EXTREMAMENTE INFLAMABLE. SU INGESTIÓN ES PERJUDICIAL O MORTAL. VAPOR DAÑINO. IRRITANTE DE LOS OJOS. PUEDE IRRITAR LAS VÍAS RESPIRATORIAS. CONTENIDO BAJO PRESIÓN. MANTENGA FUERA DEL ALCANCE DE LOS NIÑOS. Lea las advertencias en el dorso.



No. 03084  
Item# 1003351

Net Wt./Peso Neto  
11 oz (311 g)



To review S.D.S.: Tear (DO NOT CUT) label along these perforations and fold back label. After viewing, reattach label. Do not completely remove label until can is empty. Para revisar la Hoja de Datos de Seguridad (HDS): Rasgue (NO CORTE) la etiqueta siguiendo estas perforaciones y doblela hacia atrás. Al terminar, vuelva a pegar la etiqueta. No la retire completamente hasta que la lata esté vacía.

## 1. Identification

**Product identifier:** Dry Moly Lube  
**Product code No.** 03084 (Item# 1003351)  
**Recommended use:** Dry film lubricant  
**Restrictions:** None known.  
**Manufactured or sold by:** CRC Industries, Inc., 885 Louis Drive, Warminster, PA 18974  
**Phone:** 215-674-4300  
**Emergency phone number:** CHEMTREC - 24 HOURS: 800-424-9300

## 2. Hazard(s) identification

**Physical hazards** Flammable aerosols (Category 1)  
Gases under pressure (Liquefied gas)  
**Health hazards** Serious eye damage/eye irritation (Category 2A)  
Reproductive toxicity, the unborn child (Category 2)  
Specific target organ toxicity, single exposure (respiratory tract irritation, narcotic effects) (Category 3)  
Specific target organ toxicity, repeated exposure (Category 2)  
Aspiration hazard (Category 1)

Label elements (see front side of label)

## 3. Composition/information on ingredients

### Hazardous components

Chemical name	CAS number	%
acetone	67-64-1	25 - 35
isopropyl alcohol	67-63-0	20 - 30
n-butane	106-97-8	20 - 30
propane	74-98-6	5 - 10
heptane, branched, cyclic and linear	426260-76-6	3 - 5
molybdenum disulphide	1317-33-5	1 - 3
n-heptane	142-82-5	1 - 3
medium aliph. solvent naphtha	64742-88-7	1 - 3
toluene	108-88-3	< 0.3

(Specific chemical identity and/or percentage of composition has been withheld as a trade secret.)

## 4. First-aid measures

**Inhalation** Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.  
**Skin contact** Wash off with soap and water. If skin irritation occurs: Get medical advice/attention.  
**Eye contact** Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.  
**Ingestion** Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.  
**Most important symptoms/effects** May cause drowsiness, dizziness, headache, nausea and vomiting. Severe eye irritation. May cause respiratory irritation. Aspiration may cause pulmonary edema and pneumonitis.  
**Special treatment needed** Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

## 5. Fire-fighting measures

**Suitable extinguishing media** Water fog, Alcohol resistant foam, Dry chemical powder, Carbon dioxide (CO2).  
**Unsuitable extinguishing media** Do not use water jet as an extinguisher, as this will spread the fire.  
**Specific hazards** Extremely flammable aerosol. Contents under pressure. Pressurized container may rupture when exposed to heat or flame. During fire, gases hazardous to health may be formed.  
**Special protective equipment and precautions for firefighters** Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

## 6. Accidental release measures

**Personal precautions** Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective equipment. Ventilate closed spaces before entering them.  
**Containment and cleaning up** Eliminate all ignition sources. Keep combustibles away from spilled material. Wipe up with absorbent material and place into containers. Prevent entry into waterways, sewer, basements or confined areas.

## 7. Handling and storage

**Handling** Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not breathe mist or vapor. Avoid contact with eyes. Avoid prolonged exposure. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling.  
**Storage** Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place, away from incompatible materials.

## 8. Exposure controls/personal protection

Occupational exposure limits	Type	Value
<b>Components</b>		
acetone	TWA	250 ppm
isopropyl alcohol	TWA	200 ppm
molybdenum disulphide	TWA	3 mg/m3 (respirable fraction) 10 mg/m3 (inhalable fraction)
n-heptane	TWA	400 ppm
propane	PEL	1000 ppm
n-butane	STEL	1000 ppm
medium aliphatic solvent naphtha	PEL	100 ppm
toluene	TWA	20 ppm

**Appropriate engineering controls** Mechanical ventilation or local exhaust ventilation is recommended.

### Individual protection measures:

**Eye/face protection** Wear safety glasses with side shields (or goggles).

**Skin protection** Wear protective gloves such as nitrile or neoprene. Wear appropriate clothing to prevent skin contact.

**Respiratory protection** If needed, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Wear positive pressure self-contained breathing apparatus (SCBA) in case of emergency.

## 9. Physical and chemical properties

**Appearance** Gray liquid.  
**Odor threshold** Not available.  
**Melting point/freezing point** Not available.  
**Flash point** -20 °F (-29 °C) Pensky-Martens Closed Cup  
**Explosive limit - lower (%)** 1  
**Vapor pressure** 13.5 kPa  
**Relative density** 0.71  
**Partition coefficient (n-octanol/water)** Not available.  
**Decomposition temperature** Not available.  
**VOC (Weight %):** 61.8% (3.7 lb/gal, 438.8 g/L)

**Odor Solvent.**  
**pH** Not available.  
**Initial boiling point** Not available.  
**Evaporation rate** Fast.  
**Explosive limit - upper (%)** 12.8  
**Vapor density** 1.55 (Air = 1)  
**Solubility(ies)** Not available.  
**Auto-ignition temperature** Not available.  
**Viscosity** 7 mm<sup>2</sup>/s (104 °F (40 °C))

## 10. Stability and reactivity

**Reactivity** Non-reactive  
**Chemical stability** Stable  
**Possibility of hazardous reactions** No  
**Conditions to avoid** Heat, flames and sparks. Incompatible materials.  
**Incompatible materials** Acids. Strong oxidizing agents. Nitrates. Isocyanates. Fluorine. Chlorine.  
**Hazardous decomposition products** Carbon oxides. Sulfur oxides. Metal oxides.

## 11. Toxicological information

### Information on likely routes of exposure:

**Inhalation** May cause drowsiness, dizziness, headache, nausea and vomiting. May cause irritation to the respiratory system.  
**Skin contact** Prolonged skin contact may cause temporary irritation.  
**Eye contact** Causes serious eye irritation.  
**Ingestion** Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.  
**Symptoms related to the physical, chemical and toxicological characteristics** Aspiration hazard. Severe eye irritation. May cause drowsiness, dizziness, headache, nausea and vomiting. May cause respiratory irritation.  
**Information on toxicological effects:**  
**Acute toxicity** May be fatal if swallowed and enters airways.  
**Respiratory sensitization** Not a respiratory sensitizer.  
**Skin sensitization** Not expected to cause skin sensitization.  
**Carcinogenicity** Not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.  
**Reproductive toxicity** Suspected of damaging the unborn child.  
**Aspiration hazard** May be fatal if swallowed and enters airways. If aspirated into lungs during swallowing or vomiting, may cause chemical pneumonia, pulmonary injury or death.  
**Chronic effects** May cause damage to organs through prolonged or repeated exposure.

## 12. Ecological information

See full SDS for additional information

## 13. Disposal considerations

**Disposal instructions** If discarded, this product is considered a RCRA ignitable waste, D001.  
**Hazardous waste code** D001: Waste Flammable liquid

## 14. Transport information

**DOT shipping description:** UN1950, Aerosols, flammable, 2.1, limited quantity

## 15. Regulatory information

SARA 313 None.  
See full SDS for additional information

## 16. Other information

Issue date 12-DEC-17

Version # 04