

DIRECTIONS: Read entire label before using this product. 1. For personal safety, do not apply while equipment is energized. 2. May be harmful to some plastics. Test on small area before using. Do not use on sensitive electronic equipment. Use one of CRC's precision cleaner products. 3. To remove grease, oil, hydraulic fluids and related contaminants, spray until clean. For hard to reach areas, use the extension tube. For heavier soils, apply product and allow to penetrate for several minutes. Re-apply and soil should lift off. 4. Air dry or dry with a clean absorbent cloth. 5. If necessary, repeat application. 6. Allow to dry thoroughly and vent before reactivating system.

INSTRUCCIONES: Lea toda la etiqueta antes de usar este producto. 1. Por razones de seguridad personal, no aplique el producto mientras el equipo esté conectado. 2. Puede dañar algunos plásticos. Haga una prueba en una zona pequeña antes de usarlo. No lo utilice en productos electrónicos delicados. Utilice uno de los limpiadores de precisión CRC. 3. Para eliminar grasa, aceite, fluidos hidráulicos y otros tipos de contaminantes, rocíe hasta que quede limpio. Para alcanzar las áreas difíciles, utilice el tubo de extensión. Para suciedades más rebeldes, aplique el producto y permita que penetre durante varios minutos. Aplique nuevamente y la suciedad se despegará. 4. Seque al aire o con un trapo limpio y absorbente. 5. Si fuera necesario, repita la aplicación. 6. Deje que seque completamente y ventile antes de conectar nuevamente el sistema.

Danger: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. May cause drowsiness or dizziness.



Precautionary Statements: Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container. Do not pierce or burn, even after use. Do not apply while equipment is energized. Extinguish all flames, pilot lights, and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing mist or vapor. Wash thoroughly after handling. Wear eye protection/face protection. Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst. Dispose of contents/container in accordance with local/regional/national regulations.

First Aid: If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Contains acetone 67-64-1, carbon dioxide 124-38-9, and heptanes 142-82-5, 589-34-4, 591-76-4, 617-78-7. Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. For additional information, consult SDS for this product.

Electrical Shock Hazard: This metal can will conduct electricity. Keep away from all live electrical sources. Failure to observe this warning may result in serious injury and/or flash fire.

Peligro: Aerosol extremadamente inflamable. Contiene gas a presión; puede explotar si se calienta. Provoca irritación ocular grave. Puede provocar somnolencia o vértigo.

Consejos de Prudencia: Mantener alejado del calor/de chispas/de llamas al descubierto/de superficies calientes. - No fumar. No vaporizar sobre una llama al descubierto o cualquier otra fuente de ignición. Recipiente a presión: No perforar ni quemar, incluso después del uso. No aplique el producto sobre un equipo conectado. Apague todas las llamas, pilotos y calefactores. El vapor se acumulará rápidamente y puede inflamarse. Utilice solo con ventilación adecuada; mantenga la ventilación durante la utilización del producto hasta que el vapor haya desaparecido. Abra las puertas y ventanas y utilice otros medios para asegurar la provisión de aire fresco al utilizar el producto y mientras se esté secando. Si presenta algunos de los síntomas enumerados en esta etiqueta, aumente la ventilación o deje el área. Evitar respirar neblinas o vapores. Lávese cuidadosamente después de la manipulación. Usar equipo de protección para los ojos/la cara. Almacenar en un lugar bien ventilado. Guardar bajo llave. Proteger de la luz solar. No exponer a una temperatura superior a 50 °C/122 °F. La exposición a altas temperaturas puede provocar que la lata estalle. Eliminación de contenidos / contenedor en consonancia con los reglamentos locales / regionales / nacionales pertinentes.

Primeros Auxilios: En caso de inhalación: Transportar la persona al aire libre y mantenerla en una posición que le facilite la respiración. Llamar a un CENTRO DE TOXICOLOGIA o a un médico si la persona se encuentra mal. En caso de contacto con los ojos: Enjuagar con agua cuidadosamente durante varios minutos. Quitar las lentes de contacto cuando estén presentes y pueda hacerse con facilidad. Proseguir con el lavado. Si la irritación ocular persiste, consultar a un médico.

Su mal uso deliberado, concentrando e inhalando su contenido es ilegal y puede ser perjudicial o fatal. La inhalación abusiva puede causar la muerte. Para mayor información, consulte la Hoja de Datos de Seguridad para este producto.

Peligro de Descarga Eléctrica: Esta lata de metal puede conducir la electricidad. Manténgala alejada de todas las fuentes eléctricas vivas. El incumplimiento de esta advertencia puede resultar lesiones graves y/o incendio repentino.

©2017 CRC Industries, Inc., 885 Louis Dr., Warminster, PA 18974
800-521-3168 (Technical Information) • 800-272-4620 (Customer Care)

Made in U.S.A. 17A
www.crcindustries.com

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.
ADVERTENCIA: Cáncer y Daño Reproductivo - www.P65Warnings.ca.gov.



Insta-Solv® Degreaser

Desengrasante

Low VOC

Fast Evaporation

Non-Chlorinated

Bajo VOC

Rápida Evaporación

No Clorado



Nonfood Compounds
Program Listed: K1
Reg.# 140887



DANGER: EXTREMELY
FLAMMABLE. EYE IRRITANT.
CONTENTS UNDER PRESSURE.
KEEP AWAY FROM CHILDREN.
Read warnings on back panel.

PELIGRO: EXTREMAMENTE
INFLAMABLE. IRRITANTE DE
LOS OJOS. CONTENIDO BAJO
PRESIÓN. MANTENGA FUERA
DEL ALCANCE DE LOS NIÑOS.
Lea las advertencias en el dorso.



No. 03100
Item# 1003372

Net Wt. / Peso Neto
14 oz (396 g)

To review S.D.S., Tear, DO NOT CUT label along these perforations and fold back label. After viewing, reattach label. Do not completely remove label until can is empty. Para revisar la Hoja de Datos de Seguridad (HDS), Rasgue (NO CORTE) la etiqueta siguiendo estas perforaciones y doblela hacia atrás. Al terminar, vuelva a pegar la etiqueta. No la retire completamente hasta que la lata esté vacía.



1. Identification

Product identifier: Insta-Solv® Degreaser

Product code No. 03100 (Item# 1003372)

Recommended use General purpose degreaser

Restrictions None known.

Manufactured or sold by: CRC Industries, Inc., 885 Louis Drive, Warminster, PA 18974

Phone: 215-674-4300

Emergency phone number CHEMTREC - 24 HOURS: 800-424-9300

2. Hazard(s) identification

Physical hazards Flammable aerosols (Category 1)

Gases under pressure (Compressed gas)

Health hazards Serious eye damage/eye irritation (Category 2A)

Specific target organ toxicity, single exposure (Category 3 narcotic effects)

Label elements (see front side of label)

3. Composition/information on ingredients

Hazardous components

Chemical name	CAS number	%
acetone	67-64-1	80 – 90
carbon dioxide	124-38-9	10 – 20
n-heptane	142-82-5	1 – 3
3-methylhexane	589-34-4	< 1
2-methylhexane	591-76-4	< 0.3
3-ethylpentane	617-78-7	< 0.2

(Specific chemical identity and/or percentage of composition has been withheld as a trade secret.)

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth.

Most important symptoms/effects May cause drowsiness, dizziness, headache, nausea and vomiting.

Irritation of nose and throat. Severe eye irritation. Aspiration may cause pulmonary edema and pneumonitis.

Special treatment needed Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

5. Fire-fighting measures

Suitable extinguishing media Water fog. Alcohol resistant foam. Carbon dioxide (CO2). Dry chemical powder. Sand. Earth.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards Extremely flammable aerosol. Pressurized container may rupture when exposed to heat or flame. This product is a poor conductor of electricity and can become electrostatically charged. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions Remove all possible sources of ignition in the surrounding area. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective equipment. Ventilate closed spaces before entering them.

Containment and cleaning up Eliminate all ignition sources. Keep combustibles away from spilled material. Wipe up cloth, fleece, or other absorbent material and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Use appropriate containment to avoid environmental contamination.

7. Handling and storage

Handling Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Avoid breathing mist or vapor. Avoid contact with eyes. Avoid prolonged exposure. When using, do not eat, drink, or smoke. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling.

Storage Protect from sunlight and do not expose to temperatures exceeding 50 °C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source.

8. Exposure controls/personal protection

Occupational exposure limits

Components	Type	Value
acetone	TWA	250 ppm
carbon dioxide	TWA	5000 ppm
n-heptane	TWA	400 ppm
2-methylhexane	TWA	400 ppm
3-ethylpentane	TWA	400 ppm
3-methylhexane	TWA	400 ppm

Appropriate engineering controls Mechanical ventilation or local exhaust ventilation is recommended.

Individual protection measures:

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection Wear protective gloves such as neoprene, butyl rubber, and viton/butyl. Wear appropriate clothing to prevent skin contact.

Respiratory protection If needed, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Wear positive pressure self-contained breathing apparatus (SCBA) in case of emergency.

9. Physical and chemical properties

Appearance Colorless liquid.

Odor threshold Not available.

Melting point/freezing point -139 °F (-95 °C)

Flash point < 0 °F (< -18 °C) Tag Closed Cup

Explosive limit - lower (%) 1.1

Vapor pressure 5935 hPa

Relative density 0.86

Partition coefficient (n-octanol/water) Not available.

Decomposition temperature Not available.

VOC (Weight %): 2.7% (0.2 lb/gal, 21.3 g/L)

Odor Ketone.

pH Not available.

Initial boiling point 133 °F (56 °C)

Evaporation rate Fast.

Explosive limit - upper (%) 12.8

Vapor density 2 (Air = 1)

Solubility(ies) Slightly soluble.

Auto-ignition temperature 540 °F (282 °C)

Viscosity Not available.

10. Stability and reactivity

Reactivity Non-reactive

Possibility of hazardous reactions No

Conditions to avoid Heat, flames and sparks. Incompatible materials.

Incompatible materials Acids. Aluminum.

Hazardous decomposition products Carbon oxides.

Chemical stability Stable

11. Toxicological information

Information on likely routes of exposure:

Inhalation May cause drowsiness, dizziness, headache, nausea, and vomiting.

Skin contact Prolonged skin contact may cause temporary irritation.

Eye contact Causes serious eye irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Narcotic effects. Severe eye irritation.

Information on toxicological effects:

Acute toxicity None known.

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization Not expected to cause skin sensitization.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

Reproductive toxicity Not expected to cause reproductive or developmental effects.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

See full SDS for additional information

13. Disposal considerations

Disposal instructions If discarded, this product is considered a RCRA ignitable waste, D001.

Hazardous waste code D001: Waste Flammable liquid

14. Transport information

DOT shipping description: UN1950, Aerosols, flammable, 2.1, limited quantity

15. Regulatory information

SARA 313 None

See full SDS for additional information

16. Other information

Issue date 28-NOV-17

CRC #732/1002760

Version # 02