

DIRECTIONS: Read entire label before using this product.

1. Do not apply while equipment is energized. 2. Before applying, pre-test on a hidden section of surface to be cleaned for color fastness and surface integrity. 3. Shake well and spray on surface to be cleaned. Allow product to set for 10 to 30 seconds. 4. Wipe or rinse clean with potable water or a lint-free cloth, sponge or paper towel. 5. Heavy soils may require repeat applications.

INSTRUCCIONES: Lea toda la etiqueta antes de usar este producto.

1. Por razones de seguridad personal, no aplique el producto mientras el equipo esté conectado. 2. Antes de aplicar, pruebe previamente sobre una parte no visible de la superficie a limpiar para probar que no altere el color ni dañe la superficie. 3. Agite bien y rocíe sobre la superficie a limpiar. Deje actuar el producto durante 10 a 30 segundos. 4. Limpie o enjuague con agua potable o un paño sin pelusas, una esponja o una toalla de papel. 5. Las suciedades más rebeldes podrían necesitar aplicaciones repetidas.

Danger: Flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye damage.



Precautionary Statements: Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wash thoroughly after handling. Wear eye protection/face protection. Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst. Dispose of contents/container in accordance with local/regional/national regulations.

First Aid: If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor.

Contains ethyl lactate 97-64-3, acetone 67-64-1, carbon dioxide 124-38-9, dipropylene glycol monopropyl ether 29911-27-1, and ethoxylated alcohol 68439-50-9. Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. For additional information, consult SDS for this product.

Electrical Shock Hazard: This metal can will conduct electricity. Keep away from all live electrical sources. Failure to observe this warning may result in serious injury and/or flash fire.

Peligro: Aerosol inflamable. Contiene gas a presión; puede explotar si se calienta. Provoca lesiones oculares graves.

Consejos de prudencia: Mantener alejado del calor/de chispas/de llamas al descubierto/de superficies calientes. - No fumar. No vaporizar sobre una llama al descubierto o cualquier otra fuente de ignición. Recipiente a presión: No perforar ni quemar, incluso después del uso. Usar con ventilación adecuada. Abra las puertas y ventanas y utilice otros medios para asegurar la provisión de aire fresco al utilizar el producto y mientras se esté secando. Si presenta algunos de los síntomas enumerados en esta etiqueta, aumente la ventilación o deje el área. Lávese cuidadosamente después de la manipulación. Usar equipo de protección para los ojos/la cara. Almacenar en un lugar bien ventilado. Proteger de la luz solar. No exponer a una temperatura superior a 50 °C/122 °F. La exposición a altas temperaturas puede provocar que la lata estalle. Eliminación de contenidos / contenedor en consonancia con los reglamentos locales / regionales / nacionales pertinentes.

Primeros Auxilios: En caso de contacto con los ojos: Enjuagar con agua cuidadosamente durante varios minutos. Quitar las lentes de contacto cuando estén presentes y pueda hacerse con facilidad. Proseguir con el lavado. Llamar inmediatamente a un centro de toxicología o a un médico.

Su mal uso deliberado, concentrando e inhalando su contenido es ilegal y puede ser perjudicial o fatal. La inhalación abusiva puede causar la muerte. Para mayor información, consulte la Hoja de Datos de Seguridad para este producto.

Peligro de Descarga Eléctrica: Esta lata de metal puede conducir la electricidad. Manténgala alejada de todas las fuentes eléctricas vivas. El incumplimiento de esta advertencia puede resultar lesiones graves y/o incendio repentino.

©2019 CRC Industries, Inc., 885 Louis Dr., Warminster, PA 18974
800-521-3168 (Technical Info.) • 800-272-4620 (Cust. Care) *Made in USA with Foreign and Domestic Components*

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.
ADVERTENCIA: Cáncer y Daño Reproductivo - www.P65Warnings.ca.gov.



Super-Soy™ Degreaser

Desengrasante

**Biodegradable Formula
Dissolves Grease, Tar, and Oil
Fórmula Biodegradable
Disuelve Grasa, Brea y Aceite**



Nonfood Compounds
Program Listed: K1
Reg.# 141172



DANGER: FLAMMABLE.
CAUSES SERIOUS EYE DAMAGE.
CONTENTS UNDER PRESSURE.
KEEP AWAY FROM CHILDREN.
Read warnings on back panel.

PELIGRO: INFLAMABLE.
PROVOCA LESIONES
OCULARES GRAVES.
CONTENIDO BAJO PRESIÓN.
MANTENGA FUERA DEL
ALCANCE DE LOS NIÑOS.
Lea las advertencias en el dorso.



No. 03135
Item# 1003413

Net Wt. / Peso Neto
15 oz (425 g)

To review S.D.S. - Tear (DO NOT CUT) label along these perforations and fold back label. After rereading, reattach label. Do not completely remove label until can is empty. Para revisar la Hoja de Datos de Seguridad (HDS) - Resaque (NO CORTE) la etiqueta siguiendo estas perforaciones y dóblela hacia atrás. Al terminar, vuelva a pegar la etiqueta. No la retire completamente hasta que la lata esté vacía.



1. Identification

Product identifier: Super-Soy™ Degreaser

Product code No. 03135 (Item# 1003413)

Recommended use General purpose degreaser

Restrictions None known.

Manufactured or sold by:

CRC Industries, Inc., 885 Louis Drive, Warminster, PA 18974

Phone: 215-674-4300

Emergency phone number CHEMTREC - 24 HOURS: 800-424-9300

2. Hazard(s) identification

Physical hazards Flammable aerosols (Category 2)

Gases under pressure (Compressed gas)

Health hazards Serious eye damage/eye irritation (Category 1)

Label elements (see front side of label)

3. Composition/information on ingredients

Hazardous components

Chemical name	CAS number	%
ethyl lactate	97-64-3	5 – 10
acetone	67-64-1	1 – 3
carbon dioxide	124-38-9	1 – 3
dipropylene glycol monopropyl ether	29911-27-1	1 – 3
ethoxylated alcohol	68439-50-9	< 0.3

(Specific chemical identity and/or percentage of composition has been withheld as a trade secret.)

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.

Ingestion Rinse mouth. Get medical advice/attention if you feel unwell.

Most important symptoms/effects Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.

Special treatment needed Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

5. Fire-fighting measures

Suitable extinguishing media Water fog, foam, dry chemical powder, carbon dioxide, sand or earth.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards Contents under pressure. Pressurized container may rupture when exposed to heat or flame. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. Material will float and can be re-ignited on surface of water.

Special protective equipment and precautions for firefighters Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions Keep people away from and upwind of spill/leak. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained.

Containment and cleaning up Eliminate all ignition sources. Keep combustibles away from spilled material. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Prevent entry into waterways, sewer, basements or confined areas. Use appropriate containment to avoid environmental contamination.

7. Handling and storage

Handling Pressurized container: Do not pierce or burn, even after use. Do not smoke while using or until sprayed surface is thoroughly dry. Do not get this material in contact with eyes. Avoid contact with skin. Avoid prolonged exposure. Use only in well-ventilated areas. Avoid release to the environment.

Storage Store in a cool, dry place (below 122°F/50°C) and out of direct sunlight. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Avoid spark promoters. Store in a well-ventilated place.

8. Exposure controls/personal protection

Occupational exposure limits

Components	Type	Value
acetone	TWA	250 ppm
carbon dioxide	TWA	5000 ppm

Appropriate engineering controls Mechanical ventilation or local exhaust ventilation is recommended.

Individual protection measures:

Eye/face protection Wear safety glasses with side shields (or goggles) and a face shield.

Skin protection Wear protective gloves such as neoprene or nitrile. Wear appropriate clothing to prevent skin contact.

Respiratory protection If needed, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Wear positive pressure self-contained breathing apparatus (SCBA) in case of emergency.

9. Physical and chemical properties

Appearance Light yellow liquid.

Odor Mild.

Odor threshold Not available.

pH Not available.

Melting point/freezing point -139 °F (-95 °C)

Initial boiling point 133 °F (56 °C)

Flash point 84 °F (29 °C) Tag Closed Cup

Evaporation rate Slow.

Explosive limit - lower (%) 0.7

Explosive limit - upper (%) 12.8

Vapor pressure 1609 hPa

Vapor density > 1 (Air = 1)

Relative density 0.91

Solubility(ies) Insoluble in water.

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature 401 °F (205 °C)

Decomposition temperature Not available.

Viscosity Not available.

VOC (Weight %): 8.2% (0.6 lbs/gal, 73.1 g/l)

10. Stability and reactivity

Reactivity Non-reactive

Chemical stability Stable

Possibility of hazardous reactions No

Conditions to avoid Heat, flames and sparks. Incompatible materials.

Incompatible materials Strong acids. Alkalis.

Hazardous decomposition products Methanol is given off during processing and by reaction with water.

11. Toxicological information

Information on likely routes of exposure:

Ingestion Ingestion of large amounts may produce gastrointestinal disturbances including irritation, nausea, and diarrhea.

Inhalation Prolonged inhalation may be harmful.

Skin contact Prolonged skin contact may cause temporary irritation.

Eye contact Causes serious eye damage.

Symptoms related to the physical, chemical, and toxicological characteristics Severe eye irritation.

Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.

Information on toxicological effects:

Acute toxicity Not known.

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization Not expected to cause skin sensitization.

Carcinogenicity Not considered to be a carcinogen by IARC, ACGIH, NTP or OSHA.

Reproductive toxicity Not expected to cause reproductive or developmental effects.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

See full SDS for additional information

13. Disposal considerations

Disposal instructions This material must be disposed of as hazardous waste.

Hazardous waste code D001: Waste Flammable liquid

14. Transport information

DOT shipping description: UN1950, Aerosols, flammable, 2.1, limited quantity

15. Regulatory information

SARA 313 None

See full SDS for additional information

16. Other information

Issue date 08-MAY-17

CRC #699A/1002748

Version # 02