



**DIRECTIONS: Read entire label before using this product. 1. Do not apply while equipment is energized or on hot surfaces. 2. Spray in light, even coats to chutes, dead plates and rails requiring lubrication or moisture protection. 3. Repeat step 2 until adequate lubrication or protection is achieved. Use only the necessary amount to achieve results. 4. Re-apply as needed to maintain performance.**

**INSTRUCCIONES: Lea toda la etiqueta antes de usar este producto. 1. No lo aplique sobre equipos encendidos o sobre superficies calientes. 2. Rocíe en capas ligeras y parejas sobre tolvas, soleras de horno y rieles que requieren lubricación. 3. Repita el paso 2 hasta alcanzar la lubricación o protección adecuada. 4. Aplique nuevamente, según sea necesario, para mantener el rendimiento.**

**Danger:** Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Causes skin irritation. Causes eye irritation. May cause drowsiness or dizziness. Suspected of damaging fertility or the unborn child.



**Precautionary Statements:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not apply while equipment is energized. Extinguish all flames, pilot lights, and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing mist/vapor. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst. Dispose of contents/container in accordance with local/regional/national regulations.

**First Aid:** If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If exposed or concerned: Get medical advice/attention.

Contains liquefied petroleum gas 68476-86-8, hydrotreated light naphtha 64742-49-0, 2-methylpentane 107-83-5, hydrotreated light distillates 64742-47-8, and n-hexane 110-54-3. Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. For additional information, consult SDS for this product.

**Electrical Shock Hazard:** This metal can will conduct electricity. Keep away from all live electrical sources. Failure to observe this warning may result in serious injury and/or flash fire.

**Peligro:** Aerosol extremadamente inflamable. Contiene gas a presión; puede explotar si se calienta. Puede ser mortal en caso de ingestión y de penetración en las vías respiratorias. Provoca irritación cutánea. Provoca irritación ocular. Puede provocar somnolencia o vértigo. Susceptible de perjudicar la fertilidad o dañar al feto.

**Consejos de prudencia:** Procurarse las instrucciones antes del uso. No manipular antes de haber leído y comprendido todas las precauciones de seguridad. Mantener alejado del calor/de chispas/de llamas al descubierta/de superficies calientes. - No fumar. No vaporizar sobre una llama al descubierta o cualquier otra fuente de ignición. Recipiente a presión: No perforar ni quemar, incluso después del uso. No aplique el producto sobre un equipo conectado. Apague todas las llamas, pilotos y calefactores. El vapor se acumulará rápidamente y puede inflamarse. Utilice solo con ventilación adecuada; mantenga la ventilación durante la utilización del producto hasta que el vapor haya desaparecido. Abra las puertas y ventanas y utilice otros medios para asegurar la provisión de aire fresco al utilizar el producto y mientras se esté secando. Si presenta algunos de los síntomas enumerados en esta etiqueta, aumente la ventilación o deje el área. Evitar respirar nieblas/vapores. Lávese cuidadosamente después de la manipulación. Usar guantes/ropa de protección/equipo de protección para los ojos/la cara. Almacenar en un lugar bien ventilado. Guardar bajo llave. Proteger de la luz solar. No exponer a una temperatura superior a 50 °C/122 °F. La exposición a altas temperaturas puede provocar que la lata estalle. Eliminar el contenido/recipiente conforme a las reglamentaciones local/regional/nacional.

**Primeros Auxilios:** En caso de ingestión: Llamar inmediatamente a un centro de toxicología o a un médico. NO provocar el vómito. En caso de contacto con la piel: Lavar con abundante agua. En caso de irritación cutánea: Consultar a un médico. Quitar la ropa contaminada y lavarla antes de volverla a usar. En caso de inhalación: Transportar la persona al aire libre y mantenerla en una posición que le facilite la respiración. Llamar a un CENTRO DE TOXICOLOGÍA o a un médico si la persona se encuentra mal. En caso de contacto con los ojos: Enjuagar con agua cuidadosamente durante varios minutos. Quitar las lentes de contacto cuando estén presentes y pueda hacerse con facilidad. Proseguir con el lavado. Si la irritación ocular persiste, consultar a un médico. En caso de exposición demostrada o supuesta: consultar a un médico.

Su mal uso deliberado, concentrando e inhalando su contenido es ilegal y puede ser perjudicial o fatal. La inhalación abusiva puede causar la muerte. Para mayor información, consulte la Hoja de Datos de Seguridad para este producto.

**Peligro de Descarga Eléctrica:** Esta lata de metal puede conducir la electricidad. Manténgala alejada de todas las fuentes eléctricas vivas. El incumplimiento de esta advertencia puede resultar lesiones graves y/o incendio repentino.

©2018 CRC Industries, Inc., 885 Louis Dr., Warminster, PA 18974

800-521-3168 (Technical Information) • 800-272-4620 (Customer Care)

Made in U.S.A. 18A

www.crcindustries.com

**WARNING: Reproductive Harm - www.P65Warnings.ca.gov.**  
**ADVERTENCIA: Daño Reproductivo - www.P65Warnings.ca.gov.**



# Chute Lube® Silicone Lubricant Lubricante de Silicona

**Reduces Friction**

**Helps Packages Slide Easier  
Wide Temperature Range**

**Reduce la Fricción**

**Ayuda a los Paquetes más Fácil Deslizarse  
Amplio Rango de Temperaturas**



Nonfood Compounds  
Program Listed: H2  
Reg.# 138031



**DANGER: EXTREMELY  
FLAMMABLE. HARMFUL OR  
FATAL IF SWALLOWED.  
EYE AND SKIN IRRITANT.  
CONTENTS UNDER PRESSURE.  
KEEP AWAY FROM CHILDREN.  
Read warnings on back panel.**

**PELIGRO: INFLAMABLE.  
NOCIVO O FATAL SI SE INGIERE.  
IRRITANTE DE OJOS Y PIEL.  
CONTENIDO BAJO PRESIÓN.  
MANTENGA FUERA DEL  
ALCANCE DE LOS NIÑOS.  
Lea las advertencias en el dorso.**



No. 03204  
Item# 1003459

**Net Wt. / Peso Neto  
11 oz (311 g)**

To view S.D.S.: Tear (DO NOT CUT) label along these perforations and fold back label. After viewing, reattach label. Do not completely remove label until can is empty. Para revisar la Hoja de Datos de Seguridad (HDS): Resque (NO CORTE) la etiqueta siguiendo estas perforaciones y dóblela hacia atrás. Al terminar, vuelva a pegar la etiqueta. No la retire completamente hasta que la lata esté vacía.

## 1. Identification

**Product identifier:** Chute Lube® Silicone Lubricant

**Product code** No. 03204 (Item# 1003459)

**Recommended use** Lubricant for package handling chutes

**Restrictions** None known.

**Manufactured or sold by:**

CRC Industries, Inc., 885 Louis Drive, Warminster, PA 18974

**Phone:** 215-674-4300

**Emergency phone number** CHEMTREC - 24 HOURS: 800-424-9300

## 2. Hazard(s) identification

|                         |  |
|-------------------------|--|
| <b>Physical hazards</b> | Flammable aerosols (Category 1)<br>Gases under pressure (Liquefied gas)  |
| <b>Health hazards</b>   | Skin corrosion/irritation (Category 2)<br>Serious eye damage/eye irritation (Category 2B)<br>Reproductive toxicity (Category 2)<br>Specific target organ toxicity, single exposure (Category 3 narcotic effects)<br>Aspiration hazard (Category 1) |

**Label elements (see front side of label)**

## 3. Composition/information on ingredients

### Hazardous components

| Chemical name                 | CAS number | %       |
|-------------------------------|------------|---------|
| liquefied petroleum gas       | 68476-86-8 | 60 – 70 |
| hydroreated light naphtha     | 64742-49-0 | 30 – 40 |
| 2-methylpentane               | 107-83-5   | 3 – 5   |
| hydroreated light distillates | 64742-47-8 | 1 – 3   |
| n-hexane                      | 110-54-3   | 1 – 3   |

(Specific chemical identity and/or percentage of composition has been withheld as a trade secret.)

## 4. First-aid measures

**Inhalation** Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

**Skin contact** Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention.

**Eye contact** Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

**Ingestion** Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

**Most important symptoms/effects** Aspiration hazard. Narcotic effects. Eye and skin irritation.

**Special treatment needed** Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

## 5. Fire-fighting measures

**Suitable extinguishing media** Water fog. Foam. Dry chemical powder. Carbon dioxide (CO<sub>2</sub>).

**Unsuitable extinguishing media** Do not use water jet as an extinguisher, as this will spread the fire.

**Specific hazards** Extremely flammable aerosol. Contents under pressure. Pressurized container may rupture when exposed to heat or flame. During fire, gases hazardous to health may be formed.

**Special protective equipment and precautions for firefighters** Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

## 6. Accidental release measures

**Personal precautions** Keep people away from and upwind of spill/leak. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained.

**Containment and cleaning up** Eliminate all ignition sources. Keep combustibles away from spilled material. Prevent product from entering drains. Stop the flow of material, if this is without risk. Wipe up with absorbent material. Clean surface thoroughly to remove residual contamination.

## 7. Handling and storage

**Handling** Do not use if spray button is missing or defective. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment.

**Storage** Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C/122 °F. Do not puncture, incinerate or crush. Store in a well-ventilated place. This material can accumulate static charge which may cause spark and become an ignition source.

## 8. Exposure controls/personal protection

### Occupational exposure limits

| Components                    | Type | Value   |
|-------------------------------|------|---------|
| hydroreated light distillates | PEL  | 100 ppm |
| n-hexane                      | TWA  | 50 ppm  |
| 2-methylpentane               | TWA  | 500 ppm |

**Appropriate engineering controls** Mechanical ventilation or local exhaust ventilation is recommended.

**Individual protection measures:**

**Eye/face protection** Wear safety glasses with side shields (or goggles).

**Skin protection** Wear protective gloves such as nitrile, PVC, or viton/butyl. Wear appropriate clothing to prevent skin contact.

**Respiratory protection** If needed, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Wear positive pressure self-contained breathing apparatus (SCBA) in case of emergency.

## 9. Physical and chemical properties

**Appearance** Light yellow liquid.

**Odor threshold** Not available.

**Melting point/freezing point** -58 °F (-50 °C)

**Flash point** < 0 °F (-18 °C)

**Explosive limit - lower (%)** 0.6

**Vapor pressure** 3183 hPa

**Relative density** 0.68

**Auto-ignition temperature** 428 °F (220 °C)

**Viscosity** Not available.

**VOC (Weight %):** 95% (5.4 lb/gal, 649 g/L)

**Odor** Petroleum.

**pH** Not available.

**Initial boiling point** 118 °F (48 °C)

**Evaporation rate** Fast.

**Explosive limit - upper (%)** 8.0

**Vapor density** > 1 (Air = 1)

**Solubility(ies)** Not available.

## 10. Stability and reactivity

**Reactivity** Non-reactive

**Chemical stability** Stable

**Possibility of hazardous reactions** No

**Conditions to avoid** Heat, hot surfaces, sparks, open flames and other ignition sources. Incompatible materials.

**Incompatible materials** Strong oxidizing agents.

**Hazardous decomposition products** Carbon oxides.

## 11. Toxicological information

**Information on likely routes of exposure:**

**Inhalation** May cause drowsiness, dizziness, headache, nausea, and vomiting.

**Skin contact** Causes skin irritation.

**Eye contact** Causes eye irritation.

**Ingestion** Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

**Symptoms related to the physical, chemical and toxicological characteristics** Aspiration hazard. Narcotic effects. Eye and skin irritation.

**Information on toxicological effects:**

**Acute toxicity** May be fatal if swallowed and enters airways.

**Respiratory or skin sensitization** Not a sensitizer.

**Carcinogenicity** Not classifiable as to carcinogenicity to humans.

**Reproductive toxicity** Suspected of damaging fertility or the unborn child.

**Specific target organ toxicity** May cause drowsiness and dizziness.

**Aspiration hazard** May be fatal if swallowed and enters airways.

**Chronic effects** Prolonged inhalation may be harmful.

## 12. Ecological information

**See full SDS for additional information**

## 13. Disposal considerations

**Disposal instructions** The dispensed liquid product is a RCRA hazardous waste.

**Hazardous waste code** D001: Waste Flammable liquid

## 14. Transport information

**DOT shipping description:** UN1950, Aerosols, flammable, 2.1, limited quantity

## 15. Regulatory information

**SARA 313 n-hexane**

**See full SDS for additional information**

## 16. Other information

**Issue date** 8-OCT-18

**CRC #** 685B-C/1002729-1002731

**Version #** 02