

Gasket Remover

Para obtener información adicional en Español, visite www.crcindustries.com.

CRC Gasket Remover effectively removes and loosens gaskets, adhesives, sealants, cements and paints. Penetrating action loosens gasket material in minutes. Eliminates excessive scraping that could cause damage to gasket surfaces and flanges.

DIRECTIONS: Read entire label before using this product.

1. Do not apply to energized equipment. **2.** Always wear eye and hand protection when using this product. **3.** Protect painted and finished surfaces from overspray. **4.** For gasket and adhesive removal, liberally apply CRC Gasket Remover on gasket surface and let penetrate for 5 to 10 minutes. Use a gasket scraper to remove old gasket and a dry rag to remove adhesive. **5.** For paint removal, liberally apply CRC Gasket Remover to painted surface. Allow to dry and remove paint with bristled brush.

For the best sealing results, thoroughly clean gasket surface and use K&W® Copper Coat gasket adhesive for a leak-proof seal.

Contains acetone 67-64-1, liquefied petroleum gas 68476-86-8, N-methyl-2-pyrrolidone 872-50-4, xylene 1330-20-7, and ethylbenzene 100-41-4.

DANGER: Contents are flammable. Vapors can accumulate and create a flammable atmosphere. Do not use near open flame or other sources of ignition. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F/49°C. Exposure to high temperature may cause can to burst. Do not place in direct sunlight or near any heat source. Avoid breathing vapor. Avoid contact with skin and eyes. Overexposure to liquid or vapors can cause serious eye and skin irritation, upper respiratory tract irritation, headache, dizziness, or drowsiness. Product may pose an aspiration hazard if swallowed. Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. Vapors are heavier than air and can accumulate in low areas. If you experience any symptoms listed on this label, increase ventilation, use respiratory protection or leave the area.

FIRST AID: In case of eye or skin contact, flush with water for 15 minutes. If too much is breathed, remove to fresh air. If swallowed, call your poison control center at 1-800-222-1222.

DISPOSAL: All used and unused product should be disposed of in conformance with local, state, and federal regulations. DO NOT dump in sewers, floor drains, on the ground or into any body of water.

ELECTRICAL SHOCK HAZARD: This metal can will conduct electricity. Keep away from all live electrical sources. Failure to observe this warning may result in serious injury and/or flash fire.

KEEP AWAY FROM CHILDREN



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

VOC Category: Gasket Adhesive Remover

VOC Limit: 50%

©2017 CRC Industries, Inc., Warminster, PA 18974
www.crcindustries.com
Made in U.S.A.

800-521-3168 (Technical Information)
800-272-8963 (Customer Care)
17A



Gasket Remover

Removedor de juntas



Easily Removes Gaskets & Sealants



PLEASE RECYCLE
WHEN EMPTY



Eliminates Excessive Scraping & Cleaning
Also Removes Graffiti, Paint & Decals

DANGER: FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. VAPOR HARMFUL. EYE AND SKIN IRRITANT. CONTENTS UNDER PRESSURE. READ WARNINGS ON BACK PANEL.

Net Wt. 12 oz (340 g)

No. 05021
Item# 1003638