




# Zinc-It® Instant Cold Galvanize

**Actively Fights Corrosion**

*GALVANIZADOR  
FRÍO INSTANTÁNEO*

**Stops Rust • Dries Fast**



**DANGER:** EXTREMELY FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. VAPOR HARMFUL. CAUSES SKIN IRRITATION. CONTENTS UNDER PRESSURE. READ WARNINGS ON BACK PANEL.

Net Wt. 13 oz (368 g)

No. 05048  
Item# 1003659



## Zinc-It® Instant Cold Galvanize

Para obtener información adicional en Español, visite [www.crcindustries.com](http://www.crcindustries.com).

Galvanized protection fights rust and corrosion with >92% pure zinc. Provides the protection of expensive hot dip galvanizing.

- Protects iron and steel through sacrificial action. Protects even when scratched or abraded.
- Protects welds or bare metals on previously galvanized surfaces.
- Use as touch up for marred galvanized surfaces.

### DIRECTIONS: *Read entire label before using this product.*

**1.** Prepare surface by removing all paint, loose rust, scale, oil and grease. Surface must be bare metal clean and dry. Mask area not to be sprayed. **2.** Shake well until agitator ball is free. Repeat while using. **3.** Best results are obtained when sprayed above 60°F. Hold can 8-12 inches from surface. Apply in light, even coats. **4.** When finished spraying, clean valve by turning can upside down and pressing button. If clogging occurs, remove button, clean slot and orifice with fine wire and replace carefully. Important: Some paints are not compatible with either cold or hot dipped galvanized surfaces. Check paint for compatibility.

Contains elemental zinc 7440-66-6, propane 74-98-6, toluene 108-88-3, n-butane 106-97-8, stoddard solvent 8052-41-3, isopropyl alcohol 67-63-0, aluminum sodium salt silicic acid 1344-00-9, zinc oxide 1314-13-2, and n-methyl-2-pyrrolidone 872-50-4.

**DANGER:** Contents are extremely flammable. Do not smoke while spraying. Extinguish all flames, pilot lights, and heaters. Do not apply while equipment is energized. Vapors will accumulate readily and may ignite. Maintain ventilation during use and until vapors are gone. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F/49°C. Exposure to high temperature may cause can to burst. Do not place in direct sunlight or near any heat source. Do not use near open flame or other sources of ignition. Avoid breathing vapor. Avoid contact with skin and eyes. Exposure can cause skin irritation, eye irritation, upper respiratory tract irritation, headache, dizziness, or drowsiness. Product may pose an aspiration hazard if swallowed. Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation, use respiratory protection, or leave the area.

**FIRST AID:** If swallowed, call your poison control center at 1-800-222-1222. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.

**DISPOSAL:** All used and unused product should be disposed of in conformance with applicable regulations. Do not dump in sewers, on the ground, or into any body of water.

### KEEP AWAY FROM CHILDREN

**ELECTRICAL SHOCK HAZARD:** This metal can will conduct electricity. Keep away from all live electrical sources. Failure to observe this warning may result in serious injury and/or flash fire.

 **WARNING:** Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

VOC Category: Metallic Coating    MIR Limit: 1.90 (EPA) 1.25 (CA)

©2018 CRC Industries, Inc., Warminster, PA 18974  
[www.crcindustries.com](http://www.crcindustries.com)  
Made in U.S.A.

800-521-3168 (Technical Information)  
800-272-8963 (Customer Care)  
18A