

# MAF Sensor Cleaner

Para obtener información adicional en Español, visite [www.crcindustries.com](http://www.crcindustries.com).

Most fuel injected vehicles are equipped with a mass air flow (MAF) sensor to measure air velocity which the computer uses to determine the proper air/fuel mixture. However, the MAF sensor gets dirty with debris, oil, air filter fibers, dust and pollen causing inaccurate measurements of intake air flow which results in a "rich" running engine, loss of power and excess emissions.

- Plastic Safe • Increases Horsepower • Reduces Rough Idle
- Decreases Hesitation and Pinging • Improves Fuel Economy & MPG
- Entire Job Takes Less than 10 Minutes!

Don't use aggressive chemicals like brake cleaner, carburetor cleaner or air intake cleaner on MAF sensors. These can cause serious damage to sensitive parts. Use CRC MAF SENSOR CLEANER – the right product for the job!

## FOR ALL GAS AND DIESEL VEHICLES EQUIPPED WITH MAF SENSORS

**DIRECTIONS:** Read entire label before using this product.

1. Do not apply while equipment is energized. Turn off vehicle. 2. Locate your MAF between the air box and throttle body. 3. Unplug MAF wire harness. 4. Remove MAF housing. 5. Place shop towel under MAF to catch any run-off. 6. With straw attached, apply 10-15 sprays of CRC MAF SENSOR CLEANER onto hot-wires or hot plate. DO NOT contact hot-wires with straw or any other object. 7. Be sure to spray all sides of the MAF sensor and clean all wires and connectors. 8. Reassemble MAF and allow to dry thoroughly before reactivating. 9. For best results clean your mass air flow sensor every time you clean or change your air filter. 10. DO NOT use on vehicles with a Karman-Vortex air flow sensor, e.g. Toyota Supra Turbos, Mitsubishi's and most Lexus vehicles.

## QUICK DRYING FORMULA. SAFE TO USE ON MOST SENSORS & CONNECTORS!

\* Test data obtained on a dynamometer at R/T Tuning in Montgomeryville, PA.

Contains isohexane 107-83-5, 64742-49-0, 110-54-3, carbon dioxide 124-38-9, 2,2,4-trimethylpentane 540-84-1.

**DANGER:** Contents extremely flammable. Do not smoke while spraying. Extinguish all flames, pilot lights, and heaters. Do not apply while equipment is energized. Vapors will accumulate readily and may ignite. Maintain ventilation during use and until vapors are gone. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F/49°C. Exposure to high temperature may cause can to burst. Do not place in direct sunlight or near any heat source. Avoid breathing vapor. Avoid contact with skin and eyes. Exposure can cause skin or eye irritation, upper respiratory tract irritation, headache, dizziness, or drowsiness. Product may pose an aspiration hazard if swallowed. Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area.

**FIRST AID:** In case of skin or eye contact, flush with water for 15 minutes. If too much is breathed, remove to fresh air. If swallowed, call your poison control center at 1-800-222-1222.  
**DISPOSAL:** All used and unused product should be disposed of in conformance with local, state, and federal regulations. Do not dump in sewers, on the ground, or into any body of water.

**ELECTRICAL SHOCK HAZARD:** This metal can will conduct electricity. Keep away from all live electrical sources. Failure to observe this warning may result in serious injury and/or flash fire.

**KEEP AWAY FROM CHILDREN**

**WARNING:** Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

©2017 CRC Industries, Inc., Warminster, PA 18974  
[www.crcindustries.com](http://www.crcindustries.com)  
Made in U.S.A.

800-521-3168 (Technical Information)  
800-272-8963 (Customer Care)  
DOT 2Q 17A



# Mass Air Flow Sensor Cleaner

Limpiador del sensor de flujo de aire



Safe for delicate hot wire, hot plate & plastic

Evaporates in Seconds



PLEASE RECYCLE WHEN EMPTY



0 78254 05110 9

Increases  
**MPG**  
& Fuel Economy

Proven to Gain  
**4-10**  
Horsepower at Wheels

Improves  
**AFR**  
Air-to-Fuel Ratio

**REAL TESTS • REAL RESULTS**

**DANGER:** EXTREMELY FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. CAUSES SKIN AND EYE IRRITATION. CONTENTS UNDER PRESSURE. READ WARNINGS ON BACK PANEL.

Net Wt. 11 oz (311 g)

No. 05110  
Item# 1003729