



Heavy Duty Silicone

Multi-Use Silicone Lubricant

LUBRICANTE MULTIUSO

Stops Rust • Waterproofs • Protects



DANGER: EXTREMELY FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. EYE AND SKIN IRRITANT. CONTENTS UNDER PRESSURE. READ WARNINGS ON BACK PANEL.

Net Wt. 11 oz (311 g)

No. 05174
Item# 1003743

Heavy Duty Silicone

Para obtener información adicional en Español, visite www.crcindustries.com.

CRC Heavy Duty Silicone is a non-corrosive, VOC compliant formula that lubricates and eliminates squeaking and binding caused by friction. Its film is clean, odorless, and highly resistant to water. Its lubricating properties are retained as low as -40°F and as high as 400°F.

• Lubricates metal, rubber, nylon and wood. • **NOT FOR USE ON PLASTICS.** • Protects and lubricates tools, jacks, hoists, locks, latches, seat adjusters, zippers, springs and pulleys. • Meets FDA Regulation CFR-21-178.3570 for lubricants with incidental food contact.

DIRECTIONS: *Read entire label before using this product.*

1. For personal safety, do not apply while equipment is energized. **2.** Cover and protect plastic and painted surfaces from overspray. Check on small area before using. Not for use on automotive interiors. **3.** Apply light, even film. **4.** Hold can 8" to 10" away from surface to be sprayed. **5.** Use extension tube for pinpoint accuracy. **6.** Wipe off excess with cloth. **7.** Repeat applications periodically.

Contains acetone 67-64-1, hydrocarbon propellant 68476-86-8, heptanes 142-82-5, 589-34-4, methylcyclohexane 108-87-2, and polydimethylsiloxane 63148-62-9.

DANGER: Contents are extremely flammable. Do not smoke while spraying. Extinguish all flames, pilot lights, and heaters. Do not apply while equipment is energized. Vapors will accumulate readily and may ignite. Maintain ventilation during use and until vapors are gone. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F/49°C. Exposure to high temperature may cause can to burst. Do not place in direct sunlight or near any heat source. Avoid breathing vapor or contact with skin and eyes. Overexposure to liquid or vapors can cause serious eye or skin irritation, irritation to upper respiratory tract, headache, dizziness, or drowsiness. Product may pose an aspiration hazard if swallowed. Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area.

FIRST AID: In case of eye or skin contact, flush with water for 15 minutes. If too much is breathed, remove to fresh air. If swallowed, call your poison control center at 1-800-222-1222.

DISPOSAL: All used and unused product should be disposed of in conformance with local, state and federal regulations. Do not dump in sewers, on the ground, or into any body of water.

ELECTRICAL SHOCK HAZARD: This metal can will conduct electricity. Keep away from all live electrical sources. Failure to observe this warning may result in serious injury and/or flash fire.

KEEP AWAY FROM CHILDREN

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

©2017 CRC Industries, Inc., Warminster, PA 18974
800-272-8963 Customer Care
800-521-3168 Technical Info

www.crcindustries.com
Made in USA
17A



PLEASE RECYCLE WHEN EMPTY

**DOT 2Q
M5749 DSC**



0 78254 105174 11