




# FUEL THERAPY® Diesel Injector Cleaner Plus

■ CLEANS INJECTORS

■ IMPROVES FUEL LUBRICITY

No. 05255  
Item# 1003754



05255

NET WEIGHT 363 lb (164 kg)



## DANGER

Flammable liquid and vapor. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. Harmful if inhaled. Suspected of causing genetic defects. Suspected of causing cancer.

## PRECAUTIONARY STATEMENTS

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use only explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing vapors. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Store in a well-ventilated place. Keep cool. Do not store container above 100 °F/38 °C. Store locked up. Dispose of contents/container in accordance with local/regional/national regulations.

## FIRST AID

If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. In case of fire: Do not use water jet as an extinguisher, as this will spread the fire.

Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. For additional information, consult SDS for this product.

## DIRECTIONS: Read entire label before using this product.

FOR PREVENTATIVE MAINTENANCE: One quart treats up to 125 gallons of diesel fuel. One gallon treats up to 500 gallons of diesel fuel. FOR PRE-EXISTING CONDITIONS OR TREATMENT OF BIODIESEL FUELS: One quart treats up to 50 gallons of diesel fuel. One gallon treats up to 200 gallons of fuel. Pour into fuel tank and operate normally. For cold conditions, use CRC Diesel Fuel Cond. w/ Anti-Gel (No. 05425 / Item# 1003807). For anticipated extreme conditions, add CRC Diesel Cold Flow™ Anti-Gel with Lubricity (No. 05632 / Item# 1003794) to fuel prior to temperature drop.

This diesel fuel additive complies with the federal ultra-low sulfur content requirements for use in all diesel motor vehicles and non-road engines.

- Prevents Corrosion
- Improves MPG
- Stabilizes Fuel
- OK for Biodiesel

Contains hydrodesulfurized middle distillates 64742-80-9, hydrotreated light distillates 64742-47-8, hydrotreated heavy naphtha 64742-48-9, and oleic acid 112-80-1.

©2017 CRC Industries, Inc.  
885 Louis Dr.  
Warminster, PA 18974  
800-521-3168 (Technical information)  
800-272-8963 (Customer Care)  
www.crcindustries.com  
17A Made in U.S.A  
FOR EMERGENCIES CALL CHEMTREC  
1-800-424-9300



Batch No.:  
Date Code: