



# Ultra Screwloose®

## Penetrating Oil

ACEITE PENETRANTE

Penetrates Fast • Dissolves Rust & Corrosion



**DANGER: FLAMMABLE, HARMFUL OR FATAL IF SWALLOWED. EYE AND SKIN IRRITANT. CONTENTS UNDER PRESSURE. READ WARNINGS ON BACK PANEL.**

Net Wt. 11 oz (311 g)

No. 05330  
Item# 1003768

## Ultra Screwloose®

Para obtener información adicional en Español, visite [www.crcindustries.com](http://www.crcindustries.com).

New advanced Ultra Screwloose® outperforms other leading brands in penetration, speed, and corrosion resistance. Ultra Screwloose® loosens rusted fasteners, frozen parts, pipe threads, and couplings quickly and effectively.

Use Ultra Screwloose® on automobiles, household items, plumbing fixtures, agricultural equipment, guns, sporting equipment, and locks. Dissolves gums, rust and corrosion. Provides proper lubrication and prevents corrosion.

**DIRECTIONS:** Read entire label before using this product. Follow all directions in numerical order.

1. Do not apply while equipment is energized. Allow to dry at least 4 to 6 hours before energizing.
2. Apply liberal coating to corroded surfaces, saturating problem areas.
3. Tap joint lightly to aid penetration.
4. Proceed with disassembly.
5. Repeat application for stubborn joints, fasteners and assemblies.

Contains petroleum distillates 64742-47-8, 64742-48-9, 64742-70-7, 64742-71-8, and carbon dioxide 124-38-9.

**DANGER:** Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F/49°C. Exposure to high temperature may cause can to burst. Do not place in direct sunlight or near any heat source. Product is flammable and should be kept from all flames and other ignition sources. Avoid breathing mist or vapor. Avoid contact with skin and eyes. Overexposure to liquid or vapors can cause severe irritation to eyes, skin, and upper respiratory tract, and central nervous system effects such as headache, dizziness, drowsiness, nausea or confusion. Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. Vapors are heavier than air and can accumulate in low areas. If you experience any symptoms listed on this label, increase ventilation or leave the area. Product may pose an aspiration hazard if swallowed.

**FIRST AID:** If swallowed, call your poison control center at 1-800-222-1222. In case of eye or skin contact, flush with water for at least 15 minutes. If too much is breathed, remove to fresh air. For all cases of overexposure, contact a physician.

**DISPOSAL:** All used and unused product should be disposed of in conformance with local, state and federal regulations. DO NOT dump in sewers, floor drains, on the ground or into any body of water.

**ELECTRICAL SHOCK HAZARD:** This metal can will conduct electricity. Keep away from all live electrical sources. Failure to observe this warning may result in serious injury and/or flash fire.

KEEP AWAY FROM CHILDREN



**WARNING: Cancer and Reproductive Harm -**  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

©2018 CRC Industries, Inc., Warminster, PA 18974  
800-272-8963 Customer Care  
800-321-3168 Technical Info

[www.crcindustries.com](http://www.crcindustries.com)  
Made in USA  
1&A



PLEASE RECYCLE  
WHEN EMPTY

DOT 2G  
M5749 DSC

