

Clean-R-Carb™ Carburetor Cleaner

Para obtener información adicional en Español, visite www.crcindustries.com.

CRC Clean-R-Carb™ dissolves carburetor deposits such as gum, sludge and varnish to improve fuel system performance and insure maximum fuel economy. Safe for use with oxygen sensors and catalytic converters.

DIRECTIONS: Read entire label before using this product.

This product is extremely flammable and may cause flash fires and engine backfires which may result in injury. Do not spray on hot metal surfaces or when engine is hot. Use plastic extension tube to direct spray to exact location. CARBURETOR AND LINKAGE: With ignition off and engine cool, remove air filter and spray entire exterior surface of carburetor including linkage. After carburetor dries, start engine and spray CRC Clean-R-Carb™ down the carburetor throat to remove the deposits from the lower throttle plate area. AUTOMATIC CHOKES: With engine off, spray CRC Clean-R-Carb™ on both ends of choke valve and corresponding linkages while opening and closing choke by hand. MANIFOLD HEAT CONTROL VALVE: With engine cold, spray CRC Clean-R-Carb™ on both ends of heat control valve shaft. Move counterweight up and down until valve moves freely. If necessary, tap gently with a light hammer to loosen a frozen heat control valve. PCV VALVE: Disconnect crank case side of PCV valve and with engine running spray CRC Clean-R-Carb™ into open end of valve while working the plunger back and forth. IMPORTANT: If spilled or sprayed on painted surface, wipe off or wash off immediately.

Contains acetone 67-64-1, carbon dioxide 124-38-9, and heptanes 142-82-5, 589-34-4, 591-76-4, 617-78-7, 562-49-2.

DANGER: Contents are extremely flammable. Do not smoke while spraying. Extinguish all flames, pilot lights, and heaters. Vapors will accumulate readily and may ignite. Maintain ventilation during use and until vapors are gone. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F/49°C. Exposure to high temperature may cause can to burst. Do not place in direct sunlight or near any heat source. Do not use near open flame or other sources of ignition. Avoid breathing vapor. Avoid contact with skin and eyes. Exposure can cause skin irritation, eye irritation, upper respiratory tract irritation, headache, dizziness, or drowsiness. Product may pose an aspiration hazard if swallowed. Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation, use respiratory protection, or leave the area.

FIRST AID: In case of eye or skin contact, flush with water for 15 minutes. If too much is breathed, remove to fresh air. If swallowed, call your poison control center at 1-800-222-1222.

DISPOSAL: All used and unused product should be disposed of in conformance with local, state, and federal regulations. DO NOT dump in sewers, floor drains, on the ground or into any body of water.

ELECTRICAL SHOCK HAZARD: This metal can will conduct electricity. Keep away from all live electrical sources. Failure to observe this warning may result in serious injury and/or flash fire.

KEEP AWAY FROM CHILDREN



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

©2017 CRC Industries, Inc., Warminster, PA 18974
www.crcindustries.com
Made in U.S.A.

800-521-3168 (Technical Information)
800-272-8963 (Customer Care)
DOT 2Q 17A

Professional users should consult SDS and follow all applicable OSHA regulations.
Los usuarios profesionales deben consultar el HDS y cumplir con todas las regulaciones de OSHA que correspondan.




PLEASE RECYCLE
WHEN EMPTY



Clean-R-Carb™ Carburetor Cleaner

Limpiador de carburador



50 State Formula

Maximizes Performance

**Cleans & Frees: Auto Chokes,
Carb Linkage, Heat Risers, PCV System**

DANGER: EXTREMELY FLAMMABLE. VAPORS MAY CAUSE FLASH FIRES. HARMFUL OR FATAL IF SWALLOWED. CAUSES SKIN AND EYE IRRITATION. CONTENTS UNDER PRESSURE. READ WARNINGS ON BACK PANEL.

Net Wt. 12 oz (340 g)

No. 05379
Item# 1003800