



*Diesel*<sup>™</sup>

# Fuel Therapy<sup>®</sup>

**Diesel Injector Cleaner  
with Anti-Gel**

*Limpiador para Inyectores de Diesel con antigelificante*

- *Provides Top-Tier Clean-Up with Max Treat*
- *Prevents Corrosion while Stabilizing Fuel*
- *Adds Lubricity to Low Sulfur Fuel*

**Treats  
35  
Gals.**

**DANGER:** COMBUSTIBLE. HARMFUL OR FATAL  
IF SWALLOWED. EYE AND SKIN IRRITANT.  
READ WARNINGS ON BACK PANEL.

No. 05412  
Item# 1003806

**12 fl oz (354 mL)**

# FUEL THERAPY® with Anti-Gel

Para obtener información adicional en Español, visite [www.crcindustries.com](http://www.crcindustries.com).

**Emissions reducing formula rated "SUPERIOR" in Cummins L-10 test for injector cleanliness.**

• Increases MPG • Improves Power • Lowers Pour Point • Reduces Smoke • OK for Biodiesel

This product complies with the federal ultra-low sulfur content requirements for use in all diesel motor vehicles and non-road engines. Contains no alcohol. Compatible with all diesel fuels. Improves cold weather starting.

**DIRECTIONS: Read entire label before using this product. To reliquefy gelled fuel:** 1. Remove diesel fuel filter. 2. Fill removed or new filter with FUEL THERAPY Diesel Injector Cleaner Plus w/Anti Gel. 3. Replace fuel filter. 4. Start engine. 5. Allow fuel system to circulate until full power is restored to engine. **For preventive maintenance and biodiesel fuels:** This container is sufficient to treat up to 35 gallons of diesel fuel, depending on fuel temperature. **To lower pour point,** the following ratios are recommended: • One bottle treats 18 gallons of fuel to lower pour point by as much as 35°F and CFPP by 31°F. • One bottle treats 35 gallons of fuel to lower pour point by as much as 15°F and CFPP by 24°F. For anticipated extreme conditions, add CRC DIESEL Cold Flow™ Anti-Gel with Lubricity (No. 05612 / Item# 1003830) to fuel prior to temperature drop. For optimum performance, one bottle treats 18 gallons of fuel.

Contains petroleum distillates/naphtha 64742-80-9, 64742-47-8, 64742-48-9, 64742-94-5, and naphthalene 91-20-3. **DANGER:** Product is combustible and should be kept from heat, open flames, and other ignition sources. Do not store container above 100 °F/ 38 °C. Avoid breathing vapor and contact with skin and eyes. Exposure can cause irritation to eyes, skin, and respiratory tract, headache or dizziness. Product may pose an aspiration hazard if swallowed. Use with adequate ventilation. Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. **FIRST AID:** In case of eye or skin contact, flush with water for 15 minutes. If too much is breathed, remove to fresh air. If swallowed, immediately call your poison control center at 1-800-222-1222. **DISPOSAL:** All used and unused product should be disposed of in conformance with regulations. Do not dump in sewers, floor drains, on the ground, or into any body of water. **KEEP AWAY FROM CHILDREN**



**WARNING: Cancer and Reproductive Harm -**  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

©2018 CRC Industries, Inc., Warminster, PA 18974  
800-272-8963 Customer Care • 800-521-3168 Technical Info

Made in USA 18A  
[www.crcindustries.com](http://www.crcindustries.com)

