



*Diesel*<sup>™</sup>

# Fuel Therapy<sup>®</sup>

**Diesel Injector Cleaner with Anti-Gel**

*Limpiador para Inyectores de Diesel con antigelificante*

- *Provides Top-Tier Clean-Up with Max Treat*
- *Excellent Winter Protection*
- *Adds Lubricity to Low Sulfur Fuel*

**Treats  
500  
Gals.**

**DANGER:** COMBUSTIBLE. HARMFUL OR FATAL  
IF SWALLOWED. EYE AND SKIN IRRITANT.  
READ WARNINGS ON BACK PANEL.

No. 05428  
Item# 1003809

1 Gallon (3.78 L)

# FUEL THERAPY® with Anti-Gel

Para obtener información adicional en Español, visite [www.crcindustries.com](http://www.crcindustries.com).

Emissions reducing formula rated "SUPERIOR" in Cummins L-10 test for injector cleanliness.

- Prevents Fuel Gelling
- Lowers Pour Point
- Adds Lubricity
- Increases MPG
- Cleans Injectors
- Prevents Corrosion
- Improves Power
- Reduces Smoke
- Stabilizes Fuel

This product complies with the federal ultra-low sulfur content requirements for use in all diesel motor vehicles and non-road engines.

CRC DIESEL Fuel Therapy® Diesel Injector Cleaner with Anti-Gel is non-corrosive and contains no alcohol. Compatible with all diesel fuels. Improves cold weather starting. OK for biodiesel.

**DIRECTIONS:** *Read entire label before using this product.*

**To reliquefy gelled fuel:** 1. Remove diesel fuel filter. 2. Fill removed or new filter with FUEL THERAPY Diesel Injector Cleaner Plus w/Anti Gel. 3. Replace fuel filter. 4. Start engine. 5. Allow fuel system to circulate until full power is restored to engine.

**For preventive maintenance and biodiesel fuels:** This container is sufficient to treat up to 500 gallons of diesel fuel, depending on fuel temperature. **To lower pour point,** the following ratios are recommended: (For biodiesel fuels, use 200 gallon treat.)

- One bottle treats 200 gallons of fuel to lower pour point by as much as 35°F and CFPP by 31°F.
- One bottle treats 500 gallons of fuel to lower pour point by as much as 15°F and CFPP by 24°F.

For anticipated extreme conditions, add CRC DIESEL Cold Flow™ Anti-Gel with Lubricity (No. 05632 / Item# 1003794) to fuel prior to temperature drop.

For optimum performance, one bottle treats 200 gallons of fuel.

Contains petroleum distillates/naphtha 64742-80-9, 64742-47-8, 64742-48-9, 64742-94-5, and naphthalene 91-20-3.

**DANGER:** Product is combustible and should be kept from heat, open flames, and other ignition sources. Do not store container above 100 °F/ 38 °C. Avoid breathing vapor and contact with skin and eyes. Exposure can cause irritation to eyes, skin, and upper respiratory tract and headache or dizziness. Product may pose an aspiration hazard if swallowed. Use with adequate ventilation. Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal.

**FIRST AID:** In case of eye or skin contact, flush with water for 15 minutes. If too much is breathed, remove to fresh air. If swallowed, immediately call your poison control center at 1-800-222-1222.

**DISPOSAL:** All used and unused product should be disposed of in conformance with local, state, and federal regulations. Do not dump in sewers, floor drains, on the ground, or into any body of water.

**KEEP AWAY FROM CHILDREN**

 **WARNING: Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).**

©2018 CRC Industries, Inc., Warminster, PA 18974  
800-272-8963 Customer Care  
800-521-3168 Technical Info



[www.crcindustries.com](http://www.crcindustries.com)  
Made in USA

18A

