



FUEL THERAPY[®] with Anti-Gel

■ LOWERS POUR POINT & CFPP ■ RELIQUFIES GELLED FUEL

No. 05455
Item# 1003812



05455

NET WEIGHT 363 lb (164 kg)



DANGER

Flammable liquid and vapor. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. Harmful if inhaled. May cause drowsiness or dizziness. Suspected of causing genetic defects. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure.

PRECAUTIONARY STATEMENTS

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist or vapor. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying, if you experience any symptoms listed on this label, increase ventilation or leave the area. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Keep cool. Do not store container above 100 °F/38 °C. Store in a well-ventilated place. Store locked up. Dispose of contents/container in accordance with local/regional/national regulations.

DIRECTIONS: Read entire label before using this product.

For preventative maintenance and to lower pour point by as much as 15°F and CFPP by 24°F: 5 gallons treat 2500 gallons. To lower the pour point by as much as 35°F and CFPP 31°F and for biodiesel fuels: 5 gallons treats 1000 gallons. For anticipated extreme conditions, add CRC Diesel Cold Flow™ Anti-Gel with Lubricity (No. 05632 / Item# 1003794) to fuel prior to temperature drop.

This diesel fuel additive complies with the federal ultra-low sulfur content requirements for use in all diesel motor vehicles and non-road engines.

- Cleans Injectors
- Adds Lubricity
- Increases MPG
- OK for Biodiesel

Contains hydrodesulfurized middle distillates 64742-80-9, hydrotreated light distillates 64742-47-8, hydrotreated heavy naphtha 64742-48-9, heavy aromatic solvent naphtha 64742-94-5, and naphthalene 91-20-3.

©2018 CRC Industries, Inc.
885 Louis Dr.
Warminster, PA 18974
800-521-3168 (Technical information)
800-272-4620 (Customer Care)
www.crcindustries.com
18A Made in U.S.A.
FOR EMERGENCIES CALL CHEMTREC
1-800-424-9300

Batch No.:
Date Code:



 **WARNING: Cancer and Reproductive Harm**
- www.P65Warnings.ca.gov