



*Diesel*<sup>TM</sup>

**Bio-Con**<sup>TM</sup>

**Sludge Sediment Remover**

- *Improves Storage Stability of Fuel*
- *Great for Storing Tractors, Mowers, Snowblowers & 2-Cycle Engines*
- *Absorbs Moisture*

*Treats*  
**50**  
*Gals.*

**DANGER:** COMBUSTIBLE, HARMFUL OR FATAL  
IF SWALLOWED, EYE AND SKIN IRRITANT.  
READ WARNINGS ON BACK PANEL.

No. 05557  
Item# 1003825

**12 fl oz (354 mL)**

# BIO-CON™ Sludge Sediment Remover

Para obtener información adicional en Español, visite [www.crcindustries.com](http://www.crcindustries.com).

**Bio-Con™ removes sludge sediment from diesel fuel and furnace oils. Absorbs and disperses moisture. Controls the corrosion of steel and aluminum while removing fuel sludge and sediment and improving storage stability. Eliminates hard starting. Keeps fuel tank, lines and filters clean.**

*This product does not comply with the federal ultra-low sulfur content requirements for use in model year 2007 and newer diesel motor vehicles or model year 2011 and newer diesel non-road equipment engines.*

## **DIRECTIONS: Read entire label before using this product.**

1. To ensure uniform dispersion, add Bio-Con when tank is half filled. Use entire contents at once. One container treats 50 gallons of diesel fuel. As an initial treatment, use 2 containers to clean the system more rapidly.
2. Once cleaned, one container every third or fourth tankful is sufficient to maintain cleanliness.

Contains diesel fuel 64742-80-9, 2-butoxyethanol 111-76-2, diethylene glycol monomethyl ether 111-77-3, and benthiazole 21564-17-0. **DANGER:** Avoid breathing vapor and contact with skin and eyes. Exposure can cause irritation to eyes, skin, and respiratory tract, allergic skin reaction, headache or dizziness. Product may pose an aspiration hazard if swallowed. Use with adequate ventilation. Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Product is combustible and should be kept from heat, open flames, and ignition sources. Do not store container above 100 °F/ 38 °C. **FIRST AID:** In case of eye or skin contact, flush with water for 15 minutes. If too much is breathed, remove to fresh air. If swallowed, immediately call your poison control center at 1-800-222-1222. **DISPOSAL:** All used and unused product should be disposed of in conformance with regulations. Do not dump in sewers, floor drains, on the ground, or into any body of water. **KEEP AWAY FROM CHILDREN**



**WARNING: Cancer and Reproductive Harm -**  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

©2018 CRC Industries, Inc., Warminster, PA 18974  
800-272-8963 Customer Care • 800-521-3168 Technical Info

Made in USA 18A  
[www.crcindustries.com](http://www.crcindustries.com)

**SILCO**



2

7825405557

0