

## MAF Sensor Cleaner

Para obtener información adicional en Español, visite [www.crcindustries.com](http://www.crcindustries.com).

### DIRECTIONS: Read entire label before using this product.

1. Do not apply while equipment is energized. Turn off vehicle. 2. Locate your MAF between the air box and throttle body. 3. Unplug MAF wire harness. 4. Remove MAF housing. 5. Place shop towel under MAF to catch any run-off. 6. With straw attached, apply 10-15 sprays of CRC MAF SENSOR CLEANER onto hot-wires or hot plate. DO NOT contact hot-wires with straw or any other object. 7. Be sure to spray all sides of the MAF sensor and clean all wires and connectors. 8. Reassemble MAF and allow to dry thoroughly before reactivating. 9. For best results clean your mass air flow sensor every time you clean or change your air filter. 10. DO NOT use on vehicles with a Karman-Vortex air flow sensor, e.g. Toyota Supra Turbos, Mitsubishi's and most Lexus vehicles.

### QUICK DRYING FORMULA. SAFE TO USE ON MOST SENSORS & CONNECTORS!

Contains isohexane 107-83-5, 64742-49-0, 110-54-3, carbon dioxide 124-38-9, 2,2,4-trimethylpentane 540-84-1. **DANGER:** Contents extremely flammable. Do not smoke while spraying. Extinguish all flames, pilot lights, and heaters. Do not apply while equipment is energized. Vapors will accumulate readily and may ignite. Maintain ventilation during use and until vapors are gone. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F/49°C. Exposure to high temperature may cause can to burst. Do not place in direct sunlight or near any heat source. Avoid breathing vapor. Avoid contact with skin and eyes. Exposure can cause skin or eye irritation, upper respiratory tract irritation, headache, dizziness, or drowsiness. Product may pose an aspiration hazard if swallowed. Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. **FIRST AID:** In case of skin or eye contact, flush with water for 15 minutes. If too much is breathed, remove to fresh air. If swallowed, call your poison control center at 1-800-222-1222. **DISPOSAL:** All used and unused product should be disposed of in conformance with local, state, and federal regulations. Do not dump in sewers, on the ground, or into any body of water. **ELECTRICAL SHOCK HAZARD:** This metal can will conduct electricity. Keep away from all live electrical sources. Failure to observe this warning may result in serious injury and/or flash fire.

**KEEP AWAY FROM CHILDREN**



**WARNING:** Reproductive Harm-[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

©2017 CRC Industries, Inc., Warminster, PA 18974  
[www.crcindustries.com](http://www.crcindustries.com)

Made in U.S.A. 17A

800-521-3168 (Technical Information)  
800-272-8963 (Customer Care)



PLEASE RECYCLE  
WHEN EMPTY



# Mass Air Flow Sensor Cleaner

Limpiador del sensor de flujo de aire



Safe for delicate  
hot wire, hot plate  
& plastic

*Evaporates in Seconds*

**Increases MPG & Fuel Economy**  
**Proven to Gain 4-10 HP at the Wheels**

**DANGER:** EXTREMELY FLAMMABLE. HARMFUL  
OR FATAL IF SWALLOWED. CAUSES SKIN AND EYE  
IRRITATION. CONTENTS UNDER PRESSURE.  
READ WARNINGS ON BACK PANEL.

Net Wt. 4.5 oz (127 g)

No. 05610  
Item# 1003828