




COLD FLOW™ Anti-Gel with Lubricity

■ LOWERS POUR POINT BY UP TO 40°F ■ PREVENTS DIESEL FUEL GELLING

No. 05655
Item# 1003839



NET WEIGHT 390 lb (176 kg)



DANGER

Flammable liquid and vapor. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. Harmful if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness. Suspected of causing cancer. Suspected of damaging the unborn child. May cause damage to organs (auditory system, central nervous system, kidney, liver, peripheral nervous system) through prolonged or repeated exposure.

PRECAUTIONARY STATEMENTS

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe the mist or vapor. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Dispose of contents/container in accordance with local/regional/national regulations. In case of fire: Do not use water jet as an extinguisher, as this will spread the fire.

This diesel fuel additive complies with the federal ultra-low sulfur content requirements for use in all diesel motor vehicles and non-road engines.

- Concentrated Anti-Gel
- Lowers CFPP
- Disperses Water
- OK for Biodiesel

Contains xylene 1330-20-7, ethylbenzene 100-41-4, heavy aromatic solvent naphtha 64742-94-5, toluene 108-88-3, 1,2,4-trimethylbenzene 95-63-6, naphthalene 91-20-3, oleic acid 112-80-1, cumene 98-82-8, and alkylamine 94-91-7.

©2018 CRC Industries, Inc.
885 Louis Dr., Warminster, PA 18974
800-521-3168 (Technical information)
800-272-8963 (Customer Care)
www.crcindustries.com
18A Made in U.S.A.
FOR EMERGENCIES CALL CHEMTREC
1-800-424-9300

Batch #:
Date Code:



FIRST AID

If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If exposed or concerned: Get medical advice/attention.

Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. For additional information, consult SDS for this product.

DIRECTIONS: Please read entire label before using this product.

Before outside temperature drops to 50°F (10°C), add one gallon CRC Premium Anti-Gel w/ Lubricity to each 1000 gallons of diesel or biodiesel fuel to obtain maximum pour point reduction. Depending on type of fuel, pour point can be lowered by as much as 40°F & CFPP by 25°F. For optimum treat of biodiesel fuels or to help treat fuel mildly gelled, add two or three gallons Anti-Gel per 1000 gallons of diesel fuel. Mix thoroughly. Change fuel filter. Usage in excess of recommended quantity will not be harmful.