

Jump Start® Starting Fluid

Para obtener información adicional en Español, visite www.crcindustries.com.

CRC JUMP START Starting Fluid is approved for use in gasoline and diesel engines in autos, trucks, motorcycles, marine outboard motors, lawn and garden equipment, construction equipment and more. This product complies with the federal ultra-low sulfur content requirements for use in all diesel motor vehicles and non-road engines.

- Contains 20% ether content
- Effective at temperatures as low as -65°F
- Prolongs battery and starter life and reduces engine wear
- Lubricates upper cylinders and protects against rust

IMPORTANT: STARTING FLUID SHOULD NOT BE USED IN DIESEL VEHICLES EQUIPPED WITH GLOW PLUGS.

DIRECTIONS: Read entire label before using this product.

Hold can in an upright position. With engine off, spray once or twice into air intake system (air cleaner, carburetor or intake manifold). Crank engine and, if necessary, continue to spray while engine is being turned over until it begins to run smoothly. Do not flood engine before using. Do not use with glow plugs.

Contains heptane 426260-76-6, diethyl ether 60-29-7, carbon dioxide 124-38-9, ethanol 64-17-5, and chloroethane 75-00-3.

DANGER: Contents extremely flammable. Do not smoke while spraying. Extinguish all flames, pilot lights, and heaters. Do not apply while equipment is energized. Vapors will accumulate readily and may ignite. Maintain ventilation during use and until vapors are gone. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F/49°C. Exposure to high temperature may cause can to burst. Do not place in direct sunlight or near any heat source. Avoid breathing mist or vapor. Avoid contact with skin and eyes. Exposure can cause skin or eye irritation, upper respiratory tract irritation, headache, dizziness, or drowsiness. Product may pose an aspiration hazard if swallowed. Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area.

FIRST AID: In case of skin or eye contact, flush with water for 15 minutes. If too much is breathed, remove to fresh air. If swallowed, call your poison control center at 1-800-222-1222.

DISPOSAL: All used and unused product should be disposed of in conformance with local, state, and federal regulations. Do not dump in sewers, on the ground, or into any body of water.

ELECTRICAL SHOCK HAZARD: This metal can will conduct electricity. Keep away from all live electrical sources. Failure to observe this warning may result in serious injury and/or flash fire.

KEEP AWAY FROM CHILDREN

WARNING: Cancer and Reproductive Harm-www.P65Warnings.ca.gov.



Jump Start®

Starting Fluid with Lubricity

For Gas & Diesel Engines

LÍQUIDO DE ARRANQUE CON LUBRICANTE
PARA MOTORES A GASOLINA Y DIESEL

Effective to -65°F

**Prolongs Starter Life
Lubricates Upper Cylinders**

DANGER: EXTREMELY FLAMMABLE. HARMFUL OR FATAL
IF SWALLOWED. VAPOR HARMFUL. MAY IRRITATE SKIN.
CONTENTS UNDER PRESSURE. READ WARNINGS ON BACK PANEL.

Net Wt. 11 oz (311 g)

**No. 05671
Item# 1003843**



PLEASE RECYCLE
WHEN EMPTY

