



Marine

Dry Lube

WITH PTFE TECHNOLOGY

Lubricante seco para uso marino
con tecnología PTFE

Micro-Thin Film Penetrates
& Bonds to Surface

*Película microscópica que penetra y se
adhiera a la superficie*

Reduces Friction & Drag
Reduce la fricción y el arrastre

Net Wt. 10 oz (283 g)


No. 06114
Item# 1003917

**DANGER: FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED.
EYE AND SKIN IRRITANT. CONTENTS UNDER PRESSURE.**

Read warnings on back panel.



PLEASE RECYCLE
WHEN EMPTY



Dry Lube with PTFE Technology

Para obtener información adicional en Español, visite www.crcindustries.com.

CRC® MARINE DRY LUBE WITH PTFE Technology penetrates and bonds to aluminum, metals, wood, rubber, plastic and most surfaces. Seals out moisture and helps prevent corrosion.

Great for rigging, mast and sail tracks, rudders, daggerboards or centerboards, tools, deck hardware, hinges, zippers, fishing reel components and more!

DIRECTIONS: Read entire label before using this product. Do not apply while equipment is energized. Shake can well before use. Spray in light, even coats on a clean, dry surface. Do not apply to hot surfaces. Allow 10-15 minutes to dry, or 24 hours for best results. Reapply as needed.

Contains liquefied petroleum gas 68476-86-8, isopropyl alcohol 67-63-0, hydrotreated light naphtha 64742-49-0, 2-methylpentane 107-83-5, titanium tetrabutanolate 5593-70-4, and n-hexane 110-54-3.

DANGER: Contents are flammable. Do not smoke while spraying. Do not use near open flame or other sources of ignition. Do not apply while equipment is energized. Vapors will accumulate readily and may ignite. Maintain ventilation during use and until vapors are gone. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F/49°C. Exposure to high temperature may cause can to burst. Do not place in direct sunlight or near any heat source. Avoid breathing vapor. Avoid contact with skin and eyes. Exposure can cause skin, eye, or upper respiratory tract irritation, headache, dizziness, or drowsiness. Product may pose an aspiration hazard if swallowed. Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation, use respiratory protection, or leave the area. When exposed to extreme heat or hot surfaces, vapors may decompose to harmful or fatal corrosive gases such as hydrogen fluoride.

FIRST AID: In case of eye or skin contact, flush with water for 15 minutes. If too much is breathed, remove to fresh air. If swallowed, call your poison control center at 1-800-222-1222.

DISPOSAL: All used and unused product should be disposed of in conformance with local, state, and federal regulations. DO NOT dump in sewers, floor drains, on the ground or into any body of water.

ELECTRICAL SHOCK HAZARD: This metal can will conduct electricity. Keep away from all live electrical sources. Failure to observe this warning may result in serious injury and/or flash fire.

KEEP AWAY FROM CHILDREN



WARNING: Reproductive Harm - www.P65Warnings.ca.gov.

©2018 CRC Industries, Inc., Warminster, PA 18974
800-521-3168 Technical Information
800-272-8963 Customer Care

18A
Made in U.S.A.
www.crcindustries.com