DIRECTIONS: Read entire label before using this product

Do not apply while equipment is energized. Cover and protect plastic surfaces for overspray. Check on small area before using. Not for automotive interiors. Use extension tube for pippoint accuracy.

Contains acetone 67-64-1, hydrocarbon propellant 68476-86-8, heptanes 142-82-5, 589-34-4 methylcyclohexane 108-87-2 and polydimethylsiloxane 63148-62-9

DANGER: Contents are extremely flammable. Do not smoke while spraying. Extinguish all flames, pilot lights, and heaters. Do not apply while equipment is energized. Vapors will accumulate readily and may ignite. Maintain ventilation during use and until vapors are gone. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above $120^{\circ}F/49^{\circ}C$. Exposure to high temperature may cause can to burst. Do not place in direct sunlight or near any heat source. Avoid breathing vapor or contact with skin and eyes. Overexposure to liquid or vapors can cause serious eye or skin irritation, irritation to upper respiratory tract, headache, dizziness, or drowsiness. Product may pose an aspiration hazard if swallowed. Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area.

FIRST AID: In case of eye or skin contact, flush with water for 15 minutes. If too much is breathed, remove to fresh air. If swallowed, call your poison control center at 1-800-272-1272

DISPOSAL: All used and unused product should be disposed of in conformance with local, state and federal regulations. Do not dump in sewers, on the ground, or into any body of water.

ELECTRICAL SHOCK HAZARD: This metal can will conduct electricity. Keep away from all live electrical sources. Failure to observe this warning may result in serious injury and/or flash fire.

KEEP AWAY FROM CHILDREN

★ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

Made in USA



Scan to watch a quick video on how to take care of your Phantom retractable screens!



SILICONE LUBRICANT

Stops sticking and binding.

Ideal for use on Phantom retractable screens.

1-888-PHANTOM phantomscreens.com



EXTREMELY FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. EYE AND SKIN IRRITANT. CONTENTS UNDER PRESSURE.

READ WARNINGS ON BACK PANEL.

Net Wt. 7.5 oz (212 g)



