



# Battery Terminal Protection Spray

- Lead free formula
- Fights battery corrosion
- Prolongs battery life

Contains Hexane and heptane isomers (64742-49-0, 142-82-5, 107-83-5, 589-34-4, 591-76-4, 426260-76-6, 108-87-2, 617-78-7, 110-54-3), Petrolatum (8009-03-8), Solvent naphtha (64742-89-8), Xylene (1330-20-7), Ethylbenzene (100-41-4) and Liquefied petroleum gas (68476-86-8).

Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. For additional information, consult SDS for this product.

**Electrical Shock Hazard:** This metal can will conduct electricity. Keep away from all live electrical sources. Failure to observe this warning may result in serious injury and/or flash fire.

**Danger:** Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of causing cancer. Suspected of damaging fertility. May cause damage to organs through prolonged or repeated exposure by ingestion.



**Precautionary Statements:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe mist or vapor. Use only outdoors in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Dispose of contents/container in accordance with local/regional/national regulations.

**First Aid:** If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. If exposed or concerned: Get medical attention.

## INSTRUCTIONS

*Read entire label before using this product.*

1. SHAKE SPRAY CAN WELL.
2. Place terminal protectors over battery posts. Connect battery terminal cables.
3. Spray "Battery Terminal Protection Spray" on battery carrier, terminal cables, and battery posts. OLDER BATTERIES: Prepare surface by removing all corrosion, then follow instructions above.
4. For preventive maintenance, apply at least every 3-4 months.
5. When finished spraying, clean valve by turning can upside down and depressing actuator until only propellant escapes.



**WARNING:** Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

VOC Category: Electrical Coating | MIR Limit: 2.0



NET WT. 10 oz (283 g)

Read warnings on back panel.

**DANGER: EXTREMELY FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. MAY CAUSE EYE OR SKIN IRRITATION. CONTENTS UNDER PRESSURE. KEEP AWAY FROM CHILDREN.**



PROUDLY MADE IN USA