

ETERNABOND

EternaClean™ Non-Chlorinated Formula removes grease, oil, oxidation and other contaminants from roof surfaces prior to application of EternaBond® tapes.

WORKS ON MOST ROOF SURFACES AND MANY TYPES OF CONSTRUCTION SURFACES

Hypalon Granulate TPO EPDM
Fiberglass Metal Copper

DIRECTIONS: Read entire label before using this product.
Follow all directions in numerical order.

1. Test on a small area before using. 2. Use caution on painted surfaces.
3. Wet down surfaces to be cleaned using short bursts of EternaClean™ at a distance of 18-24 inches. Avoid breathing any dust or vapors that may become airborne. (See inhalation warning.) 4. After all surfaces have been wetted, continue spraying EternaClean™ to remove contaminants. 5. Wipe with a clean cloth, turning often.
6. For heavy deposits, repeat application as necessary. 7. Runoff should be collected and disposed of properly. (See disposal statement.) 8. For plastic surfaces (TPO, Hypalon, Etc.), score with sand cloth or Scotch-Brite pad before spraying.

Professional users should consult SDS and follow all applicable OSHA regulations.

Contains acetone 67-64-1, carbon dioxide 124-38-9, 3-methylhexane 589-34-4, methylcyclohexane 108-87-2, n-heptane 142-82-5 and cyclohexane 110-82-7.

DANGER: Contents are extremely flammable. Do not smoke while spraying. Extinguish all flames, pilot lights, and heaters. Do not apply while equipment is energized. Vapors will accumulate readily and may ignite. Maintain ventilation during use and until vapors are gone. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F/49°C. Exposure to high temperature may cause can to burst. Do not place in direct sunlight or near any heat source. Avoid breathing vapor. Avoid contact with skin and eyes. Overexposure can cause serious eye and skin irritation, upper respiratory tract irritation, headache, dizziness, or drowsiness. Product may pose an aspiration hazard if swallowed. Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation, use respiratory protection or leave the area.

FIRST AID: In case of eye or skin contact, flush with water for 15 minutes. If too much is breathed, remove to fresh air. If swallowed, call your poison control center at 1-800-222-1222.

DISPOSAL: All used and unused product should be disposed of in conformance with local, state and federal regulations. DO NOT dump in sewers, floor drains, on the ground or into any body of water.

ELECTRICAL SHOCK HAZARD: This metal can will conduct electricity. Keep away from all live electrical sources. Failure to observe this warning may result in serious injury and/or flash fire.

KEEP AWAY FROM CHILDREN



WARNING: Cancer and Reproductive Harm -
www.P65Warnings.ca.gov.

EternaBond Inc.
4401 Page Ave., Michigan Center, MI 49254
800-248-4010 • www.EternaBond.com

No. 09945 18A
Made in U.S.A.

ETERNABOND

EternaClean™



• Works Fast

• Dries Fast

• Non-Chlorinated



**Removes Oxidation,
Tree Sap, Grime,
Grease and Oil
Leaves No Residue
Low VOC Formula**

DANGER: EXTREMELY FLAMMABLE.
VAPORS MAY CAUSE FLASH FIRES. HARMFUL
OR FATAL IF SWALLOWED. EYE AND SKIN
IRRITANT. CONTENTS UNDER PRESSURE.
READ WARNINGS ON BACK PANEL

Net Wt. 14 oz (396 g)



PLEASE RECYCLE
WHEN EMPTY

